Review paper on Radioactive Wastes and its Management.

Sanjogta Meshram[a], Siddhant Binani[b], Mrunal Mohatkar[b], Shubhangi Bokde[b], Prachi Shahu[b], Sulbha Rathi[b], Sahil Chopkar[b]

[a*]Assistant Professor, Department of Chemistry, Shri Ramdeobaba College of Engineering and Management,

Nagpur.

[b]Department of Industrial Engineering, Shri Ramdeobaba College of Engineering and Management, Nagpur.

Abstract

The waste that is left over after the use of radioactive materials in atomic reactors or at some point after the progress of atomic weapons is known as radioactive waste. Since the use of radioactive substances has been completed on a large scale in recent years, resulting in the creation of a big amount of radioactive waste, radioactive material management has become an important stage in dealing with it. Even if not correctly implemented, light from radioactive material will cause problems for humans and the climate.

The peer-review paper discusses a well-known assessment of globally nuclear waste research. The cutting-edge evaluation includes studies on protection tests, decommissioning and disinfection of nuclear power plants, fusion power plants, and haulage. Furthermore, the evaluation emphasizes radioactive wastewater remediation, its management and final disposal alternatives for consumed petroleum and waste materials, by keeping in mind its effects on ecology due to radio radioactive isotope mobility in the ecology.

Keywords : *Radioactive waste;Waste management;Ion exchange;Cementation;polymerization;*

DOI Number: 10.14704/nq.2022.20.9.NQ44235 **Neuro Quantology 2022; 20(9):2038-2044**

1 Introduction

As a by-product, nuclear reactors, fuel processing facilities, health centres, and research centres all generate radioactive (or nuclear) waste. Radioactive waste is generated during the deactivation and dismantling of nuclear reactors and other nuclear installations. (Nayak, 2020)(De 2012). Also be stated as a form of unsafe trash that incorporates radioactive materials is called as radioactive waste. Radio-active wastes are produced at some stage of manufacturing of nuclear drug and exploration institute. During fission of nuclei like 235U, 239Pu large amount of energy and radioactive elements releases which can be controlled in nuclear power plant reactors through the fission reaction(De *et al.*, 2012). In case of 'atom' and 'hydrogen' (thermonuclear) bombs releases vast energy in uncontrolled manner. During different industrial processes, like nuclear industry, one gets hazardous wastes. Government authorities regulate the storage and disposal of radioactive waste for the protection of human health and the environment. Radioactive wastes are results into different forms of wastes. (K. Raj, K. P. (2006). Radioactive liquid waste is classified into three types: low-level waste (37-3.7 106 Bq/L), intermediate-level waste (3.7 106-3.7 1011 Bq/L), and high-level waste (above 3.7 1011 Bq/L) (K. Raj, K. P. (2006). Solid radioactive waste materials are also categorised based on their physical properties. (Raj, Prasad and Bansal, 2006).

1.1 Sources

There are many different sources of radioactive waste. The nuclear fuel cycle and nuclear weapons reprocessing generate the vast majority of waste in countries with nuclear power plants, nuclear weaponry. The others are medicinal waste i. e. β particle and gamma ray emitters, industrial waste, coal and naturally occurring radioactive material (Nikunj Khelurkar, 2015).

1.2 Classification of Radioactive waste

Classification of radioactive waste differ from country to country. Radioactive Waste Safety Standards (RADWASS), also plays a vital role. Percentage of different kinds of waste generated in the UK:

low-level waste (LLW) - 4%

intermediate-level waste (ILW) ~6%

high-level waste (HLW) - <1% (Nikunj Khelurkar, 2015)

Figure 1 represent the different steps of radioactive waste treatment used in India Only a few examples include waste description, diagnosis, conditioning, stockpiling, disposal, and surveillance/monitoring. Depending on the physical form of the waste, various treatment, conditioning, stockpiling, and safe disposal are also listed. The descriptions provided here are general in nature, and they relate to hazardous waste management from mining and milling, fuel manufacturing, nuclear power generation, medical and commercial use of radioactive substances, and ecological sustainability.



Figure 1 Management of Radioactive Waste

1.3 Storage

Radioactive waste should be stored in such a state which allows its isolation, environmental protection, and monitoring, as well as treatment, conditioning, and disposal measures. Storage of radioactive waste is used for a variety of reasons, including decay and subsequent release of short-lived radionuclides, and storage of high-level radioactive waste for thermal concerns. Storage may be used for economic or policy reasons in other circumstances.

1.4 Cause for Concern

Natural or man-made radioactive waste can expose individuals to radioactive material in a number of ways. The most common ways radioactive materials enter the body are through exposure, inhalation of these substances or the through food. Natural radiation, such as that produced by the Sun as well as stars, radioactive materials in minerals and soil, radio nuclides incorporated into our bodies' tissues is constantly emitted by all people on Earth. We are also subjected to radiation exposure from man-made sources, most noticeably X-ray diagnostics. The radiation therapy targeted tissues are mainly the ones that are affected by the radiation. Radiation effects can be categorised as physical and genetic effects. The person exposed to the toxin will experience physical effects. Delayed physical effects occur.

The exposed person experiences physical symptoms. Somatic effects on the body that are due to a mental disorder can lead to cancer and cataracts. Skin burns, nausea, loss of hair, temporary infertility, and blood alteration are all possible side effects of acute radiation. Severe chronic effects include ocular cataracts as well as cancer development. Genetic effects include damage to reproductive cells in the exposed person's future generations, which is less risky than somatic effects. To put the situation in context, it must be observed that nuclear power plants are handled with many radiological protection controls in place. Second, "a 1000 MW coal-fired power station emits nearly 6 million tonnes of greenhouse gases, 500,000 tonnes of SOx and NOx mixtures, and nearly 320,000 tonnes of ash into the atmosphere."

1.4 Prevention

Generation IV reactors produce less waste per unit of energy generated, so in the future, reactors will be phased out in favor of these more efficient machines. The Nuclear Decommissioning Authority of the United Kingdom has a position paper on advances in approaches to the management of separated plutonium that was based on the findings of work that the Nuclear Decommissioning Authority shared with the UK government.

2 Radio-active waste management.

After garbage generation, the first step in waste management is pre-treatment of waste. This first stage of the waste management process can help to separate different waste streams and provide an opportunity for recycling as regular nonradioactive trash when the proportions of radioactive substances present are free from regulatory constraints. The process allows for the separation of radioactive waste, which can be used for near-surface or geological burial.

2.1 Treatment of Gaseous waste

All nuclear plants must have an effective off-gas cleaning system in order to manage and reduce activity discharge via the air route in accordance with the ALARA principle. The selected radiation protection system is based on the specific activity, kind of radioactive material, particle density and size distribution and concentrations, and other factors. Integrated particle and liquid production, testing and supply of I_2 filters are widely used in nuclear power plant emergency air purification systems. In addition, ruthenium adsorbers using perchloric acid (PERCOSIB)-treated silica bricks, particulate respirators, charcoal-impregnated sampling filters are in use. Nuclear reactor operations are a crucial part of ensuring safe and successful nuclear power plants.

2.2 Chemical treatment

The clariflocculator sludge is concentrated further by decanting, filtering, and centrifuging. The radioactive material in a waste disposal site is made up of solids. The liquid waste originally contains immobilized materials within the cement matrix.

2.3 Ion exchange

The ion selective process is employed to different radionuclides. The intermediate-level waste is separated into two streams as a result of this treatment: a tiny amount of high-level radioactive material and a huge portion of low-level radioactive material, each of which is treated and released into the environment. Tarapur currently has an ion exchange plant in process (Kulkarni et al., 1996). Trombay has recently exhibited the successful deployment of a new transportable protected ion exchange power station (Ozarde et al., 2002). This method employs resorcinol formaldehyde polycondensate resin to achieve a high throughput of 400 L per hour waste processing.

To remove 90Sr, an iminodiacetic acid resin is used.

2.4 Cementation

The cementation process provides significant advantages due to its minimal cost and simplicity, as well as its ability to produce high-quality products. (K. Raj, 2006). Special type of cement is developed in India by mixing it with suitable additives to enhance characteristics. There are cementation facilities that use reusable agitators to condition radioactive waste. The cementation process has also been used in some cases to immobilize intermediate level waste in situ.

2.5 Polymerization

In India, polyester styrene has been chosen and is being used to immobilize LLW concentrates and wasted ion exchange resin from nuclear power plants and other facilities. A cone mixer in use at WIP in Trombay. A 90 kg resin batch is moved to a specifically built product drum that is kept on a load cell. The vacuum dewatering system removes any excess water followed by installation of mixing assembly on the product drum.

Premixed with an optimal concentration of accelerator (dimethyl aniline) and catalyst, the required amount of benzoyl peroxide is used.



Figure 2 Process for vitrification of high-level radioactive liquid waste.

2.6 Management of high-level liquid waste

Evaporation is used to concentrate HLW produced during spent nuclear fuel reprocessing, which is then stored in stainless steel tanks. These storage tanks should be maintained at a low temperature and constantly monitored. Liquid storage in stainless steel tanks is only a band-aid solution, and India has executed a three-step strategy for HLW management. This process requires the fixation of waste iron oxide containers of the conditioned refuse under continuous cooling, and disposal in deep geological formations. To avoid exposure of any radiation to the public during transportation, the HLW management facility is co-located near a reprocessing plant. Pumping HLW from the reprocessing plant to the vitrification plant is a difficult task. A secondary stainless-steel pipe surrounds the primary stainless-steel pipe used for waste transfer, and this outer pipe is shielded from its surroundings by a stainless-steel box.

2.6 Processes to treat HLW

2.6.1 The TRUEX process

Two carbamoyl organophosphorus extractants have been thoroughly tested for their effectiveness in removing all actinides from HNO3 waste solutions on a plant scale: one uses the superior extractant octyl(phenyl)-N,N-diisobutylcarbamoyl, and the other uses the well-studied dihexylN,N-diethylcarbamoylmethylphosphonate (CMP) (CMPO).

It has been created to employ CMPO that has been dissolved in the PUREX process solvent to extract trans-uranic elements from nitric acid waste (TBP in normal paraffin hydrocarbon). Trans-uranic elements can be extracted from nitric acid wastes using CMPO. 2,3 TRUEX is a method that may significantly lower TRU concentrations in waste solutions that contain various quantities of nitric acid, salt, and fission product. A crucial component is that the technique is easily adaptable for waste processing in current fuel reprocessing facilities.



CMP



CMPO

Figure 3 Structures of dihexyl-N,N-diethylcarbamoylmethylphosphonate (CMP) and octylphenyl-N,N-di isobutyl carbamoyl methyl phosphine oxide (CMPO)

A new generic actinide extraction and recovery method called TRUEX is suggested in a review paper as a means of removing all actinides from acidic $NO3^-$ and Cl^- nuclear waste solutions. For the purpose of predicting the TRUEX process's applicability in actinide partitioning in HLLW from the PUREX process, some counter-current studies have also been conducted. According to the findings, the major actinides had decontamination factors higher than 103. An extraction chromatographic approach using CMPO adsorbed on Chromosorb-102 has also been tested as an alternative to the TRUEX solvent extraction process to recover minor actinides from high activity waste solutions of PUREX origin.

In order to reduce extractant and solvent waste, the Los Alamos National Laboratory developed a membrane based on the TRUEX technique. The TRUEX process fluid contains trivalent lanthanides alongside actinides, necessitating the separation of lanthanides from actinides. SETFICS (Solvent Extraction for Trivalent f-Elements Intragroup separation in CMPO-complexant System) is a procedure that has been designed to accomplish this goal. (K. Nash, 2010). The recovery of Am and Cm from acidic waste solutions as well as the separation of trivalent actinides and lanthanides have been accomplished using the SETFICS method, a version of the TRUEX process K. Nash, J. B. (2010). Trivalent actinides are selectively stripped using a solution of diethylenetriamine-N, N, N, N, N, N-pentaacetic acid (DTPA)-NaNO3 using the general TRUEX solvent as the extraction reagent. The tris-CMPO ligand system has been used by certain researchers to separate actinides and lanthanides.

To improve the selectivity of actinide extraction over lanthanide extraction, a ligand with three preorganized CMPO moieties attached onto a stiff (3)-symmetric triphenoxymethane platform has been designed. This ligand's solutions were used to extract simulated nuclear waste streams, and the results showed a strong affinity for actinide thorium and a weak, but consistent, affinity for lanthanides. The TRUEX method has been tested to remove actinides from a variety of acidic waste streams, including liquid Na-bearing wastes that have high levels of Hg. The ability of Hg to be extracted into and stripped from the solvent is demonstrated by successive extraction batch contacts with the Hg spiked waste and successive scrubbing and stripping batch contacts with the Hg loaded TRUEX solvent. The distribution behavior of Mo (VI) under the circumstances of the TRUEX and PUREX procedures has been investigated in order to compare the outcomes. Molybdenum is less extractable under PUREX settings, however larger molybdenum distribution ratios are seen under TRUEX process conditions. Oxalic acid was found to effectively reduce molybdenum extraction when TRUEX was utilized.

2.6.2 The DIAMEX process

This process involves the use of diamides for the extraction of actinides from HLW nitric acid solutions. The main advantage claimed is the use of CHON principle, which leads to a minimization of the generation of wastes from extractant. In fact, organophosphorous extractants produce a solid residue that can be avoided by the use of diamides. This approach has been the basis for intense research efforts, tending to improve the diamides design to optimize their extractive performance (Anne Jorden, M. A., 2013).



Figure 4 Structure of N,Ní-dimethyl-N,Ní-dibutyltetradecylmalonamide (DMDBTDMA)

An effective trivalent actinide recovery has been cited as drawbacks of the DIAMEX method.

2.6.3 The DIDPA process

Diisodecylphosphoric acid was used as the technique' primary extractant by Japanese researchers in the late 1980s (DIDPA). Thus, to separate the TRU elements, namely U(VI), Pu (IV), Np (IV), Am(III), Cm(III), and lanthanides from HLW, a mixture of DIDPA and TBP is utilised (III). However, the HLW's acidity must be decreased to 0.5M. Through batch and countercurrent studies, this procedure has already been assessed, and the results showed extremely high actinide extraction profiles. The lanthanides (III) are separated from Am (III) and

Cm (III) using DTPA as a strippant, with the latter being recovered by a 4M HNO3 solution.

Oxalic acid phase is then used as a stripping agent for Np (IV) and Pu (IV), and a Na2CO3 solution is used to strip U(VI) at the end of the process. Using a hydrazine carbonate solution, a further investigation shown that it is possible to back-extract Am(III), Eu(III), Pu(IV), and Np(IV) from DIDPA; the last ion being oxidised to Np(V) during stripping.



Fig.5 Structure of diisodecylphosphoric acid (DIDPA)

Numerous foundational studies have documented the recovery of Nd (III), U(VI), Th (IV), Am (III), and other elements from nitric acid solutions using dialkylphosphoric acids of the di-2- ethylhexylphosphoric acid (D2EHPA) type or synergistic combinations of these acids with neutral phosphorous extractants.

But up until this point, only DIDPA has advanced technologically significantly.

However, a significant amount of research has been done on the use of dialkyldithiophosphinic acids, or Cyanex 301, which are promising extractants that enable effective separation factors for trivalent actinide/lanthanide elements3,19,99 (for further details, see last section).

The necessity for high dilutions and denitration, both of which significantly increase the volume of HLW to be treated, are the principal problems of the DIDPA procedure, and they are essentially comparable to those raised against the TRPO.

2.6.4 The UNEX process

Researchers from the former Czechoslovakia created the UNEX technique before having it put into practise in Russia. The most recent discoveries result from research collaborations between Russian and American scientists. It is based on the utilisation of a synergistic mixture consisting of polyethylene glycol (PEG), diphenylcarbamoylmethylphosphine oxide (a specific CMPO), and the hexachloro derivative of cobalt dicarbolide (CCD), which extracts Cs(I), Sr(II), and a number of actinides and lanthanides from HLW. As a result, PEG helps to increase the extraction of Sr(II), CCD extracts Cs(I), and CMPO extractant is sufficient for the actinide/lanthanide fraction. The solvent was methodically optimised for an effective treatment of particular HLW using a number of batch100 and flowsheet development 101 investigations. When the HLW was diluted with an HF solution to prevent a significant extraction of Fe and Zr instead of Eu, promising results were obtained (III). After retiring Fe and Zr using an HNO3-citric acid solution scrub stage, Cs, Sr, and the actinides/lanthanides were stripped with a guanidine carbonate/DTPA solution. A 2M HNO3 aqueous phase demonstrated to be an effective reagent for the solvent cleanup.

2.7 Management of solid waste

Radioactive solid wastes produced at various stages of the nuclear fuel cycle are present in the larger diversity of materials, sizes, forms, and levels of contamination. According to the radiation field, radioactivity concentration, and type, these wastes are divided into different categories. They are divided into two categories: combustible and non-combustible, and compressible or non-compressible. The majority of the total solid waste is either flammable or compressible and has minimal activity.

3. Conclusion

The problems with managing radioactive waste are severe over the long run. It hasn't been able to comprehend it thus far. Over the past 50 years, the development of solvent extraction techniques has been crucial to the technological advancement of the nuclear sector. As a result, the development of the PUREX process, some of its most recent advancements, and a general overview of all the new technological processes idealized to address the issues related to the disposal of radiotoxic wastes are just a few examples of the significant investment made in this field of knowledge and are reported in this review paper.

The information provided therein makes it quite evident that the nuclear business will continue to employ this established practice. Although there are several emerging alternative technologies to solvent extraction (supported liquid membranes, extraction chromatography, molten salt solutions, magnetic ion exchange resins, etc.), they were mostly developed to coexist with solvent extraction methods in pilot-plant experiments. It has been observed that research on the application of solvent extraction had a significant impact on the creation of all of these methods.

Acknowledgements

The author is thankful to the Management of Shri Ramdeobaba College of Engineering and Management, Nagpur, for providing the necessary research facility. The author is also thankful to Dr Rajesh. S. Pande, Principal, for his constant encouragement and motivation whenever required.

(Bansal, september 30 ,october 04 1991)

References

K. Raj, K. P. (2006). Radioactive Waste Management Practices in India. Nuclear Engineering and Design, 914-930.

K. Nash, J. B. (2010). Challenges for Actinide Separations in Advanced Nuclear Fuel Cycles. *Environmental Science*.

Anne Jorden, M. A. (2013). Improved Understanding of factors that contribute to extraction selectivity. *Inorganic Chemistry*, 3445-3458.

Nikunj Khelurkar, S. S. (2015). International Conference on Technologies for sustainable

Development (ICTSD) 2015. Atomic Energy Regulatory Board. Safety code on establishing a radioactive waste management system. Department of Atomic Energy.

Bansal, N. K., Rastogi, R. C., & Ali, S. S. (1991). Design basis and construction features of shallow land storage and disposal facilities for radioactive solid wastes in India—An overview. In *Proceedings of the International Seminar on Storage and Disposal of Low Level Radioactive Waste*, September 30, October 04. Paris, France.

Samanta, S. K., Kansra, V. P., Sao, D. D., Upadhyaya, T. C., Kansara, H. N., & Katiyar, S. C. (1997). Cesium selective synthetic zeolite for reduction of activity in spent fuel storage pool: Process development and industrial application. In *Proceedings of the Symposium on Advances in Chemical Engineering-97* (ACE-97), October 22–24 (pp. 159–165).

Bhabha Atomic Research Centre.

International Atomic Energy Agency. (1983b). *Conditioning of low and intermediate level radioactive waste, Vienna*, Technical Report Series no. 222 p. 14.

Kulkarni, Y., Samanta, S. K., Bakre, S. Y., Raj, K., & Kumra, M. S. (1996). Process for treatment of intermediate level radioactive waste based on radionuclide separation. In *Proceedings of the Waste Management' 96 Symposium*, Tucson, AZ

Description of Radioactive Waste Disposal in JAPAN., [online] Available: http://www.jaea.go.jp/english/04/ntokai/backend/backend_01_04.html.

Entergy corporation. Indian point energy center. [Online] Entergy corporation., [online] Available: http://www.safesecurevital.com/safe-secure-vital/spent-fuel.html

BARC, DAE, Government of India. Radioactive Waste Management: Indian scenario. Bhabha atomic research centre. [Online] http://www.barc.gov.in/pubaware/nw_n4.html. Entergy corporation. Indian point energy center. [Online] Entergy corporation. http://www.safesecurevital.com/safe-secure-vital/spent.