Processing Model for Efficient Remote Sensing Image Based on Pipeline

Mirzanur Rahman[1], Dr. Parismita Sarma[2]

[1]Assistant Professor, Department of Information Technology, Gauhati University, Guwahati, Assam, India.

[2]Assistant Professor, Department of Information Technology, Gauhati University, Guwahati, Assam, India.

Abstract

Image processing is often a combination of pictures where the input is an image and the output is a collection of an image's properties. This research project has three main contributions, the first of which is the implementation of fundamental parallel processing-based image processing algorithms for satellite image improvement. The model suggests a parallel image processing pipeline and focuses primarily on the current efficacy of remote sensing image processing, which is often not up to standard. In image processing, parallel processing facilitates the division of a large picture into smaller ones. Every activity is often carried out differently under this approach, and each person completes various tasks in their own unique style. The experimental results show the effectiveness of a pipeline-based parallel processing approach in moving remote sensing images along large amounts of data, and the second contribution of this research work is suggesting a new parallel classification methodology using a new clustering and classification concept.

Keywords: *Parallel processing, Remote sensing, Image processing, Pipeline and Enhancement.*

Number: 10.14704/nq.2022.20.9.NQ44322 **Neuro Quantology 2022; 20(9):2757-2769**

1. Introduction

The ultimate goal of a sizable number of image processing methods is to extract important properties from visual data. Here, the mechanism may provide the narrative, analysis, or acceptance of the scenes [1]. Picture processing is the process of altering an active image to conform to a desired behaviour. This system often enables the user to print an image using printer procedures, enabling the user to collect screen images into disc files using a variety of file types. Generally speaking, image processing deals with the alteration and analysis of graphical information, making the human brain and eye the most potent image processing system. The system receives, enhances, and saves photos here very quickly [2]. The main goal of image processing is to enhance or statically estimate a number of aspects that are not consciously detectable in the original form of a picture [3]. Although it does not provide any more information content, the essential standard of image processing procedures is completed, allowing for better perception and vision to be used. This goal is achieved by processing that is improved and performed well, both of which require operating on pictures [4]. Although humans are adept at reading pictures, there is a certain point beyond which obvious variations in the imagery cannot be recognised. Here, it is essential to continuously monitor large volumes of data, yet the data's storage capacity might be problematic. It is desired to process the photos using digital computers, which can do so considerably more quickly than humans can [5], in order to overcome these difficulties. The distribution of tiny points in an image in two dimensions, known as pixels, may be thought of as an image. It may be considered a utility of two real variables in this context. Picture processing is the art of enhancing and using an image, making it possible to extract relevant information [6]. A digital picture may be described most comprehensively as a collection of statistics showing the geographical distribution of some field characteristics, such as electromagnetic radiation reflectivity, emissivity, temperature, or some geophysical elevation [7]. Image processing is the method used to enhance raw photos that are captured by a variety of tools, including cameras, satellites, aeroplanes, or the images that are captured in everyday life for a variety of purposes. Over the years, several assortments of processing processes have been developed [8]. Due to the easy availability of current memory devices, personal computers, graphics software, etc., image processing methods were becoming more and more popular. Therefore, image processing involves changing an image's personality to enhance its symbolic representation for human interpretation or to make them more trustworthy for autonomous machine observation [9]. There are a number of methods used in image processing to enhance and extract information from the photos; they are divided into the following categories as shown in Figure.1. Image acquisition: Using a picture capture method, a paper envelope may provide a digital image. Here, acquisition may be carried out via a scanner or a CCD camera.

Image enhancement: In picture enhancement, an image is processed to provide a result that is suitable for a variety of applications. Examples include removing noise from a picture, boosting the edges, increasing the disparity of the image, and removing the backdrop from the image.



Figure.1. Illustration of image processing techniques

This method may be utilised to carry out some of the fundamental chores for producing the resulting picture for carrying out different appropriate activities [10]. Here, it entails increasing the image's contrast and identifying multiple areas that mostly contain the postcode.

The practise of undoing damage to a picture that was caused by an identifiable cause is known as image restoration. Examples include the elimination of linear motion blur, the elimination of optical aberrations, and the elimination of periodic interference in a picture.

Picture compression: In order to demonstrate the information content of the image, the quantity of data is examined and then decreased.

Image segmentation is the process of dividing an image into its component elements or characteristics, such as discovering lines, circles, and different forms in an image. The process of extracting certain, chosen traits that allow for object classification is referred to as this method in terms of representation and description. ultimately uses postcodes to distinguish between various weights.

Classification and recognition: In this method, different labels may be applied to the objects based on the descriptors. So it is possible to identify certain numbers and understand a string of digits with postcodes.

2. Literature Survey

Enhancing a picture's prominence is required for image processing, and doing so allows for the extraction of characteristics and categorization of an image. It is used successfully in many disciplines, including meteorology, computer vision, astronomy, remote sensing, and others, although it may be time-consuming [11]. Therefore, a parallel computing strategy may be used to tackle this problem. Picture processing is a method that employs a number of procedures to produce an enhanced image or to extract useful information from the image. As a result, it may be regarded as an emerging technology that can be used in a variety of computer and engineering-related applications.

A method for improving the contrast in satellite photos was developed in [12]. Here, based on the morphology, a method for enhancing local dissimilarity of original photographs was put into practise. In the development of the mathematical approach, the conservative hypothetical perception of local dissimilarity improvement was unbounded. In order to improve local characteristics in the picture, standards based on the intensity of the retrieved image features might be used. For image recovery, these local traits may be strengthened and integrated. It was evident from the simulation results that this suggested strategy had improved efficiency rates when compared to the other standardised procedures.

A model for the contrast augmentation in multispectral pictures has been developed in [13]. The improvement in this case is directed at maintaining a number of imperative behaviours dependent on the coordinate axis. However, comprehensive coverage with clear restrictions is deployed by autonomous modification of the colour space's feature. Additionally, the colour space may be enhanced to achieve qualities with appropriate conservation. With a significant basis for extracting the colours from the photos with spectral features, this was very accurate. Without using either perpetual or clipping procedures, an unique variability enhancement method called histogram explosion was used to create a colour space. As a result, the metric values may be chosen while taking into account the preservation of hue values. It was evident from the investigation's findings that the histogram explosion required less processing effort to depict. An technique for enhancing satellite pictures has been developed in [14]. In this case, a new mask framing strategy based on the uniformity principle was developed for gathering the settlements of optimally ordered fractional differential un-sharp masking, which were then counter-corrected by piecewise gamma correction (PGC) through a robustly framed weighted summation framework. The positive involvement of reciprocal gamma values, which results in both provisional compression and provisional enlarged pictures, has an influence on PGC. Here, a modified Cuckoo Search (MCS) optimization model with a newly designed Grey-Level Co-occurrence Matrix (GLCM) features-based objective-function was used. It was motivated by the golden ratio rule. The results of the investigation made it clear that the proposed method's combination of parallel texture enhancement and dark image enhancement performed better by a preferred increment in contrast, entropy, colorfulness, and sharpness along with least values of correlation, energy, and homogeneity.

A model for increasing brightness in satellite pictures was presented in [15]. Using a Modified Dierential Evolution (MDE) strategy, the brightness of satellite photos may be improved. This strategy may be put into practise throughout the investigative, developmental, and exploitation phases. It may be expected that it will be used to characterise the fitness function by improving the features to update the processed conversion function and adding information about the edges, deviations, etc. in an image. According to the simulation results, this strategy achieves more durability and efficacy when compared to other augmentation options.

An technique for classifying cotton crops was developed in [16]. Images may be categorised based on the geographic information they contain. It may be seen as a plan that incorporates more accurate processing and mapping of that picture. With regard to the control of pests, cotton based on the barrier sector may be achieved in this case, leading to improved mapping in terms of crops. The barrier sector's position and implementation both deal with different elements related to financial situations. The results of the simulation made it evident that this strategy improves more than the other alternatives in terms of accurately categorising the cotton crop.

[17] has outlined a methodology for classifying cotton crops. Here, the performance may be studied based on techniques like the Dynamic Range Vegetation Index (WDRVI), Simple Ratio (SR), Enhanced Vegetation Index (EVI), Normalized IR, Wide- and Green NDVI (GNDVI), and Normalized Difference Vegetation Index (NDVI). Based on the results of this study, it is possible to classify vegetation using both neural networks and fuzzy c-means (FCM) clustering. From the results of the inquiry, it is evident that this strategy achieves a higher categorization rate when compared to the other alternatives. An better strategy for classifying cotton harvests has been developed in [18]. Depending on the population growth rate, crop monitoring may be seen as a crucial necessity to provide food safety. Turkey, for instance, might be thought of as a nation with many diverse regions where different crops were grown. Spectral Angle Mapper (SAM) and Dynamic Time Warping (DTW) approaches were eventually used for the better classification once it became obvious from this inquiry that crops like cotton, wheat, and

maize may be categorised. It was evident from the simulation results that this strategy achieves an effective classification rate when compared to the other approaches. An better method for classifying crops using remote sensing has been developed in [19]. The key factor at play was the determination scheme based on learning methodologies, which may be changed by employing different augmented resolvers. A demanding scheme based on defeasible sense that could be employed to execute dialectical reasoning on benefits and drawbacks linked with a decision towards the classification process was established to potentially determine classification strategies. Both of the acquired policies may be used to acquire accessible skills depending on the learners and classifiers. The analysis showed that this method has a higher classification accuracy for several crops, including cotton, corn, and others. Multiple regions are included in the assessment site that was set up for the testing. The experimental results show that, when compared to previous divergence-based algorithms for the classification of vegetation-based pictures, this method optimises the classification accuracyness. Combining the categorization and learning approaches results in computed reasoning that incorporates several points of view. The intangible instrumentation suggested in this study may thus be classified based on high data accessibility and solid professional knowledge with decision-making justification, according to the experimental findings.

Described a categorization scheme for cotton crops in [20]. The photos in this situation may be grouped using probabilistic fuzzy c-means (PFCM) clustering, and then they can be categorised using support vector machines (SVM). This method can be used for various investigative learning activities as well as the classification of crops based on vegetation indices like the Normalized Difference Vegetation Index (NDVI), Soil Adjusted Vegetation Index (SAVI), Transformed Normalized Difference Vegetation Index (TNDVI), Simple Ratio (SR), and Triangular Vegetation Index (TVI). This categorization method tends to advance investigative study, after which it may be contrasted with other methods. It is evident from the simulation results that the suggested strategy produces more accuracy than the other traditional approaches. A categorization model for urban scenes was put out in [21]. The ability to categorise urban settings based on local angular features was used in this instance for the categorization in relation to the high resolution ZY-3 multi-view photos. To represent the angular information at three levels, including pixel, feature, and label levels, three categories of angular difference features were specifically constructed. The angular information was immediately extracted by pixel evaluation between the multi-angle pictures in this case for the ADF pixel. Next, in ADF features, the differences between the multi-angle spatial features were compared to identify the angular differences in the feature domains (e.g., morphological attribute profiles). Similar to how ADF label created label-level angular characteristics based on a set of urban primitives (such as buildings) to show how unambiguous angular information is linked to the sorts of primal classes. Additionally, by employing superpixel segmentation to augment the multi-level ADF features, spatial contextual information may be used to reduce the impacts of salt-and-pepper noise and depict the primary angular distinctiveness within a small region. The investigations using ZY-3 multi-angle photos demonstrate that the suggested ADF features may significantly improve the classification accuracy of urban scenes when compared to only utilising the spectral bands. The findings also showed that the suggested ADFs were very effective at differentiating between spectrally similar and complicated man-made classes, such as different kinds of buildings and roads.

An study for the categorization of vegetation has been developed in [22]. UAV imaging systems may be used in this situation to investigate the vegetation. To get RGB photos for a vegetation inquiry, low altitude remote sensing, commonly known as remote sensing utilising a UAV, was carried out. The photographs were obtained using two UAV platforms, a VTOL quadcopter and a fixed wing UAV. Tree crown classification was accepted out on images achieved from the fixed-wing UAV to express its use in applications that require coverage over a relatively larger area, while crop region classification was accepted out on images achieved from the VTOL quadcopter to reveal its deployment in applications like inspections that require the hovering of UAVs. Using a spectral-spatial technique, classification was done for tree crown mapping and crop area mapping. The Bayesian information principle was used in this suggested technique to specify the best number of clusters for a given picture. A discordant strategy was used to cluster the dataset using k-means and the EM method while maintaining this limitation. The dataset was combined using the agglomerative method on these clusters. A proportional determination was used to create the combination. Additionally, spatial categorization was made functional to improve classification competency. The presentation of the suggested method was revealed using UAV photos gathered utilising the two UAV platforms. A performance comparison of the suggested classification strategy based on spatial characteristics with the other techniques was available. The findings showed that the suggested classification strategy based on the spatial feature outperformed the other traditional algorithms and was more reliable. In order to remove the desired difficulties, a method to examine the dissimilar parameter based sample strategy has been developed in [23]. When compared to the traditional sample method, active erudition based on windowing methods may achieve high classification rates. These techniques' proficiency was calculated using various datasets. The results of the experiments showed that the conventional arbitrary based sampling was used in various stages, could be effective as dynamic erudition methods, and could be used again to compute an improved dynamic erudition approach. Additionally, dependent on the amount of windows, the computational cost was reduced by using the dynamic erudition parameters. It is evident from the simulation results that this strategy achieves a higher classification rate when compared to the other approaches.

[24] has put into practise a method for simulating plant cover. The digital photos in this instance were gathered using several evaluation methods, and after some pre-processing, they could be classified. This method mostly relies on the vegetation's covered area. Here, the study of the image's objects allows the classification of the photos. Several digital photos, including sedges, mosses, and others, may be classified according to the vegetation's covering area. Here, different types of vegetation, including those in polar or desert regions, may be classified based on their vegetation, roughly including the absolute numbers of sedges. Predictions may be made using the digital picture based on both the vegetation type and the green normalised dissimilarity vegetation index (GNDVI), but the vegetation type is most relevant. The WorldView-2 photos and meadow images may be combined to create dissimilarity in the index values between the photographs. Here, it mainly depends on the reflectance of all the color bands. From the simulation outcomes, it was clear that this approach attains better classification rate based on the vegetation type and magnitude of the input images.

3. Parallel Image Processing

It is possible to think of parallel processing as a method that may be used to enhance picture processing. The practise of using several computer resources simultaneously to complete computational tasks is known as parallel image processing. The basic goal of parallel image processing is to identify and focus on the process that operates most efficiently and effectively. The idea of parallel image processing primarily refers to the distribution of different components of oversized computations among a number of processors, producing a rapid throughput as compared to other processors. As a result, a parallel computing model with a large number of processors has an unrestricted chance of achieving a high computational throughput. As a result, a number of computer languages, including C, UNIX, and FORTRAN, may be geared toward improving the relevance of processing technique[26]. As a result, the parallel processing technique's throughput and its integration with other approaches may provide this approach with a number of advantages and allow it to be employed for a variety of remote sensing applications.

The datasets must be split in order for a parallel method to be deployed effectively, and the segmented sets result in data being sent between processors. Furthermore, a parallel programme was developed from sequential programmes using a very small amount of tools.

Neuro Quantology | September 2022 | Volume 20 | Issue 9 | Page 2757-2769 | doi: 10.14704/nq.2022.20.9.NQ44322

Since these programmes are more easily parallelizable [27], their effectiveness as rebuilt parallel programmes is largely dependent on the software of the available systems, their expertise, and their comprehension of the purpose and application of parallel based techniques. Similar to this, the parallel processing and remote sensing methods [28] should be combined due to the absence of these abilities and comprehensions. Wide-ranging hardware mechanisms, reliable software platforms, and parallel programming libraries are all now more widely available thanks to the expansion of an industry research in the field. Thus, it can be assumed that adopting parallel image processing based on distant sensing would become more successful in the next years [29]. Depending on the processing levels, the amounts of unprocessed data decrease in the pyramidal parallel image processing stages. Since there are more pixels here at the lower level when compared to the higher level, Figure 2 may be used to show the relationship between these levels. pyramidal in shape.



Figure.2. Pyramidal parallel image processing levels

High computational demands in image processing applications result in a variety of designs with regard to their high concert and can thus be typically combined with parallel processing methodologies in a variety of ways.

Parallel image processing has developed into a useful research field that moves from expert photography to various applications, including computerised photography, astronomy, medical or biological image processing, space image processing, automatic character recognition, fingerprint, face, or iris recognition, reconnaissance, industrial applications, and a number of remote sensing applications, including the interpretation of aerial and satellite images.

4. Parallel Image Processing for Satellite Images

Typically, satellite photos include a variety of composite elements including woods, rivers, towns, and deserts. Similar to this, other factors including cloud cover, illumination, and climatic conditions increase the difficulty of processing such photographs taken in outdoor settings [30]. At the same time, the most complex computer methods, which primarily depend on atmospheric and photogrammetric models, enable feature identification characterising satellite pictures by a human operator to be reasonably competent with the pre-arranged quantity of instructions. Currently, the majority of methods used for picture feature extraction and classification may be seen as extensions of algorithms, making them inapplicable for fully automated geospatial applications. The term "remote sensing" primarily describes the method of photographing things without the sensor making direct touch with the item. With the use of numerous satellites, airborne remote sensing may be utilised to create satellite-based remote sensing, which can be used to gather data from the ocean, ice, and the surrounding area. Thus, mapping and ecological monitoring may be seen as an established approach that can be utilised to provide reliable information at a minimal cost. Here, digital pictures may be utilised to represent satellite photos, enabling efficient computer-based processing, which gives rise to the term "image processing scheme." The major components of the image processing setup are the unique software and hardware components that allow for the management, analysis, and presentation of the digital pictures. Furthermore, satellite-based remote sensing may be seen as a regulation in which the processing can be viewed as somewhat more sophisticated owing to the great data capacity. The study being done in space is now more difficult since more scanners have been launched with higher sequential, spectral, and spatial resolutions, increasing the number of pictures that can be recorded. There is a requirement for tested processing models due to the volume, variety, and importance of this information. Additionally, the duty of examining an image progression with respect to spectral time can be used for the same environmental position and in a variety of applications, particularly for the examinations of vibrant environmental variations, which increases the need for high-performance image processing. This may be protected based on inclination and reflects on ecological processes at a wide variety of scales, from local to global. Additionally, a number of legitimate time apps employ sensed data to compile geographic data with quick image response. Thus, feature extraction, categorization, organisation, clustering, degradation, and description are some of the methods used in satellite image processing. As a result, the information is primarily presented in two formats: raster and comma separated value formats. The expansion of disaster management, agricultural field monitoring, remote sensing, and many other industries depends critically on image processing based on satellite application. However, due to the significant amount of computing time required, processing such satellite pictures might be regarded as complicated and including several processing criteria. As a result, this might be seen as the fundamental barrier to real-time decision-making. Disseminated computing may be utilised as a suitable clarification to speed up this procedure.

This method may be used to the perception and gathering of data from a picture. They choose each little feature and incident from the earth's surface by using a regulated spectrum of light. For instance, archaeologists could use such specifics to determine gradual soil changes to identify potential sites. Environmentalists may use the same information to spot changes in vegetation and moisture in a picture.

Finding or seeing things is impossible. For instance, the soil found in a rainforest might be blocked by the tree canopy. The characteristics of the woodland may be affected by the cloud cover in this area. Images from various time periods should be chosen at a select few locations, primarily in overcast regions, in order to produce a clear picture. It also needs lots of storage space and power and also found to be expensive.

5. Satellite Image Enhancement

The process of processing an image based on the improved visibility of a feature is referred to as satellite image enhancement. Typically taken from many miles above the earth, satellite photos may be noisy and subject to interference from other sources, which can make matters worse. The separation between the sensors and the ground may be thought of as the main barrier to fine picture detail, which causes a single pixel to represent an oversized ground region that ranges in size from a few centimetres to several metres. High resolution satellite photos may be produced using a variety of techniques that merge many images. It is possible to compare such combination approaches, and as a result, the sensors often appear to create noisy, too dark, or too brilliant pictures. As a result, before being used, these satellite photos virtually always go through an improvement procedure. Image enhancement is often the initial stage of image processing that should be finished before using any other approaches since it may be thought of as a major topic. Generally speaking, there are two sorts of picture enhancement techniques, such as those that work in both the frequency and spatial fields. The power-law transformation, log transformation, contrast stretching, and histogram equalisation methods are more often used among spatial domain approaches. These methods are intended to increase an image's dynamic range to a reasonable level. There are a number of 28 denoising techniques that aim to reduce the signal's noise. The well-adopted resolution is the blurring of the image during the application of various filters, such as Gaussian, Mean, or Median filters. However, blurring techniques have the drawback of erasing the signal's existing boundaries. The overall disparity in the picture may be reduced by using a boundary-preserving denoising technique, which has been suggested to lessen this impact. On the other hand, the signal may be translated into the frequency domain via a Fourier transformation in frequency domain-related techniques. The noise may usually be reduced since it is associated with the high-frequency component of the signal. As a successful denoising strategy, the signal may lastly be transferred to the spatial domain. Similar to this, a variety of common low pass filters are available to reduce high-frequency compounds. In India, where 67% of the population depends on agriculture for a living, it is said to be the foundation of the economy, providing around 35% of the country's GDP. Keeping track of agricultural information is so vital. Remote sensing systems may thus be used to keep track of information thanks to its synoptic screening capability and variety of temporal and geographical resolution. Since remote sensing methods are quick and efficient, they are preferable to traditional methods. In farming and harvest management applications including crop inventory, crop fabrication predictions, consideration of drought and flood damage, and crop categorization, remote sensing methods play a significant role. According to [6], crop categorization can typically be highlighted using multispectral temporal data. Numerous factors, including geographic location, crop variety, field size, crop phenology, and soil conditions, are important in the categorization of crops.



Figure.3. Vegetation area classification

There are several image processing techniques available [8]. As seen in Figure 1.3, image processing techniques give ambiguous data from satellite photos. There are several considerations while working with these photos, including loading an image with the correct format, storing the data as multiple data types, displaying images, adapting to different image formats, etc. These instructions mostly call for image processing techniques. Future information could be categorised as quantitative or qualitative. It might be difficult to classify ground cover more accurately with only one satellite picture. Through radiometric annotations from the satellite, the vegetation ground cover may be seen. However, owing to seasonal variations, unstable air, etc., the radiometric annotations are only linked to the vegetation ground cover in an arithmetical sense.

6. Proposed Method

With the help of the pipeline idea, this technique employs parallel image processing and image recognition. The approach that has been created consists of four stages, which are I Pipeline Processing Model Design (ii) Parallel Meta-Algorithm Processing (iii), Template Matching and Document Classification (iii), and (iv) Structure of Image/Document Inspection. Every activity is typically carried out differently in this designed paradigm, and each person does various tasks in a unique method. This model examines images that include large amounts of data or information from remote sensing and that are divided into several blocks of varying sizes, particularly in both the horizontal and vertical axes. In parallel image processing, all stages are carried out simultaneously, and the pipeline idea also improves the efficiency of picture identification. The pipeline, which is furthermore an implementation strategy that makes the processor overlap for the execution of process, is often an intensive description of the execution of instruction in CPU. Figure.4. demonstrates the image recognition process based on the pipeline.



Figure.4. Architecture of Parallel Image Processing and Image Recognition

Here, a more complex imaging job is to be divided into a number of parallel pipelining processes, each of which completes the same work using a set of contrast data. The map-reduce model is eagerly addressed in the picture analysis. Some of the examples include facial detection and tracking. Figure 5 depicts the pipeline processing architecture.



Figure.5. Design of pipeline processing

In the experiments of processing remote sensing images, the pipeline classes that are available through Intel Threading Building Blocks and Java are used. Additionally, the act of processing the input, which results in the output, completes the whole processing process. These stages, in particular, are relatively unique in character. After the pipeline has been started, the reading phase reads blocks into memory for parallel processing, and the subsequent writing phase writes the processed blocks back into the files on the disc. These processes operate without regard to any limitations, and this parallel approach could be able to boost effectiveness. Since this procedure is more complicated and time-consuming, Lee filter is used to assess processing efficiency in this case. These filters analyse the processing time while adjusting the remote sensing picture to a size of 73M using a parallel pipeline technique. This is another decomposing approach where the sequential job is broken down into smaller tasks, and the smaller tasks are carried out in a dedicated stage that runs concurrently with all the other stages. The terms SIMD systems (Single Instruction Multiple Data), MIMD systems (Multiple Instruction Multiple Data), and Data Parallel Systems are also used to describe asynchronous parallel computers. Since every processor has a matching control flow, each one is capable of running its own programme. There are no location-related assumptions made in this application. Only the areas of overlap between the two photos are examined. In contrast, the typical assumption of applications of supreme optical flow is that the place has the least variation and smallest movements between succeeding frames. The most straightforward method for discovering an initial constraint is to use the 3D model and the assessed camera tupules from each picture. The visual outcomes are examined by three methods, however all the datasets are handled by a similar way. Each method treats certain regions better than others.

7. Results and Analysis

A personal computer with a 64-bit Windows operating system, 2 GB of actual memory, and an Intel core i-3 CPU is used to conduct the exploratory examination of the parallel approach that has been created. The programme used for the execution is MATLAB (R-2020a), which has facilities for parallel computation and image processing. Remote sensing photos have been used in this study project. Each image is presented here in a distinct manner. There are several modules that should be accessible throughout the development process. They are all individually tested against the user requirements. Given its large number of components, the system has to be tested as soon as possible to ensure user satisfaction. Since the proposed system must be improved over the existing one in order to function better, the implementation stage must be carefully measured in order to generate a successful satisfied system. Figure.6. shows various image representations



Figure.6. (a) Original Satellite image (b) Parallel Processing image using pipeline (c) Change Color (d) Contrast in (e) Contrast de (f) Darkness (g) Negative



Figure.7. Evaluation of efficiency rate

Figure.7 is used to assess the efficiency rate. The effectiveness is evaluated while taking sample numbers into consideration. There has been an increase in speedup, and it now solely relies on the volume of data. Figure.8. shows the pace of calculation. When processing large data sets, the pipeline technique performs better.



Figure.8. Speedup-size diagram

Visual Quality Analysis

In this analysis, visual quality is compared under the three algorithms of motion-related evaluation, color/edge-based assessment, and the RESCUE framework's suggested algorithm along a single selected key frame that is devoid of motion process. Motion-based assessments are carried out using movement vectors and entire sequence results. Since it was designed for outside landscapes, global depth is not appropriate for inside scenarios. The influence of the vertical gradient's creation on the evaluation of global depth leads to the estimation of motion, colour, and edge. Both vertical gradients and heretical gradients are used to evaluate the vanishing point and line method. In addition, 2D videos have one frame removed from them (captured using digital camera). The vanishing point along line model that was created intends to extract moving objects from 2D footage. However, motion/edge is based on a personal assessment.

(a) Live Accident on Highway

(b) Protecting human by forest animal

Figure.9. Converting 2D streaming to frames in which duplication frames are eradicated via RESCUE frame work (a) Live Accident on Highway (b) Protecting human by forest animal.



Figure.10. Depth map of foreground

Figure.9. represents the conversion of 2D into frames, with RESCUE frame work eliminating duplicate frames. This is Figure 10. defines the depth map for 2D frames using segmentation, motion detection, and motion detection for single and group objects.

8. Conclusion

This research effort has mostly focused on processing images quickly even as data volume rises significantly. The research project has used parallel processing to build fundamental image processing algorithms for satellite picture improvement. The experiment demonstrated a considerable increase in the pipeline model's processing performance with large amounts of data. The pipelining method provides the successful and feasible resolution for the efficient processing of remote sensing images. The pipeline is used for continuous activities, and it can also handle non-parallel tasks like reading and writing with ease. The pipeline technology idea must not be appropriate for image processing with small amounts of data since the pipeline's efficiency may be worse due to parallel system overhead and the interfaces between distinct processing blocks and sequential execution. The progression or processing of speed improvement for the huge remote sensing picture, however, is still a challenging problem that merits further research.

References

1. Aurdal, L, Ragnar Bang Huseby, Eikvil, L, Solberg, R, Vikhamar, D & Solberg, A 2005, 'Use of hidden Markov models and phenology for multitemporal satellite image classification: applications to mountain vegetation classification', International Workshop on the Analysis of Multi-Temporal Remote Sensing Images, pp. 220-224. 5.
2. Bai, W 2013, 'A Probabilistic Patch-Based Label Fusion Model for Multi-Atlas Segmentation With Registration Refinement: Application to Cardiac MR Images', in IEEE Transactions on Medical Imaging, vol. 32, no. 7, pp. 1302-1315.
3. Banerjee, BSVG & Buddhiraju, KM 2012, 'Satellite image segmentation: A novel adaptive mean-shift clustering based approach', 2012 IEEE International Geoscience and Remote Sensing Symposium, Munich, pp. 4319-4322.
4. Barbosa, J, Tavaresand, AJ, Padilha, J 2001, 'Parallel Image Processing System on a Cluster of Personal Computers', International Conference on Vector and Parallel Processing, pp. 439-452.
5. Bettahar, S, Stambouli, AB, Lambert, P & Benoit, A2012, 'PDE-Based Enhancement of Color Images in RGB Space', in IEEE Transactions on Image Processing, vol. 21, no. 5, pp. 2500-2512.
6. Bezdek JC, Ehrlich, R & Full, W 1984, 'FCM: the fuzzy c-means clustering algorithm',Comput Geosci. vol. 10, pp. 191-203.
7. Bhandari, AK, Kumar, A & Singh, GK 2015, 'Improved knee transfer function and gamma correction basedmethod for contrast and brightness enhancement of satellite image', International Journal of Electronics and Communications (AEÜ), vol. 69, pp. 579-589.
8. Buche, SB, Dhondse, SA & Khobragade, AN 2016, 'Satellite image processing on parallel computing: A technical review', 2016 Online International Conference on Green Engineering and Technologies (ICGET), Coimbatore, pp. 1-9.
9. Choi, K, Kim C & Ra, JB 2010, 'Infrared image enhancement based on an aligned high resolution visible image', IEEE International Conference on Image Processing, Hong Kong, pp. 3341-3344.
10. Deepika, NP & Vishnu, K 2015, 'Different techniques for satellite image segmentation', 2015 Online International Conference on Green Engineering and Technologies (IC-GET), Coimbatore, pp. 1-6.
11. Denore, BJ, Beaumont, TE, Pender, J, Campion, DG, Critchley, BR & Marengo, LRM 1988, 'Cotton Area Mapping Using Multitemporal Satellite Data Integrated Within A Geographical Information System Applied To A Cotton Boll Weevil Control Programme In Paraguay', Geoscience and Remote Sensing Symposium, 1988. IGARSS '88. Remote Sensing: Moving Toward the 21st Century., International, pp. 581-582.
12. Eisserer, C 2015, 'Portable Framework for Real-Time Parallel Image Processing on High Performance Embedded Platforms', 2015 23rd Euromicro International Conference on Parallel, Distributed, and Network-Based Processing, Turku, pp. 721-724.
13. Ganesan P & Rajini, V 2014, 'Assessment of satellite image segmentation in RGB and HSV color space using image quality measures', 2014 International Conference on Advances in Electrical Engineering (ICAEE), Vellore, pp. 1-5.
14. Ganesh B Shinde & Vijaya B Musande 2015, 'Cotton Crop Classification Method Using Levenberg-Marquardt Neural Network and its Performance Analysis on Vegetation and Green Leaf Indices', International journal of innovative technology and research, vol. 3, no. 1.
15. Gauri Rode & Shandilya, VK 2014, 'A Literature Review of Satellite Image Enhancement Methods', International Journal of Science and Research (IJSR), pp. 2319-7064.

16. Gilboa, G, Sochen, N & Zeevi, YY 2004, 'Image enhancement and denoising by complex diffusion processes', in IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 26, no. 8, pp. 1020-1036.
17. Henning Gerstmann, Markus Möller & Cornelia Gläßer 2016, 'Optimization of spectral indices and long-term separability analysis for classification of cereal crops using multi-spectral Rapid Eye imagery', International Journal of Applied Earth Observation and Geoinformation, vol. 52, pp. 115-125.
18. Himanshu Singh, Anil Kumar, Balyan, LK & Singh, GK 2017, 'A novel optimally weighted framework of piecewise gamma corrected fractional order masking for satellite image enhancement', Computers and Electrical Engineering, vol. 10, pp. 1-17.
19. Imai, S, Kasauka, D, Tsutsui, H, Imagawa, T, Okuhata, H & Miyanaga, Y 2016, 'Processing time reduction of tone mapping based on iterative shrinkage smoothing using parallel processing', 2016 International Symposium on Intelligent Signal Processing and Communication Systems (ISPACS), Phuket, pp. 1-4.
20. Kawarkhe, M & Musande, V 2014, 'Performance analysis of possisblistic fuzzy clustering and support vector machine in cotton crop classification', 2014 International Conference on Advances in Computing, Communications and Informatics (ICACCI), New Delhi, pp. 961-967.
21. Maheshwari, S & Krishnapriya, P 2016, 'Satellite Image Enhancement and Restoration - A Review', International Journal of Computer Science & Communication Networks, vol. 6, no. 4, pp. 198-204.
22. Manzke, R 2010, 'Automatic Segmentation of Rotational X-Ray Images for Anatomic Intra-Procedural Surface Generation in Atrial Fibrillation Ablation Procedures', in IEEE Transactions on Medical Imaging, vol. 29, no. 2, pp. 260-272.
23. Nanfeng Liu & Paul Treitz 2016, 'Modelling high arctic percent vegetation cover using field digitalimages and high resolution satellite data', International Journal of Applied Earth Observation and Geoinformation, vol. 52, pp. 445-456.
24. udayaCoumar, S, Aravindraja, R, Arulambalam, S, Naaraayan, RR & Prasad, RS 2016, 'Contrast enhancement of satellite images using advanced block based DWT technique', 2016 International Conference on Recent Trends in Information Technology (ICRTIT), Chennai, pp. 1-6.
25. Ramesh, PS & Letitia, S 2017, 'Parallel architecture for cotton crop classification using WLI-Fuzzy clustering algorithm and Bs-Lion neural network model', The imaging Science Journal, vol. 65, no. 8.
26. Ribbens, A, Hermans, J, Maes, F, Vandermeulen, D & Suetens, P 2014, 'Unsupervised Segmentation, Clustering, and Groupwise Registration of Heterogeneous Populations of Brain MR Images', in IEEE Transactions on Medical Imaging, vol. 33, no. 2, pp. 201-224.
27. Sanjay Saxena & Neeraj Sharma 2016, 'Parallel Image Processing Techniques, Benefits and Limitations', Research Journal of Applied Sciences, Engineering and Technology, vol. 12, no. 2, pp. 223-238.
28. Tetsuro Ishida, Junichi Kuriharaa, Fra Angelico Viray, Shielo Baes Namuco, Enrico C Paringit, Gay Jane Perez, Yukihiro Takahashi & Joel Joseph Marciano Jr. 2018, 'A novel approach for vegetation classification using UAV-based hyperspectral imaging', Computers and Electronics in Agriculture, vol. 144, pp. 80-85
29. Ustunera, M, Sanli, FB, Abdikan, S, Esetlili, MT & Kurucu, Y 2014, 'Crop type classification using vegetation indices of rapideye imagery', The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences, vol. 7.
30. Xin Huang, Huijun Chen &Jianya Gong 2018, 'Angular difference feature extraction for urban scene classification using ZY-3 multiangle high-resolution satellite imagery', ISPRS Journal of photogrammetry and remote sensing, vol. 135, pp. 127-141.