Automatic License Plate Recognition using OpenCV

Shivanshi Yadav *C*
omputer Science Department   Meerut Institute of Engineering and Technology Meerut, India
descent.shivanshi17@gmail.com

Kirtimaan Gaur
***Computer Science Department Meerut Institute of Engineering and Technology Meerut, India*kirtimaan.gaur.cse.2017@miet.ac.in**

Mukesh Rawat
Computer Science Department Meerut Institute of Engineering and Technology Meerut, India
mukesh.rawat@miet.ac.in

Abstract –

Object detection and image segmentation are the procedure of object identification and organization. The model in this project is fabricated using YOLO Neural networks. In this project, we hope to achieve the same by training our CNN deep learning network on various datasets such as COCO acronym of Common Object in Context. The aim of this project is to disclose and classify objects which are fed to our network in different formats(png,jpeg, avi, mp4, etc.) in minimum time as well as maintaining a high accuracy. We see object identification even as backsliding trouble up to graphically bisect bounding containers also similar with class prospect. Unit neural chain forecasts enclose containers together with class chances immediately from filled pictures in single calculation. Since the entire identification duct or tube happen in a unit grid, it might be reformed everywhere quickly on identification representation. Our combine system is very rapid. Picture Segmentation happens in the technique of dividing a computerized picture within many parts. Segmentation, basically define as technique of set a flag to every singlepixelinsideapictureso thatpixelswhich has same flag have certain properties. And also, in this report we have given a short outline about some segmentation techniques used in picture processing like clustering, edge based, region based, model based, etc. Our simple YOLO model processes pictures at 45 fps. The small-scale category of the grid, Rapid YOLO, approach at 155 fps. Contrast to state-of-the-art recognition method, YOLO put together many localizations inaccurate still is smaller likely to forecast wrong positives on environment. This paper addresses the recognition, object detection and segmentation issues in whitebackgroundphotoswithdeeplearningmethod.Inparticular,wefirstlytrainarecognitionmodelbasedonYOLO to judge whether a photo is white background. 3238

Keywords— Image Segmentation; Object Identification; Neural Networks; YOLO; COC.
DOINumber:10.14704/nq.2022.20.10.NQ55323 **NeuroQuantology2022;20(10):3238-3247**

I. Introduction

The technical world is deploying analysis in intelligent shipment systems which have a larger impact on mankind. LicensePlatedetectionisacomputertechnologytofigureoutthelicensenumberofautomobilesfrompictures.Itisa planted system which has multiple uses and challenges. At instant, the application of automobiles is increasing in the world.Alloftheseautomobileshaveaspecificvehicledetectionnumberastheirmajor identifier .TheIDisthelicense numberthatisalegallicensetotakepartinthecrowdiemovement. Eachautomobileontheglobemusthaveitsspecific number plate that must be fixed on its body. Typical LPR systems are applied using costly proprietary technologies.Thisconcludedapproachalsopreventsfurtheranalysisandgrowthofthesystem. One of the important collections of the open-source community in the technological world isPython.

Figure 1



Intel's exploration in Computer Vision develops Open Computer Vision (OpenCV) library helps in computer vision development. It assists with safety, automated switching systems, highway automobiles pace spotting, light spotting, steal automobiles spotting, and human and non-human loss collection systems. The automatic license plate recognizing system restores the manual license plate numerical writing procedure in computer systems.

Problem Statement

Our project deals with deep learning techniques specifically object detection and image classification in real time to create a working model that will help the blind to understand their environment in a better way. To achieve high accuracy in real time while by training and finetuning our model in an efficient way.

Motivation

It's wellknow that for a it is tough for a blind person to live their life without the help of others so here, we are, by using our project blind people who want to exploretheirnearbyareas,caneasilyexplorewithoutbeing dependentonothersfor helpingthem.Wecaneasilydirectcomputerstodiscloseandclassifymanyobjectsinapicturewithbigaccuracy.We have to acknowledge the terms such as picture classification object spotting, object localization and lastly inspect an object spotting algorithm known as YOLO (You only look once).

II. Methodology

The focus about object identification will reveal all occurrences of the objects among a familiar class, like individuals, vehiclesorfaceinapicture.Generally,auniquebriefgroupofoccurrencesoftheobjectarethereinpicture,stillshow up a huge group of viable places and measurements around which everybody can appear and that can be inspect. All detection of the picture is mentioned with some form of information. Here it is clear that the place of object, a place alongwithscale,andareaofobjectexplaininthe boundingcontainer.[1]Inotherlayout,theintelisbetteralongwith the variables of linear or non-linear change such as face recognition into a face spotter may calculate exact places of eyes, mouth, and nose, in appending to the enclose container of face. A simple example of a bicycle recognition is shown in the picture that defines the places of some segment is shown below in Figure.[7]

Figure 2

The pose defined as a 3-D variation indicating places of objects related from the camera. Object recognition always build a replica for the object class among a variety of building examples.



Figure 3

Talking about scenario of the hard object shown in a picture, at most a single of example might require, however in generalseveralbuildingexamplesareneededtoshowsome outlookofclassflexibilityconvolutionalexecutionofthe sliding screens. Figure depicts how we can change the fully attached layers of the network into the subsequent layers. [2]

Architecture of YOLO

We unite the separate parts of the object recognition onto a sole semantic web. The webbing utilizes all the properties and characteristics among the whole picture to depict every bordered container. This also depicts every bordered container for a picture at a same time. TheYOLO sketch allows far and wide teaching and real-time rapid pace while keeping the higher overall accuracy constant. [2]



Fig 4

The system split the picture into S x S framework. If the mid-point of an entity lies in a framework cell, then that frameworkcellwillbethereasonforrecognizingthatentity. Everyframeworkcellshowsboundingcontainersand particular levels for these containers. These particular levels show how specific the sketch is that container has an entityandhowpreciseitthoughtthecontainerdepicts.Everyboundingcontainer contains 5depictions:x,y,w,h, and that particular level. X and Y show the midpoint of that container related to the bound of framework entity. The breadth and depth are depicted related to the full picture.[2]

Design and Training

Our model structure is stimulated by the Google Net sketch for picture categorization. Our model has twenty-four specified levels following the two fully interconnected levels. Moreover, because of the specific modules taken by Google Net we can use 1 x 1 reduction levels followed by 3 x 3convolution levels. We also coach a rapidtypeofYOLOcreatedtoexceedthelimitsofrapidentity recognition.RapidYOLOmakeuseofasemanticweb withlesserlevels(nineratherthantwenty-four)andlesserdepictionintheselevels. [2]The last product of our web is the 7 x 7x30tensorofpredictions. WeretainourparticularlevelsontheImageNet1000class vyingdatacollection. For relation we must use the first twenty particular levels from the picture, also a mean pooling level and a connected level. We then transform the model to do recognition. Summing the particular and connected levels to retain the web andcan enhance accuracyofthelevels.

Weadd4convolutionlevelsand2connectedlevelswithaimlesslyinitiated weights. Recognition generally needs fine-grained optic details so we can expand the i/p dimensions of the web from 225 x 225 to 449 x 449. Our output level tells class chances and bounding container's locations. We simplify the boundingcontainerbreadthanddepthbythepicturebreathandlength sothatitmayliebetweenzero (0)and one(1). [4]

Limitations ofYOLO

YOLO apply hard dimensional parameters on bounding containers depict since every framework cell and only tells twocontainersandcanhaveunitclass.Itstrugglestopredict entitieshavingsmallerdimensions.Ithasverylessrecalland havelarge number of localization mistakes as compared to Faster R_CNN model.[5]

Challenges to ObjectRecognition

Object Recognition algorithms act as a grouping of pictures classification and object locations. It fetches a picture as inputandgivesoneormorebounding containersasaoutputwiththeclassflag attachedtoeach boundingcontainers. Object Recognition faces following challenges:

- In object Recognition, the bounding containers are always rectangular in shape. So, it does not need any help with predicting the shape of objects if the object carries the curvaturepart.

- Object Recognition did not tell some measurements such as the area of an object, perimeter of an object frompicture.
  ImagePartitionisan additionalextensionofobjectdetectioninwhichwespotthepresenceofanobjectthroughpixel- wise spots generated for each object in the picture. This technique contains more grains than bounding containers generation because this helps us to determine the shape of each object present in the picture.[6] This granularity helps in various areas such as medical picture processing, satellite projection,etc.

Image Segmentation 3241

Object recognition construct bounding container respective to the class in picture. But it gives no idea about the dimensionsoftheentity.Weonlyneedthearrayofbounding containerlocation.Weneedtofetchmoreintel,andthis is very unclear for our purpose. Picture classifications generate a pixel-wise cloak for every entity in the picture. This approach gives more growing build of the entity(s) in picture. [4]

Working. By splitting the picture into multiple parts, we can use the vital parts for predicting the picture. This is how picture classification works. A picture is the set of smaller entities called pixels. Following image will give an idea about imagesegmentation.[1]

Fig 5

Withtheincreaseintechnologicaladvancementstheimage segmentationhasmadeeasier many things. There are several more other uses of Image segmentation in transforming industries suchas:Crowd Control System forroads, Self-Driving AutomatedVehicles, Entity location in satellite pictureprojection and License plate detection, etc.We have applied algorithms to our model to detect license plate of vehicles. [7]



Fig 6

In picture 1, each single pixel attached to a specific class. All pixels attached to a specific class are depictedby the exact equal color. This explains semantic segmentation. And in picture2 has attached a specific class to every pixel of the picture. Moreover, variety of entities in the similar class had variety of colors. This explains instancesegmentation.

Region-basedSegmentation.Avitalpointisthatthevalueswillvaryfortheentitiesandthepicture'sbacksideif there's a peak value is present among them. We must set a base. The values lying below or above that base can be categorized. This is called as ThresholdSegmentation.

- If we want to segment the picture into two areas (object and background), we refer to a unit base value called globalthreshold.
- If we have number of entities with the backside. These are called as the local threshold.[3]



Fig 7

It is a RGB view picture. We need to change it into gray so, we only have a unit view.



Fig 8

Now, we should analyze some base values to this picture. This base value should divide the picture into dual strategies

– The upper side and the backside. The height and breath of the picture is one hundred and ninety-two x two hundred andsixty-three.Wecan computethemidpointofthevaluesandusethisasabase.Ifvalueislargerthanbase,wecan predict that it indicates to anentity. If the value is lesser than the base, it should be stipulated as backside. [2]



Fig 9

The darker area refers to the backside and the lighter area is the upper side.



Fig10

There are total four divisions in the shown picture. You should array various base values and see how the divisions are performed.

Edge Detection Segmentation. What differentiates objects in a picture? Always, an edge is there among two different and one to one regions with variety of black and white values. The corner can be a not continuous feature ofapicture.Wecanmaketheuseofnon-continuoustopredictcornersandhencerefersalimitofthat part.This contributes us in predicting the dimensions of various entities staying in a taken picture. Now, how will we predict the corners? [1]



Fig 11

Here is the step-by-stepprocess:-
Consider the matrix

- Take it to the uppermostpictures.
- Do point-wise multiplication and have theproduct.
- Move the matrix as per pathtaken.
- Intricate till all the points areused.

Sobel Operator:

Theworthofthematrixreferstotheproductoftheintricacy.Itcontributestotakeoutthefeatures. Analystshaveconcludedthattakingseveralindividualvaluesformatricesbringustorecognizehorizontalandvertical edgesandsometimeseventhecombinationofboththeedgescanbeconsidered.Thatonematrixisthesobeloperator.Sobeloperatorcontainstwomatrices–oneforrecognizing horizontaledgesand another for vertical edges.[7]

1	2	1
0	0	0
-1	-2	-1

-1	0	1
-2	0	2
-1	0	1

(a)HorizontalOperator (b) Vertical Operator(b)VerticalOperator

Figure 12

Edge recognition works by combining these filters over the taken picture.



(a)SampleImage (b) Convolving horizontal filter

Fig 13



(a) ConvolvingverticalFilter (b) Final output(b) Final Output

Fig14

Clustering-basedSegmentation.Clusteringcanbedefinedastermofclassifyingthedatapointsintomultiple classes,likedatapointsinthesimilarclassesareequivalenttosomedatapointsinthesimilarclassthanthoseinother classes. These classes are defined as clusters. We can use k-means clustering approach. Here, the k is equal to the no. of classifications.[4]Here is the process of k-means process:

1. Aimlessly choose k originalclassifications.
2. Aimlessly equate individual data point to any kcluster.
3. Compute the mid-point of theseclassifications.
4. Compute the path of all the data points from the mid-point of every individualcombination.
5. Following this path, the data points are relocated to the closestclassification.
6. Compute the mid-point of freshly buildcombinations.
7. Now, do again steps 4, 5 and 6 until the mid-point of the classifications does not transform or we attain the definite no. ofsteps.

Fig 15Dimensional Image

It’s a three-dimensional picture of that size. For combining the picture while using k-means algorithm, we required to change it in a two-dimensional set whose size will be (height*breath, channels). The picture will be transformed to a two-dimensional set. Now, set the k-means approach on this redesigned set and take the combinations. Thecombined mid-point approach of k-means can throw back the combination mid-point and flag approach can give us the flag for every sole point.[4]



Resulted Image

Fig 16

Thisistheimagewhenwelookbacktowardstheclustersofinitialform, i.e., three-dimensionalpicture,andshowthe outputs.

Results and Discussion



Fig 17: Detected license plate

Fig18:Detected License Plate

Training and Segmentation

Fig19Segmented Characters of plate

Prediction

(a) NumberPlate 1 (b) Number Plate 2

Fig 20 Predicted characters of plate

III. Conclusion and Discussion

WeintroduceYOLOandimagesegmentation,unifiedmodel sfordetailrecognition. Unlike categorized-based algorithms, YOLO is coached on a reduction state that clearly directed to recognition accuracy and the whole formation is trainedtogether.The resulting system of our model is interactive and engaging in detection license plate of vehicles. While YOLO process pictures specifically individual, when summed a camera it performs like a GPS, recognizing things as they change the state and transform in appearances. [6]

Figure 21

Application: In this project we further hope to achieve high precision of object detection and categorization in closed environment which will ultimately help the differently able to better understand their environment without the help of others.The system performs accurately for many variations in lightning conditions and different forms of number plates commonly found in India. But now as the new high security number plates are introduced by the government, it will be work more accurately. In addition, this system is economical and can be installed in different environments. [3]

Acknowledgement:Thank you for your cooperation and contribution

REFRENCES

[1] Redmon Joseph; Divvala Santosh; Ross Girshick. “You Only Look Once: Uni-ed, Real-Time Object Detection”. The IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2016.

[2] Hossain, M.D.; Chen, D. Segmentation for Object-Based Image Analysis (OBIA): A review of algorithms and challenges from remote sensing perspective. ISPRS J. Photogramm. Remote Sens. 2019.

[3] Chen, G.; Weng, Q.; Hay, G.J.; He, Y. Geographic object-based image analysis (GEOBIA): Emerging trends and future opportunities. GIScience Remote Sens.2018.

[4] Ma, L.; Li, M.; Ma, X.; Cheng, L.; Du, P.; Liu, Y. A review of supervised object-based land-cover image classification.ISPRSJ. Photogramm. Remote Sens. 2017.

[5] Roodposhti,M.S.;Lucieer,A.;Anees,A.;Bryan,B.A.Arobustrule-basedensembleframeworkusingmean-shiftsegmentationfor hyperspectral image classification. Remote Sens.2019.

[6] Lu, H.; Ma, L.; Fu, X.; Liu, C.; Wang, Z.; Tang, M.; Li, N. Landslides information extraction using object-oriented image analysis paradigm based on deep learning and transfer learning. Remote Sens.2020.