Wireless Energy Transfer for Internet of Everything: Energy-Efficient Resource Allocation in Digital Twins

[1]K. Raja Sravan Kumar
School of Computer Science and Engineering, VIT-AP University, Amaravati, 522237, Andhra Pradesh, India sravan.kovvali@gmail.com

[2]S. Gopikrishnan
School of Computer Science and Engineering, VIT-AP University, Amaravati, 522237, Andhra Pradesh, India gopikrishnanme@gmail.com

Abstract

The objective of this research is to improve Wireless Energy Transfer (WET) reliability in the Internet of Things (IoT), this research aims to enhance the lifespan of wireless equipment and encourage ecologically responsible communica-tion. The technology of of WET based on IoT ecosystem Digital Twins (DTs) shows in what manner to maximize the energy effectiveness of massive MIMO systems. Because of MIMO's ability to produce such narrow beams, other users will experience less interference. The BCD approach and fractional planning are used to maximize this MIMO system's energy efficiency. The algorithm proposed throughput is best when the highest transmit power is 19dBm, according to simulation data.

Index Terms—Internet of Things, Resource Allocation Algo-rithm, Wireless Energy Transfer, Digital Twins , Multiple Input Multiple Output

DOI Number: 10.14704/nq.2022.20.9.NQ44379 **Neuro Quantology 2022; 20(9):3289-3295**

I. INTRODUCTION

Digital Twin(DT) is the pioneer of the Industry 4.0 revolu-tion, which is enabled by sophisticated big data and Internet of Things (IoT) connectivity. IoT has boosted the amount of data that can be utilized in industrial, healthcare, and smart city settings. Combined with data analytics, the IoT's rich environment is an indispensable resource for predictive maintenance and problem detection, to name a couple, as well as the long-term health of manufacturing techniques and smart city initiatives. DT has grown in popularity as the most promising technology of the digital age since the introduc-tion of the big data era [1]. They become the intelligence service representatives in different domains, which include academic and industry disciplines, the applications for people's livelihoods, beginning with digitalization but going beyond it. As a reflection of the actual domain, DTs use real-time information from the real world in order to operate in the real world. At the same time, they transform into the physical world's foresight, prophet, and even super body. Nowadays most popular technologies like artificial intelligence (AI), IoT, big data, and are currently sweeping the globe [2,3]. The real world and its digital counterpart constitute two systems that evolve and operate in parallel. Specifically, DTs have created a communication bridge among the virtual domain and the actual domain on multiple Stages and scales.

The DT-based IoE development trend has evolved, and the connectivity among objects is continuously progressing and being updated [4]. The IoT's nervous system, wireless transfer connects sensors all throughout the IoT. That's because the majority of IoT networks are battery-powered, hence there will always need to change the battery which is more expensive to maintain in a long run. Wireless Energy Transfer (WET) should be used as a replacement for wired devices where there is no possibility of communication through cables, or efficiency is low in terms of communication. By using multiple antenna arrays, WET technology can extend the life of wireless communication devices and reduce their energy consumption. Multicast characteristics, strong controllability,

and consider-able flexibility are all advantages of RF transmissions. An important method for prolonging how long do the batteries in IoT wireless end nodes last to use RF transmissions in conjunction with the technologies of WET to charge very far devices [5, 6]. It is imperative that green communication be consistently optimized for IoT due to the convergence of DTs and IoT technologies. MIMO systems can provide an exceed-ingly narrow beam to minimize disturbance to other users. An IoT-based study of a wide range of MIMO frameworks over WET provides a study background for the effective energy efficiency of large-area MIMO frameworks. The majority of this work is divided into three sections. The IoT approach based on DT is first described. The wireless energy transceiver techniques of the Internet of Things are then investigated, and a wide area distributed antenna array is used for WSNs. To make better use of energy of MIMO-WET systems, a resource allocation mechanism is described. Using comparable translation and variable replacement techniques the nonconvex the optimization approach is changed into convex. The iterative optimization procedure begins with a simplification of the input variables and continues till the end of optimization. Because of its ability to improve massive WET-based MIMO's energy efficiency while also finding the correct ratio with both energy and frequency efficiency, which makes the work more relevant.

II. RELATED WORK

WET is conventionally split into three groups based on the physical mechanism used: WET based on RF-based WET, WET due to the magnetic resonance coupling, and inductance coupling. Instead of being limited to shorter distances like the first two field region WET systems, RF-based WET may transmit energy to far further locations and communicate to other wireless communication devices. Numerous IoT gadgets are powered by small rechargeable batteries. Therefore, WET-based wireless battery charging is indispensable. [7] examined the RBC functioning characteristics that defined the extreme energy broadcast distance was able to fix the everlasting power supply for IoT devices, Then, a test framework based on the conceptual design of the WET channels was created to ensure RBC system dependability which includes transmitter efficiency, distance for transmission, and output power. [8] noted that harvesting energy technology over wireless devices exhibited clear benefits with respect to the use and easiness of application, which is an efficient method for enhancing the effectiveness of transmission in the WET process. Energy harvesting technology may utilize trembling energy, temperature differential energy, electromagnetic radiation energy, or solar energy as its source. In the present WET system in the wide range, the microwave is the carrier for the primary energy. This system is known as the microwave WET. In this method, the distribution antenna is utilized to dispatch energy in all directions, and the energy receives at the accepting end by the distribution of RF waves over space. In addition, at acceptance end of energy, in order to complete WET, direct current is made from the RF signal. Resource allocation to a node is a crucial connection that requires careful attention throughout the process of energy transmission in wireless communica-tion systems. [9] Investigated the algorithm for allocation of a resource in nonorthogonal multiple access networks with WET. An iterative approach that guarantees convergence has been designed that delivers sub-optimal approaches for model allocating resources and enhances the profitability and utility of resource allocation systems. To optimize medium allocation and energy transfer, as well as the overall effectiveness of secondary users, authors in [10] propose a Non-Linear energy dissipation framework. Non-Linear energy conversion method produced results very similar to linear energy harvesting model, according to the study. Research on green communi-cations currently focuses mostly on boosting the efficiency in terms of energy use that WET technology provides as a whole and solely analyses the data rates of MIMO devices in WET settings. However, the whole system's energy performance and power usage have received minimal attention. A new algorithm for allocating system resources is proposed in this research in order to better use the WET system when used in conjunction with the MIMO channel.

III. ENERGY RESOURCE ALLOCATION BASED ON WET

A. IoT Implementation works on DTs

DTS are digital representations of real-world physical assets and processes. They're able to keep track of a given thing over its full lifecycle. DTs rely on Internet of Things (IoT) technology to collect data in real-time from multiple sources. Sensors are needed to run and update real-time data, which is then fed back into the digital system, mimicking the virtual environment. There are no DTs without the use of IoT-based sensing technology. The sensor input is made possible by the design of DTs. In order to imitate tangible items, DTs employ these sensors to gather information about the external world in real time, allowing them to better understand performance and identify potential issues. When the product is refined, DTs can submit feedback. Figure 1 depicts a hypothetical



Fig. 1. End-to-end conceptual model of DTs in the IoT Ecosystem

end-to-end DT model for the Internet of Things. Data-driven DTs (DTs) models are necessary for integrating application layer from physical layer, this model does it by combining a number of different forms of communication and machine learning. Signal conditioning circuits transform the item's non-electrical impulses into electrical ones that can be used by edge computing devices to communicate with one other in digital and analog formats.Methods for pre-processing multivariate sensor datasets include identifying and eliminating outliers, smoothing and discretizing the data, extracting features, de-creasing the amount of data, and interpolating what's left.

B. WET in IoT Transmission

Energy harvesting allows for the direct powering of re-motely located Internet of Things devices and sensors utilising a negligible amount of conventional energy that is easily available in the environment [14]. The wirelessly transmitted energy is readily available in the area where it is being used, and transmission losses are minimal. Batteries such as capacitors are used to store the electrical energy that has been gathered. The entire energy harvesting system's power distribution architecture as shown in Figure 2 can be designed in three parts. A dynamic model of the energy source is the initial step. A prior state change of the energy source is collected, the next state change is predicted, and an expected future output change is obtained. Once the energy source has been evaluated, the next step is to determine the appropriate duty cycle allocation strategy for that source. There must be a simple and logical way to determine the appropriate duty cycle for a given system. Finally, information gathered in real time is used to firmly alter the course of the project.



Fig. 2. Architecture of Large area scattered antenna array

The remote antenna unit is the simplified access node, which performs simple data processing. To cover a large area, a slot antenna can be spread out, data processing is moved to the central processing unit (CPU). Large-scale dispersed antennas expand the system's coverage area. Communication between access nodes and CPUs is enabled because of data flow linkages between access nodes and repeaters and the CPU. For transmission, the WSN makes

use of a globally distributed antenna array. Figure 3 depicts the transmission system's general structure, which consists of a mobile and sensor network layer. A huge dispersed antenna array archi-tecture is used at the mobile network layer. The base station's coverage area is dotted with several remote antenna units. There is a wireless link between the wireless sensor and the mobile network, and this wireless communication involves the transfer of wireless data as well as the transmission of wireless power. Through the use of a massively parallel distributed antenna array architecture, the base station or core network may control the activity of users in multiple cells at once. A network of distributed antenna units allows users to exchange data with one other and the central network. The eNB node is where the entire network's heterogeneous fusion is completed. In the traditional heterogeneous network paradigm, users in separate cells are unable to coordinate with one another. Communication between neighbouring eNBs is possible via interfaces.

C. Wireless Energy Transfer according to Multi-Antenna Transmission

MIMO configures several antennas simultaneously. trans-mission end and reception end Within the condition that spectrum resources continue to be The number of channels in the system has been increased by a factor of two. Beam-forming is among the most important technologies. Among the various MIMO technologies. The transmission capable of preprocessing the carrier signal in accordance with the status of the transmission of data Beamforming technology at the receiving end reduces background noise and interference by collecting duplicates of the desired signal. This ultimately improves the system's performance by increasing the SNR of the signal obtained at the accepted end. The effectiveness of a WET-based, double-hop, three-node relay network is assessed. To regulate the flow of information between a mono antenna transmit station S and a mono antenna receiver system station D, a multiantenna relay MR with Na antennas is used. Means of transmission During symbol transmission, the transmitted signal of the system persists due to the presence of quasi-static Rayleigh fading in the system channel. The system remains unchanged, though, despite the channel changes be-tween symbols. Suppose the relay isn't really working fueled by any external source of energy In such a circumstance, the source of the energy needed for its operation collected signal energy from the transmitter. The moment necessary for symbol transmission is T, the complete The sending process can be split into two time periods. slots. It takes T/2 seconds for each time interval. The transmitter's signal is transmitted to the relays during the first time slot.It divides the signal to two portions based on the coefficient of splitting for the energy receiver. In its time slot II, the relay makes use of the collected energy to move the process ahead of transmission of data from the sender to the receiver. Consider the vectors l1 of 1 H and l2 of H 1 The coefficient of small-scale fading is denoted by l1 of 1 H. The channel from the sender to the relay , accordingly, to the receiver. Due to the near proximity of the antennas and the presence of interference, a relationship can be established between them, with RE_r and RE_l analogous to the correlation matrices of the relay's receiving and sending antennas. The node's functionality in time slot II is powered by energy stored from time slot I. Utilize the Amplification and Forward Transmission technique to transmit the received information signal The very I time slot is transmitted to the receiver end. In the CSI situation, the relay is able to get the instantaneous values of l1 and l2. The relay directly multiplies the incoming signal by two in its second time slot. Using the communication matrix K before transmitting it to the recipient side. The connection between the relay and the system's ability to perform the smaller a network's traversal capacity, will be the more correlated its nodes are.



Fig. 3. Large area dispersed antenna array transmission system

D. WET-Based Massive MIMO Systems

In the Wireless Energy Transfer situation, the deployment of power sources to recharge IoT devices can enhance their lifetime. In order to increase the transmission range of energy, WET is frequently used in conjunction with MIMO. First, a Time Division Duplexing (TDD)-based multi-user, single-cell, A communicative base station with P transmitters, O sensor nodes, and an A-antenna Base Station (BS) make up a massive MIMO wireless transmission network. The sensors are scattered all around BS and the power station with a single antenna configuration depicting the FDD downstream channel estimate and transmitting data mode in a massive MIMO system. Before transmitting the system's energy signal, the energy is collected first. Temporal gaps in the transmission and collecting of energy have been normalized. There are two distinct stages to the length of the film. The WET phase is the first step in the process. The sensor node holds the energy transferred by the power beacon. The next stage is phase 1 gamma of information transmission. All of the acquired energy is used to relay data to the BS. Assume the BS has complete knowledge about the CSI. The energy beacon transmits the indication Tw of P*1 during the WET phase (T indicates the transmission power of a power beacon, w represents beam- former). At the outcome of the WET phase of phase I, the system advances to the phase II of the data transfer stage, the duration of the period is 1-gamma., and the device d uses all the wireless energy recorded and preserved by the wireless energy transfer node during the stage I to transfer data to the bs. The problem of resource sharing with optimum energy effectiveness be able to categorize as the problem of proportional design, and the sub-problem of curved optimization could be handled using the iterative chunk coordinate descent approach. Various synchronize directions are rotated through the procedure. The approach could not be capable to get the ideal result in a limited amount of iterations for non-separable functions. Adopting an adequate coordinate system helps accelerate convergence. Principal component analysis can be used to obtain, for instance, the new coordinate is not related as possible to the previous one. Optimization of energy effectiveness is a non-convex issue. Thus, stochastic design can more effectively determine the ideal wireless energy transfer time as well as energy distribution to enhance the system's energy efficiency. As S is a curved fixed on Kn in the majority of cases, a proportional strategy in place on the goal function e(x) instead of the classified set Z. There are three optimization variables in this problem. As a result, the BCD method is implemented. Initially, the time t and power p are held constant, then the momentarily most energy-throughput pk is determined as the optimized mutable. Next, p besides the before phase pk are locked to determine and, pk are used to answer p; and at last, the procedure is iterated till convergence. The convergence routine of an energy-effectiveness resource allocation method in a MIMO wide range scheme under WET circumstances is examined once the number of handlers is 10 and 30 and the extreme transmit power differs and is worked with various dB's of 0dB, 15dB, and 30dB. Experimental simulations are done with the help of MATLAB to mimic the results. On the 2D X, and Y coordinates, the following simulation scheme settings are specified: The bs is located at the coordinates of (-20,0)m, whereas the energy beacon's coordinates are at the location of (0,20)m. There are nine sensor nodes, which are planted at random between [0,0] and [-10,10] m. The number of bs antennas is 100, the number of power antennas is 50, the dispersion of the noise in the background is I, and the whole system's power consumption circuit is 1.5dB

IV. RESULTS

Energy efficient allocation of resources approach is shown in Figures 4 and 5 when the no.of individuals is 30 or 10 and the allowable transmission energy of power beacon fluctuates. This approach can fast converge after numerous rounds. The technique requires no more than four iterations to coincide under three distinct maximum transmission powers (0 dB, 15 dB, and 30 dB), and the number of individuals has no effect on the algorithm's convergence performance. Consequently, variations in the maximal transmission energy of the power beacons and the no. of individuals has no impact on the convergence rate of the energy performance inflation of the MIMO long- scale system under WET conditions.



Fig. 4. Convergence efficiency of the energy-efficient resources for user 30



Fig. 5. Convergence efficiency of the energy-efficient resources for user 10

When the number of transferring antennas at the BS varies, the performance implementation of the devised allocation of resources algorithm is investigated under this premise. As the total count of bss antennas raises, so does the throughput of the algorithm. When the highest transmission power surpasses 19 dB, the suggested technique achieves optimal throughput performance. Total energy use is compared in Figure 5 usage of three allocation of resources algorithms, including the approach discussed in this paper, under varying base station antenna counts. As according the allocation of resources algorithm suggested in this study consumes approximately 9 percent more energy than the power minimization tech-nique. With an increase in maximum transmitting energy, the consumption of energy of the maximum capability algorithm is significantly greater than that of the energy minimization method [15], although the energy consumed falls as the total amount of antennas increases. Due to the constant energy usage of the entire circuit, the transmission range and WET time drop with increase in no. of antennas, resulting in a decrease in total energy usage. On the dependency of ensured quality of user service, the results demonstrate that the present algorithm has greater coincidence than current allocation of resources mechanisms, efficiently increases the energy con-servation of long-scale MIMO systems in WET environments, and recognizes the shift between frequency and energy effi-ciencies.

V. CONCLUSION

Currently, electromagnetic coupling resonance, electromag-netic induction, and electromagnetic radiation are prevalent WET techniques in IoT. On the basis of fractional planning, a strategy for energy-efficient resource allocation is developed for the long-scale MIMO system of WET. This technique can increase the operational cpability of long-scale MIMO systems based on WET by achieving a better throughput while consuming less overall power. In conclusion, simulated tests reveal the effect of antennas correlations on the performance of the system and demonstrate that antenna correlations can im- prove performance of the system in certain circumstances. When the upper bound of transmission power reaches 19 dB, the algorithm's throughput is at its peak. In part, the research results address transfer of energy difficulties in the IoT. Even though, few flaws are identified in the present work. The equality of users is not taken into account in WET processing. Fairness criteria for both maximum and minimal energy efficiency can be incorporated in future work to maximise efficiency for all users.

REFERENCES

[1] J. Leng et al., "Digital twin-driven manufacturing cyber-physical system for parallel controlling of smart workshop," J Ambient Intell Humaniz Comput, vol. 10, no. 3, Mar. 2019, pp. 1155-66.

[2] Z. Jiang, Y. Guo, and Z. Wang, "Digital twin to improve the virtual-real integration of industrial IoT," J. Ind. Inf. Integration, vol. 22, Jun. 2021, pp.100196.

[3] C. Zhang et al., "A reconfigurable modeling approach for digital twin-based manufacturing system," Proc. Cirp, vol. 83, Jan. 2019, pp.118- 25.

[4] S. Aheleroff et al., "Digital twin as a service (DTaaS) in industry 4.0: an architecture reference model," Adv. Eng. Inform., vol. 47, Jan. 2021, pp. 101225.

[5] A. Ali, M. Haseeb, "Radio frequency identification (RFID) technology as a strategic tool towards higher per-formance of supply chain operations in textile and apparel industry of Malaysia," Uncertain Supply Chain Manag., vol. 7, no. 2, 2019, pp. 215-26.

[6] D. A. Basnayaka, H. Haas, "Design and analysis of a hybrid radio frequency and visible light communication system," IEEE Trans Commun, vol. 65, no. 10, May. 2017, pp. 4334-47.

[7] W. Wang et al., "Wireless energy transmission channel modeling in resonant beam charging for IoT devices," IEEE Internet Things J., vol. 6, no. 2, Jan. 2019, pp. 3976-86.

[8] T. Sanislav et al., "Wireless energy harvesting: Empirical results and practical considerations for Internet of Things," J. Netw. Comput. Appl., vol. 121, Nov. 2018, pp. 149-58.

[9] Z. Chang et al., "Energy-efficient and secure resource allocation for multiple-antenna NOMA with wireless power transfer," IEEE Transactions on Green Communications and Networking, vol. 2, no. 4, Jul. 2018, pp. 1059-71.

[10] Y. Wang et al., "Resource allocation in wireless pow-ered cognitive radio networks based on a practical non-linear energy harvesting model," IEEE Access, vol. 5, Jun. 2017, pp. 17618-26.

[11] P. Zheng et al., "A generic tri-modelbased approach for product-level digital twin development in a smart manufactur-ing environment," Robot Comput Integr Manuf, Aug. 2020, pp. 101958.

[12] M. Bevilacqua et al., "Digital twin reference model development to prevent operators' risk in process plants," Sustainability, vol. 12, no. 3, Jan. 2020, pp. 1088.

[13] P. D. U. Coronado et al., "Part data integration in the Shop Floor Digital Twin: Mobile and cloud technologies to enable a manufacturing execution system," J Manuf Syst, vol. 48, Jul. 2018, pp. 25-33.

[14] P. Zhong et al., "Joint mobile data collection and wire-less energy transfer in wireless rechargeable sensor networks," Sensors, vol. 17, no. 8, Aug. 2017, pp. 1881.

[15] P. Zhao et al., "Energy-saving offloading by jointly allocating radio and computational resources for mobile edge computing," IEEE Access, vol. 5, Jun. 2017, pp. 11255-68.