ANALYSIS OF MENTAL HEALTH BASED ON THE DREAMS BY ANALYZING THE BIOMEDICAL SIGNALS OF THE BODY

[1]Dr.Huma Khan, [2]Tripti Sharma, [3]Anisha Soni, [4]Minu Choudhary, *[5]Dr. Shaziya Islam

[1-5]Department of Computer Science & Engineering,

Rungta College of Engineering and Technology, Bhilai (CG), India

*Corresponding Author- shaziya.islam26@gmail.com

ABSTRACT

One of the vital parts of biomedical signal handling is feature extraction. In this paper, feature extraction methods are categorized into the time domain, recurrence space, time and recurrence area, and sign deterioration draw near. Brief acquaintances with some high-level sign examination procedures like nonnegative grid factorization, scarcity, and compressive detecting methods are used in this part. We start by underlining the causal job of the body in the dream and predict the positivity or negativity of the dreams based on the signals produced by that particular person so that if the negativity goes off the limit then we can analyze the person mind and can provide the regular treatment for the mental health.

Keywords - *Electrocardiogram (ECG), Electromyography (EMG), Electrocardiogram, (ECG), and Artificial Intelligence (AI).*

DOI Number: 10.14704/nq.2022.20.9.NQ44479 **Neuro Quantology 2022; 20(9):4204-4210**

1. INTRODUCTION

Biomedical signals (e.g., attractive reverberation imaging (MRI), processed tomography (CT), positron emanation tomography (PET), entire slide pictures (WSIs), electrocardiogram (ECG), electroencephalogram(EEG), electromyography (EMG), and so forth) are extremely valuable for assessing the prosperity of a human. To analyze the irregularity in a specific piece of the body or a specific organ, specialists utilize these pictures, signals, and clinical archives as a specific media. In the course of the most recent couple of many years, the advancement in the picture and sign handling has empowered programmed examination by utilizing phenomenal goal and quality datasets.

Nonetheless, a large portion of the best-in-class techniques neglects to pass on the genuine situation of the body part or organ. Demonstrating and AI strategies assume significant parts in managing biomedical signals or pictures. Their applications incorporate commotion decrease, antiquity evacuation, and early discovery of malignant growth. Additionally, these strategies can be utilized for growth investigation, a combination of multi-module information for better determination, arrangement of signs/pictures, and so on.

The point of this Special Issue is to unite unique examination and survey articles talking about clever exploration results of different displaying and AI applications. Entries can incorporate biomedical signs, pictures, and different sorts of biomedical or clinical information. Potential themes incorporate however are not blueprinted to the accompanying: Biomedical sign investigation utilizing AI and demonstrating AI approaches in clinical picture investigation and handling AI in computational frameworks Displaying and reproduction strategies in medication utilizing AI, AI and multiscale models for manufactured science Cardiovascular and respiratory frameworks designing utilizing AI and displaying Remedial analytic frameworks and advancements utilizing AI and displaying Recommender frameworks utilizing AI and displaying

2. PROBLEM STATEMENT

This paper presents the plan and advancement of a mechanical arrangement that expects to take care of issues during Dreams and getting the dreams and distinguish the degree of dream quality. In doing as such, it supports the demonstrative cycle and permits specialists to screen the advancement of patients.

Dreams are certifiably not a uniform cycle, which is the reason the analysis is done from when the subjects fall sleeping until they awaken. In this paper, we obtained electrooculogram (EOG) signals, internal heat level, Airstream Sensor (AS), and skin conductance (GSR) to screen subjects and examine the quality of their dreams. At the point when an absence of dreams happens throughout some period, dreams problems arise. These influence the typical advancement of the dream wake cycle, implying that periods of dreams might endure aggravations [1]. If these changes happen throughout an extensive period, they can cause medical issues and meddle with physical, mental, and passionate usefulness. This peculiarity is called dozing infection or a dreams problem. The main aggravations are dreams deprivation (endured by 15-30% of the populace,10% constantly), apnea (7% of the populace experience the ill effects of this and 85% of them go undiscovered), narcolepsy (influencing 0.06%) and parasomnias (10-20% of the populace).

To put it plainly, planning and fostering an innovative answer for dreams quality is introduced by investigating the patient's biomedical signals. This includes distinguishing changes in dreams by handling the signals in which certain boundaries are broken down to get a quantitative assessment of dreams' quality. In doing as such, an exact conclusion can be made, which will likewise empower specialists to screen treatment progress. The grounded procedures considered for breaking down dreams quality are polysomnography, respiratory polygraphy, testing for a very long time latencies, and the video-EEG dream record [2]. These methods are commonly just performed at a medical clinic since they are troublesome and costly. This paper offers an elective dream checking arrangement, which can be utilized at patients' homes at a lower cost.

Many papers have investigated dreams issues with various sorts of sensors, similar to EEG with EOG [3][5][6].or on the other hand wind stream with GSR [4]. Nonetheless, there are no distributed papers that utilization EOG, internal heat level, AS, and GSR to dissect dreams problems.

3. RELATION OF DREAMS WITH SLEEP

Dreaming is one of the most extraordinary and fascinating parts of rest. During an ordinary night's rest, it's commonplace to go through around two hours dreaming1. The most extreme dreams occur during the fast eye development (REM) rest stage, however, unmistakable kinds of dreams can happen during any piece of the rest cycle2.

Dreams can have symbolism that is positive, negative, or through and through befuddling, probably mirroring a time of enormous creative mind during sleep3. By and by, regardless of whether in positive or negative dreams, encounters from when you're conscious are oftentimes fused into the dream

Specialists keep on bantering with regards to why we dream5, however extensive proof focuses on dreams assuming a part in working with mind capacities like memory and passionate handling. Dreams have all the earmarks of being a significant piece of typical, solid rest. Simultaneously, however, bad dreams can upset rest and even influence an individual during their waking hours.

Considering that basically everybody has dreams, both great and awful, it's normal to think about what dreaming means for rest quality, regardless of whether bad dreams are terrible for rest, and how to keep away from awful dreams.



Figure 1. Stages of sleep

A PSG is a primary device utilized as of now to analyze rest problems and ordinarily includes recording the electroencephalogram (EEG), the electrooculogram (EOG), the electromyogram (EMG), the electrocardiogram (ECG), wind stream, thoracic and stomach developments, and oximetry. Different boundaries that might be checked incorporate body position, video, and sound observation. Just as the entirety of the specific gear, a prepared specialist is needed to append the sensors in the right positions. Contentions are encompassing the adequacy of rest labs; it is felt that patients in a rest lab don't rest just as they do at home. Nonetheless, such cases have been addressed by Portier et al. (2000), who gave proof that rest design and assessment of rest quality were the same between one or the other home or lab setting.

Flemons et al. (2004) zeroed in on deciding the sit tight an ideal opportunity for determination and treatment in five distinct nations. The creators hypothesized that the stand-by times came about because of the restricted beds accessible for rest studies in every nation, just as an absence of rest experts to score the information. also in this, we are assessing the nature of dreams with sleep and arranging the dreams in positive and negative analysis.

4. METHODS FOR IMPLEMENTATION

This segment depicts the strategies used to foster this cycle, which permitted us to set up a rest screen framework and assess its quality.

4.1 PARTICIPANTS

Some individuals had their sleep checked; subjects and some old male subjects. The accounts were two hours long, which is sufficiently long to distinguish a total hour and a half rest cycle. People experiencing ongoing diseases which might modify the paper's results were barred. The reason for this review is to ensure the adequacy of the sensors and the technique.

The sensors are joined to explicit focuses to empower exact information assortment. The EOG signal is gotten by three sensors: the reference sensor is connected behind one ear and the other two over the eyebrows. The nasal wind stream sensor is connected just underneath the nose. Finally, the GSR and temperature sensors are connected to a similar hand.

The signs from the sensors are caught and handled to investigate rest quality. The subjects joined the sensors in their homes with no expert assistance. This investigation passed the moral advisory group of the University of Deusto, and the patients marked an educated assent structure.

4.2 EVALUATION PROCESS

As a feature of the assessment, the subjects finished two surveys. The first is the ESS (Epworth Lethargy Scale) [5], which is a survey evaluating the inclination to nod off in 8 unique, inactive circumstances. The second is the PSQI (Pittsburgh Sleep Quality Index) [6], which gathers data from the patient. The accompanying Figure shows the outcomes acquired from the two surveys.

From the responses got from Figure1, every poll's complete score is determined. This last computation decides the end-product of the two surveys. The figure shows the last scores from each subject.

4.3 OBTAINING DATA SET

The heart levels of signals are taken as a form of data set checking is acquired utilizing an EMG sensor, which estimates the patient's solid development [5][8].

Its readings depend on the voltage distinction existing between the cornea and retina. Under ordinary conditions, the thing that matters is 0.4 to 5 mV. By joining anodes near the eye muscles, eye development is estimated to get EOG signals. These signs are very valuable to identify the NREM stage when eye development can scarcely be recognized, and the REM (Rapid Eye Movement) stage when development speeds up fundamentally. The AS (wind current sign) is a nose and mouth stream sensor that recognizes the progression of nasal and oral air during rest. It records changes when the patient takes in and out, which is fundamental to distinguish apnea also hypopnea problems. This sign is gotten with a 200 Hz least examining recurrence. To distinguish changes in the sign, ghostly data is removed in groups from 0.1 Hz to 15 Hz. The GSR (Galvanic Skin Response) records the skin's electrical conductance and obstruction. This biomedical sign relies upon the skin's mugginess brought about by perspiring. Substantial discharges are controlled by the SNS (thoughtful sensory system), so skin conductance is a decent sign of physiological L. Moreno-Alsasua et al. /Analysis of the rest nature of old individuals utilizing biomedical signs S1079 also mental excitement [7, 8]. Handling this sign recognizes the unexpected change from profound rest to a shallower stage, which may or not prompt awakening.

Ultimately, the internal heat level is a truly steady, endogenous marker and is accordingly valuable in concentrating on circadian problems. Internal heat level follows a 24-hour beat: it begins to drop toward the start of the rest period, it arrives at its absolute bottom in the little hours and afterward ascends in the early daytime harmonizing with awakening [9, 10]. This variation in temperature between rest/attentiveness is 1°C. Values are viewed as ordinary if the adequacy (the contrast between the most extreme pinnacle and least pinnacle) is the stage with the set rest plan

5. FRAMEWORK PLAN

This segment indicates the dependable rest observing framework. The elements of every subsystem are portrayed in Figure3. This segment parts into two subcategories: Hardware and Software, with each further partitioned into sub-blocks. Information acquired from these sensors is pre-handled with Arduino programming to acquire exact information [8][9][10]

6. TOOLS

Equipment is made out of two sub-blocks: putting away information acquired from biomedical sensors, and information pre-handling utilized for the ideal variation of the signs. It shows how the main square functions. The info is non-pre-handled physiological signs and the result shipped off the PC is altered signs for ensuing examination. The accompanying segments give a more nitty-gritty portrayal

7. IMPLEMENTATION AND RESULTS

Implementation is done in colab notebook using python and data set is downloaded from Kaggle for which link is given and type of signals which are analyzed are [10]

1. Electrocardiogram signals (ECG)
2. Electromayogram signals (EMG)
3. Electroencephalogram signal (EEG)

The processing is shown as



Figure 2. Process Flow

Considering the normal person heart rate and ECG we will be evaluating the signals based on that for negative or positive dreams and analyzing it So firstly take the data set in colab notebook as



Figure 3. Colab Notebook

Plotting signals using matplotlib

So the first graph is taken as baseline signal



Figure 4. Baseline Signal

Here in the baseline signal, it is clear that for a normal person the signals generated in sleep are not constant but after some time it is constant as shown in the graph for a particular line that means while someone is having a problem in sleeping and then after some time of sleep he is getting a constant signal which does not describe the positive or negative signals basically [13,15]



Figure 5. Comparison of signals

When we consider the hyperarousal and baseline signals of people having bad sleep having negative dreams compared to people having a good sleep



Figure 6. Analysis Of signals

If we analyze these graphs then it is clear that the persona having bad sleep the signal balance is not good for that and also signal consistency is going down for that particular person [15][16][17].

And the filtered signal is not showing any ups or downs in that particular graph



Figure 7. Filtered hyperarousal signals



Figure 8. Bandpass filtered output



Figure 9. Signals of affected Sleep

Accuracy of the system



Figure 10.Accuracy of Application

8. RESULT

Accuracy	Sensitivity	Precision	specificity
83.3	86.66	65.00	77.77

9. CONCLUSION

The advancement of an adaptable, powerful, and easy-to-understand application for the examination of human biomedical sign estimation was additionally accomplished for investigating positive and negative dreams, with fast information handling for a capacity compartment. This paper explore the biomedical signals of the human body generated while they are in sleep stages ad explained above with the stages of the sleep and also we concluded that if the biomedical signals generated by body producing graphs like figure 7 it means that person is having the negative dreams and it will produce bad affects in the concerned person mental health and if the graphs are normal as shown in the figure 9 which shows the relation between type of sleep and relation with dreams then it can be said that mental health for that person is normal and also this analysis had the option to examine the signals and separate them for positive and negative dreams which again can help the individual in their emotional wellness and can come over the negative piece of their life.

From future perspective this analysis can be useful for detecting the depression and its affects in someone's mental health and also can help the person in overcoming there negative thoughts by detecting it in the initial stage.

References

[1] Y. Attikiouzcl, "Biomedical signal Processing: present and future," Proc. Of the Fifth Int. Symposium on Signal Processing and Its Applications, 1999. ISSPA '99, vol. 1, pp.2.

[2] Ibrahim, Biomedical Signal Processing and Applications, International Conference on Industrial Engineering and Operations Management Dhaka, Bangladesh, January 9 – 10, 2010

[3] Introduction to Biomedical Signals, http://www.meo.etc.upt.ro/materii/cursuri/PSB/5.pdf

[4] Biomedical Signal Processing, Areas of Research https://www.embs.org/about-biomedical-engineering/ourareas-of-research/biomedical-signal-processing/

[5] X, Literature Survey on Biomedical Signal Processing Methods, International Journal of Innovative Research in Computer and Communication Engineering Vol. 4, Special Issue 2, April 2016

[6] Korenbaum et al, Computer Evaluation of Tracheal Forced Expiratory Noise Time for Bronchial Obstruction Diagnostics, Biomedical Engineering Research Dec. 2012, Vol. 1 Iss.1, PP.7-12.

[7] Gardner, Shabot, Patient Monitoring Systems, Biomedical Informatics pp 585-625, Part of the Health Informatics book series (HI), Springer,2006

[8] Kaushik.Sinha Biomedical Signal Analysis through Wavelets: A Review, International Journal of Advanced Research in Computer Science and Software Engineering,2012.

[9] Muthuswamy, CHAPTER 18 Biomedical Signal Analysis, Arizona State University, Tempe, Arizona2004.

[10] Tatsuo, Toshio, P.Ake Oberg. Biomedical sensor and instruments. Second edition.CRC Press,2011.E- book.

[11] Robert B Northrop.Non-invasive instrumentation and measurement in medical diagnosis. CRC Press,2001.E- book.

[12] Biomedical Signal Processing and Applications Muhammad Ibn Ibrahim Department of Electrical and Computer Engineering International Islamic University Malaysia Kuala Lumpur 53100, Malaysia.

[13] Shouldice R, Heneghan C, Nolan P, et al. PR and PP ECG intervals as indicators of autonomic nervous innervation of the cardiac sinoatrial and atrioventricular nodes. In Proceedings of 1st Int. *Conference on Neural Eng;* 2003. p. 261–264.

[14] Trägårdh, E, Claesson M, Wagner GS, et al. Reduced high-frequency QRS components in electrocardiogram leads facing an area of the heart with intraventricular conduction delay due to bundle branch block. *Journal of Electrocardiology*. 2007;40(2):127–132.

[15] Use H, Masuda I, Yoshitake Y, et al. Assessment of cardiac autonomic nervous activities through ECG RR interval power spectral analysis and cardiac depolarization-repolarization process. *Annals of Noninvasive Electrocardiology*. 2000;5(4):336–345.

[16] Van Bemmel J, Musen M. *Handbook of medical informatics.* 2nd ed. Houten: Springer, 1997. p. 336–345.

[17] Virtanen R, Jula A, Salminen J, et al. Anxiety and hostility are associated with reduced baroreflex sensitivity and increased beat-to-beat blood pressure variability. *Psychosomatic Medicine*. 2003;65:751–756.

[18] Wasmund W, Westerholm E, Watenpaugh D, et al. Interactive effects of mental and physical stress on cardiovascular control. *J Appl Physiol*. 2002;92:1828–1834.