A MACHINE LEARNING METHODOLOGY TOWARDS IDENTIFYING INFECTIONS OF PLANTS

[1]Shakti Chandra, [2]Shreya Chandrakar

.[1,2]Department of Computer Science & Engineering , Rungta College of Engineering & Technology, (Chhattisgarh Swami Vivekanand Technical University, Bhilai) Raipur,(CG), India

[1]shaktee.chandra@gmail.com,[2]shreya.chandrakr@rungta.ac.in

Abstract:

Crops illnesses pose a significant danger to agricultural safety, yet timely detection is tough in numerous areas around the earth because of shortage of infrastructures. The mixture of rising cellphone usage worldwide and recent breakthroughs in computer-vision enabled by machine learning (ml) have prepared the path for ML-based diseases detection. One of the most important concerns in present farming is plants diseases identification. Diseases can be seasonal, depending on the existence of the infection, commodities, atmospheric circumstances, and variety produced. Observing leaves segment is critical in the experiment of plants biophysical functionality. This study employs image processing techniques for disease detection and SVMfor plant leaf disease categorization. Plant leaf disease detection and classification is achieved using various image processing and deep learning algorithms based on numerous retrieved properties from plant leaves. Data collecting, images handling approaches such as tone improvement, RGB to HSI, K-means, exclusion of features, recognition, and SVM groundedCategorization are all used in the detection of plant leaf disease. The planned effort focuses on four significant plants leaf illnesses. Generally, the strategy of developing deep learning algorithms on growing huge and openly accessible picture collections points to a clear route for enormous worldwide android - based plant diseases detection.

Keywords: CNN, Machine Learning, Deep Learning, Image processing, Leaves Disease.

DOI Number: 10.14704/nq.2022.20.9.NQ44482 **Neuro Quantology 2022; 20(9):4234-4241**

1.Introduction

Modern technology enabled human civilization to generate enough food to feed more than 7 billion people. However, food security is still endangered by a variety of reasons such as climate change, pollinator decrease, plant diseases, and others. Plants illnesses not simply threaten global agricultural protection, although it might be disastrous for smallholder producers whose incomes relies on crop production [1]. Smallholder producers account for greater than 80% of food growth in underdeveloped nations, and yield losses of much more than 50% because of insects and diseases are common.However, small agricultural families account for the majority of poor people (50%), giving small-scale farmers particularly vulnerable to pathogen-related interruptions in food supplies.

Due to the computer power, high-resolution screens, and broad built-in sets of equipment, like powerful High Definition cameras, smartphones particularly provide quite unique techniques to assisting in illness identification. It is commonly predicted that by 2020, there will be between 5 and 6 billion cellphones on the planet. Around the end of 2015, 69 percent of the world demography had accessibility to portable internet connections, with mobile internet adoption reaching 47 percent in 2015, a [2].The combination of extensive smartphone penetration, HD cameras, and high-performance CPUs in mobile devices creates a situation in which, if theoretically viable, illness diagnosis based on automatic picture identification can be made available on an unprecedented scale.

Computer vision, and particularly object identification, has made enormous strides in recent years. The PASCAL VOC Challenges and, more subsequently, the ILSVRC built on the ImageNet collection have been extensively utilized as standards for a range of computer vision issues, including object detection. A massive, Deep CNN (DCNN) obtained a top-5 error of 16.4 percent for picture categorization into 1000 potential categories in 2012. Various developments in deep convolutional neural networks over the next three years reduced the error rate to 3.6%.. Whereas developing big neural network models might take a long time, learned algorithms can recognize pictures fast, making them appropriate for consumer purposes on cellphones [3].



Figure 1: Pictures from the PlantVillage data-set

In attempt to build accurate images classification model for plants diseases diagnosis, we needed a large, verified database of photographs of diseased and healthier crops. A such collection didn't really available as of previously, and even smaller datasets were not openly available. To overcome this issue, the PlantVillage project has emerged gathering 1000s of photos of good and damaged agricultural crops and it has released data freely and publicly accessible (Hughes and Salathé, 2015) [4]. We provide here the categorization of 26 illnesses in 14 plant varieties utilizing a CNN technique from 54306 pictures. Our models' effectiveness is measured by their abilities to forecast the proper plant-illness match out of 38 potential classes.The top operating classifier has a mean F1 score of

0.9934 (total effectiveness of 99.35%), confirming the practical usefulness of this technique. These findings represent move towards developing a mobile-based plants diseases diagnostic system.

2.Literature Review of Plant Diseases

Fungus frequently produce crop illnesses, and they primarily target the leaf. Several others are stimulated by viruses and microbial infections. Precision in farming has grown as the usage of ML and its linkedfeatures has expanded [1]. Agriculture's lower output amount harms countless living creatures, hence its solution necessitates contemporary techniques. Due to the high accuracy and decreased problems and redundant data, image-based diagnostic systems make diseases removal and identification simpler. In some plants, such as tomatoes, using photos to identify the infections that afflict them and the quantity of the destruction is impossible until there is a high accurateness [2].

According to Crops disease study, several different aspects influence how technology-based imagesrecognition is used. In other terms, illnesses that generate apparent depressions and deviations on the plant may be recognized using this technique, as opposed to illnesses which induce damages that can be recognized through photographs of the crops [3]. According to the findings of this study, plant illnesses are often recognized whenever they begin to affect the actual look of the crops.

The biggest difficulty facing agriculture is a drop-in yield and poor-quality plant production. The problem stems from the ineffective recognition and protection from plantsillnesses.The challenge has also been expanded to effect humans in a variety of behaviors. Plant diseases limit plant cover, resulting in world climatic change, starvation, and poor air filtration. Hyperspectral scanning has proven to be a reliable method of identifying agricultural problems in real time [4].

It is difficult to pinpoint the variables that cause illnesses unless they are recognized early. In other terms, if an illness is diagnosed early enough, it is simple to link it to the likely causes. For example, experts could identify whether there was a shift in weather or environment that contributed to the disease's emergence.Another issue is a scarcity of adequate devices for image detecting tasks. Most specialists in the field lack the tools needed to examine the photographs they collect in the field, making it difficult for them to collect correct data and diagnose illnesses [5]. The other issue is that some locations have a low rate of adoption due to rules put in place to safeguard the authenticity and trustworthiness of the data derived from these studies. For instance, during the 4th and 6th WorldwideSessions on Soft Computing and ML, various restrictions were enacted that may stymie the usage of ML in specific areas [6].The criteria prevent a few of the ML algorithm findings to becoming used in reality since they do not fulfil the needed requirements.

Another option may be to concentrate on adopting cutting-edge technology that is both dependable and genuine. The confusion caused by an insufficient database for use in illness detection arises from the present systems' substandard technologies and low storing capabilities. The majority of photos are incorrectly saved, affecting data retrieval. It might be resolved through employing current data storage systems. Cloud technology, might support improving memory performance and ease of access.The other option is to educate those within control of information analysis and assessment. A trained DL algorithm improves the technology's accuracy [7].

Another alternative is to better recognize the phenotypes employed in illness detection [8]. The phenotype employed in illness recognition is generally the product of environment and weather [9]. Another option is to advancement the classifications to assure that the data gathered is updated. The high level of ambiguity in disease identification has an impact on how technology is deployed. For ex, the application of Bayesian DL is fraught with uncertainty [10]. This indicates that if employed alone, this strategy is untrustworthy.

A mixture of strategies might be used to eliminate operational inefficiency. For instance, the use of DL meta designs alleviates some of the mistakes associated with other approaches of illness identification [11]. Another alternative is approach to use deep convolutional generative adversarial networks to aid with picture recognition and study [12].

The participation of adversarial networks improves the identification process effectiveness. The usage of CNN techniques may also be beneficial in responding against infection misclassification and slower identifying procedures [13]. The approaches have been utilized to diagnose rice illnesses and have various advantages.Image based identification involves a large number of tools, which must be made accessible by the regulators to guarantee that the processes run smoothly.

3.Research Methodology

Description of the Dataset

We examine 54306 photos of plants leaf surface that contain 38 different category names given to each. Every classes tag represents theplants disease combination, and we intend to identify the plants disease combination built solely on picture of the leaves. Depicts one case from each crop-disease relationship in the PlantVillage collection. We downsize the photos to 256x256 px in all of the procedures outlined in this investigation, and we conduct model refinement and recommendations upon those downscaled pictures.

We utilize three distinct versions of the PlantVillage dataset in all of our investigations. We begin with the PlantVillage set of data in color; thereafter we test with a gray-scaled variant of the PlantVillage set of data, and ultimately, we run all of the experimental investigations on an edition of the PlantVillage dataset in which the leaves have been divided up, separating all of the excess background details that could introduce some inherent bias in the data - set due to the PlantVillage dataset's regularized data collection procedure. A script modified to operate well on our given dataset is used to automating categorization.A script modified to operate well on our specific dataset was used to automating categorization. We selected an approach based on a collection of masks developed by analyzing the color, luminosity, and brightness aspects of various regions of the photos in several color spaces. One of the phases in that processing also allowed us to readily repair color casts, which were particularly powerful in several dataset's subgroups, reducing still another possible bias.

This collection of tests was aimed to determine if the neural network genuinely understands the "notion" of plants illnesses or whether it just accumulates the dataset's inherent biases. Figure 2 depicts the several variants of the same leaves for a randomly chosen collection of leaves.

Approach

We assess the suitability of DCNN for the aforementioned categorization challenge. We concentrate on two prominent designs, AlexNet and GoogLeNet, that are created for the ImageNet dataset as part of the "Large Scale Visual Recognition Challenge".

The AlexNet architecture follows the identical design pattern as the 1990s LeNet-5 architecture. Typical LeNet-5 architectural versions consist of loaded convolution layers followed by one or more completely linked layers. The convolution layers may optionally be followed by a normalization layer and a pooling layer, and all layers in the network are normally coupled with ReLu non-linear activation units.AlexNet is made up of five convolution layers, three completely linked layers, and a softMax layer. The first two convolution layers are followed by a normalization and a pooling layer, respectively, while the last convolution layer is followed by a single pooling layer. In our customised version of AlexNet, the last fully connected layer contains 38 outputs, which inputs the softMax phase. Ultimately, the softMax phase progressively generalises the input from, resulting in a range of scores among the 38 categories that sum up to 1.These values show the network's belief that a particular input picture is represented by the appropriate categories. All of AlexNet's first seven layers are linked with a ReLu non-linearity activation unit, while the first two FC layers are linked with a dropout layer with ratio of 0.5.

In terms of implementing practicality, the quantity of related work must be kept in mind, that is why 1*1 convolution are included before the previously described 3*3, 5*5 convolutions for dimensions reducing.

Ultimately, a filtering merger layer just merges the outputs of all of these parallel layers. While this is a single inception unit, the version of the GoogLeNet architecture that we utilized in our research includes nine inception units.On the PlantVillage dataset, we examine the effectiveness of both of the approaches by developing the model from zero through first scenario and afterwards adjusting previously taught systems via transfer learning in the other. In the condition of transfer learning, the weights of layer FC-8 in AlexNet and the loss classification layers in GoogLeNet are re-initialized. Then, while training the model, we don't restrict the learning of any of the stages, as is frequently done with transferable learning.



Figure 2: Progression of mean F1 score and loss over 30 epochs of training throughout all trials, categorised by experimental setup factors.

4.Results

Randomized prediction obtained a total average accuracy of 2.7% on a dataset with 38 category identifiers. The overall correctness we achieved on the PlantVillage dataset ranged from 85.6 percent to 99.4 percent throughout our experimental specifications, which included three visual renderings of the pictorial information, indicating that the deep learning model holds great assurance for related estimation issues. The average F1 score, precision, recall, and overall accuracy for all of our experimental conditions are shown in Table 1. All of the testing setups are performed for a total of 30 epochs and almost always convergence after the first drop down in learning frequency.

	AlexNet		GoogleNet	
	Transfer learning	Training from scratch	Transfer learning	Training from scratch
TRAIN: 200%, TEST: 80%				
Color	0.9736 (0.9742, 0.9737, 0.9738)	0.9118 (0.9137, 0.9132, 0.9130)	**0.9820** (0.9824, 0.9821, 0.9821)	0.9430 (0.9440, 0.9431, 0.9429)
Grayscale	0.9361 (0.9368, 0.9369, 0.9371)	0.8524 (0.8539, 0.8555, 0.8553)	**0.9563** (0.9570, 0.9564, 0.9564)	0.8828 (0.8842, 0.6835, 0.8841)
Segmented	0.9724 (0.9727, 0.9727, 0.9726)	0.8945 (0.8956, 0.8963, 0.8969)	**0.9808** (0.9810, 0.9808, 0.9808)	0.9377 (0.9388, 0.9380, 0.9380)
TRAIN: 400%, TEST: 60%				
Color	0.9860 (0.9861, 0.9861, 0.9860)	0.9555 (0.9557, 0.9558, 0.9558)	**0.9914** (0.9914, 0.9914, 0.9914)	0.9729 (0.9731, 0.9729, 0.9729)
Grayscale	0.9584 (0.9588, 0.9589, 0.9588)	0.9088 (0.9090, 0.9101, 0.9100)	**0.9714** (0.9717, 0.9716, 0.9716)	0.9361 (0.9364, 0.9363, 0.9364)
Segmented	0.9812 (0.9814, 0.9813, 0.9813)	0.9404 (0.9409, 0.9408, 0.9408)	**0.9896** (0.9896, 0.9896, 0.9898)	0.9643 (0.9647, 0.9642, 0.9642)
TRAIN: 50%, TEST: 50%				
Color	0.9896 (0.9897, 0.9896, 0.9897)	0.9644 (0.9647, 0.9647, 0.9647)	**0.9916** (0.9916, 0.9916, 0.9916)	0.9772 (0.9774, 0.9773, 0.9773)
Grayscale	0.9661 (0.9663, 0.9663, 0.9663)	0.9312 (0.9315, 0.9318, 0.9319)	**0.9788** (0.9789, 0.9788, 0.9788)	0.9507 (0.9510, 0.9507, 0.9509)
Segmented	0.9867 (0.9868, 0.9868, 0.9869)	0.9551 (0.9552, 0.9555, 0.9556)	**0.9909** (0.9910, 0.9910, 0.9910)	0.9720 (0.9721, 0.9721, 0.9722)
TRAIN: 600%, TEST: 40%				
Color	0.9907 (0.9908, 0.9908, 0.9907)	0.9724 (0.9725, 0.9725, 0.9725)	**0.9924** (0.9924, 0.9924, 0.9924)	0.9824 (0.9825, 0.9824, 0.9824)
Grayscale	0.9686 (0.9689, 0.9688, 0.9688)	0.9388 (0.9396, 0.9395, 0.9391)	**0.9785** (0.9789, 0.9786, 0.9787)	0.9547 (0.9554, 0.9548, 0.9551)
Segmented	0.9855 (0.9856, 0.9856, 0.9856)	0.9595 (0.9597, 0.9597, 0.9596)	**0.9905** (0.9906, 0.9906, 0.9906)	0.9740 (0.9743, 0.9740, 0.9745)
TRAIN: 80%, TEST: 20%				
Color	**0.9927** (0.9928, 0.9927, 0.9928)	**0.9782** (0.9786, 0.9782, 0.9782)	**0.9934** (0.9935, 0.9935, 0.9935)	**0.9836** (0.9839, 0.9837, 0.9837)
Grayscale	**0.9726** (0.9728.0.9727, 0.9725)	**0.9449** (0.9451, 0.9454, 0.9452)	**0.9800** (0.9804, 0.9801, 0.9798)	**0.9621** (0.9624, 0.9621, 0.9621)
Segmented	**0.9891** (0.9893, 0.9891, 0.9892)	**0.9722** (0.9725, 0.9724, 0.9723)	**0.9925** (0.9925, 0.9925, 0.9924)	**0.9824** (0.9827, 0.9824, 0.9822)

Each cell in the table represents the mean F_1 score$_{(\text{mean precision, mean recall, overall accuracy})}$ for the corresponding experimental configuration.
The bold values are the F_1 scores of the best performing models in the respective row/column.

Figure 3: AlexNet v/s GoogleNet

To deal with the problem of excessively, we fluctuate the experiment set to train set ratio and find that perhaps while training with only 20% of whole data and examining the classification model on the remaining 80% of whole data, the classifier reaches an accuracy rate of 98.21% in the case of GoogLeNet::TransferLearning::Color::20–80. As predicted, the average effectiveness of AlexNet and GoogLeNet degrades as the test set to train set ratio increases, although not to the extent that we might anticipate whereas if classifier was truly excessively.Above figurefurther indicates that there is no difference among the checking and learning losses, indicating that over-fitting was neither a cause in any of our experiment’s outcomes.

Between the architectures of AlexNet and GoogLeNet, GoogLeNet constantly outperforms AlexNet.Transfer learning, on the other hand, invariably generates superior outcomes, both of which was expected. While we maintain the remainder of the testing arrangement same, the 3 variations of the dataset (color, grayscale,& segmentation) exhibit a distinctive variance in performance across all tests. Colored variation of the collection produces the best results for classifiers. We were worried that the neural nets would just learn to detect inherent beliefs linked to the lighting environment, data collection technique, and instrument when developing the experiments.

Utilizing a gray-scaled variation of the identical datasets, we examined the model's adaptability in the absence of color information, as well as its capability to understand higher level patterns and structures relevant to different plants and diseases. The effectiveness did reduce, as indicated, while comparison to the studies on the colored variant of the dataset, but perhaps in the poorest situation, the obtained average Classification effectiveness was 0.8525.The segmented forms of the entire dataset were equipped to identify the effect of the image in ultimate effectiveness. The effectiveness of the approach employing segmented pictures in order is significantly stronger than the approach utilizing grayscaled pictures, but mildly lesser than the approach employing colored pictures.

5.Discussion

As an outcome, this model's performance is heavily dependent upon an basic preset attributes.Features development is a tough and time-taking procedure that must be handled anytime the circumstance or associated dataset changes considerably. The issue arises in previous effortsin the direction of identify plantsillnesses using image-processing since they rely primarily on hand-engineered features, picture augmentation approaches, and a slew of additional sophisticated &time-consuming procedures.

Moreover, it is crucial to stress that the technique given above is designed to supplement rather than substituting current illness diagnosis approaches.Labs testing is more trustworthy than visible signs diagnoses, and early-stage identification through visual assessment is usually challenging.Images data from a cellphone may be augmented with geolocation and timing details in the future to boost accurateness even more. Finally, please remember the remarkable rate at which modern phones has advanced in recent times and may continue to do so. With the quantity and quality of cameras on smart phones increasing all the time, we think that incredibly effective mobile diagnosis were just a factor of timing.

6.Reference

[1]. M. Türkoğlu and D. Hanbay, “Plant disease and pest detection using deep learning-based features,” Turkish Journal of Electrical Engineering and Computer Sciences, vol. 27, no. 3, pp. 1636–1651, 2019.View at: Publisher Site | Google Scholar

[2]. A. Fuentes, S. Yoon, S. Kim, and D. Park, “A robust deep-learning-based detector for real-time tomato plant diseases and pests recognition,” Sensors, vol. 17, no. 9, article 2022, 2017.View at: Publisher Site | Google Scholar

[3]. M. Loey, A. ElSawy, and M. Afify, “Deep learning in plant diseases detection for agricultural crops,” International Journal of Service Science, Management, Engineering, and Technology, vol. 11, no. 2, pp. 41–58, 2020.View at: Publisher Site | Google Scholar

[4]. K. Nagasubramanian, S. Jones, A. K. Singh, S. Sarkar, A. Singh, and B. Ganapathysubramanian, “Plant disease identification using explainable 3D deep learning on hyperspectral images,” Plant Methods, vol. 15, no. 1, p. 98, 2019.View at: Publisher Site | Google Scholar

[5]. B. Ashqar and S. Abu-Naser, “Image-based tomato leaves diseases detection using deep learning,” International Journal of Engineering Research, vol. 2, no. 12, pp. 10–16, 2019.View at: Google Scholar

[6]. H. Durmus, E. O. Gunes, and M. Kirci, “Disease detection on the leaves of the tomato plants by using deep learning,” in Proc. 6th International Conference on Agro-Geoinformatics, pp. 1–5, Fairfax, VA, 2017.View at: Google Scholar

[7]. A. Rangarajan, R. Purushothaman, and A. Ramesh, “Tomato crop disease classification using pre-trained deep learning algorithm,” Procedia Computer Science, vol. 133, pp. 1040–1047, 2018.View at: Publisher Site | Google Scholar

[8]. J. Ubbens and I. Stavness, “Corrigendum: deep plant phenomics: a deep learning platform for complex plant phenotyping tasks,” Frontiers in Plant Science, vol. 8, article 2245, 2018.View at: Publisher Site | Google Scholar

[9]. E. L. Stewart, T. Wiesner-Hanks, N. Kaczmar et al., “Quantitative phenotyping of Northern Leaf Blight in UAV images using deep learning,” Remote Sensing, vol. 11, no. 19, article 2209, 2019.View at: Publisher Site | Google Scholar

[10]. S. Hernández and J. L. López, “Uncertainty quantification for plant disease detection using Bayesian deep learning,” Applied Soft Computing, vol. 96, article 106597, 2020.View at: Publisher Site | Google Scholar

[11]. M. H. Saleem, S. Khanchi, J. Potgieter, and K. M. Arif, “Image-based plant disease identification by deep learning meta-architectures,” Plants, vol. 9, no. 11, article

1451, 2020.View at: Publisher Site | Google Scholar

[12]. J. Li, J. Jia, and D. Xu, "Unsupervised representation learning of image-based plant disease with deep convolutional generative adversarial networks," in Proc. 37th Chinese Control Conference (CCC), pp. 9159–9163, Wuhan, China, 2018.View at: Google Scholar

[13]. A. Singh, B. Ganapathysubramanian, S. Sarkar, and A. Singh, "Deep learning for plant stress phenotyping: trends and future perspectives," Trends in Plant Science, vol. 23, no. 10, pp. 883–898, 2018.View at: Publisher Site | Google Scholar

[14]. Lowe, D.G., Distinctive Image Features from Scale-Invariant Keypoints, International Journal of Computer Vision, 60 (2)(2004).

[15]. Agaian, S., Almuntashri, A., Papagiannakis, A. T. An improved Canny edge detection application for asphalt concrete. 2009 IEEE International Conference on Systems, Man and Cybernetics, 1-14 October 2009. San Antonio, TX, USA: IEEE, 3683–3687 (2009).

[16]. Sai Kirthi Pilli, BharathirajaNallathambi, Smith Jessy George, Vivek Diwanji, eAGROBOT-A Robot for Early Crop Disease Detection using Image Processing, IEEE, 2014.