Comparative Of Different Classifiers For Modified Slant Stack Algorithm Along With Artificial Intelligence To Find Diabetic Retinopathy At Early Stage

Mrs. Madhuri Yogesh Sonule[1]
Dept. of E&TC, Government Polytechnic, Kolhapur, India, madhusonule@rediffmail.com

Dr. Mrs. Sangeeta R. Chougule[2]
Dept. of E&TC, KIT College of Engineering, Kolhapur, India, shsangeeta.chougule@rediffmail.com

Abstract:

This research paper is to pick out automated microaneurysms (MAs) to prevent diabetic retinopathy due to which visible impairment occurs in a diabetic patient. There are some pathologies has intricacies that cause the disintegration, or maybe lack of the sight. Among them, one of the maximum big is the diabetic retinopathy, which is, at an eye fixed level, the maximum incessant and true complexity of diabetes mellitus. In this paper compare different extracted features of DR and classification for diabetic retinopathy with use of support vector machine (SVM), k-nearest neighbor (KNN), Naive Bays (NB), Decision Tree (DT), Random Forest (RF) and artificial Neural network.

Keywords: *DR:Diabetic Retinopathy, MAs:Microaneurysms, Diabetes Mellitus, Pathologies, NPDR: Non-Proliferative Diabetic Retinopathy PDR :Proliferative Diabetic Retinopathy, KNN: k-nearest neighbor, NB: Naive Bays, DT: Decision Tree , SVM: support vector machine . RF: Random Forest ()*

DOI NUMBER: 10.14704/NQ.2022.20.9.NQ44641 **NEURO QUANTOLOGY 2022; 20(9):5485-5493**

1.INTRODUCTION:

Diabetic associated eye diseases are the mainly frequent cause of loss of sight in the world. World Health Organization (WHO) has expected that in 2000 there were 171 million public global with diabetes and this number will increase to 366 million by 2030 [15], [16]. This makes diabetes among the leading causes of disabilities, death and economic hardship in the world. A side effect of diabetes is diabetic retinopathy in which different parts of the retina gets affected. Diabetic retinopathy is a health situation where the retina is injured because liquid leaks from blood vessels into the retina.

1.1. Abnormalities Associated with the Eye

Characteristics associated with the concept can be allotted primary classes, the essential being contamination of the concept, like outpouring, conjunctivitis, blepharitis and glaucoma. The accompanying accumulating is controlled as approach of existence associated disease like hypertension, arteriosclerosis and diabetes.

At the factor while the retina is been affected because of diabetes, this kind of corrupting is referred to as Diabetic Retinopathy (DR), even as perhaps now at this factor now no longer unequivocally overseen it is able to ultimately get going shortfall of vision. Ophthalmologists have come to concur that early spot and connect is the amazing solution for this debasement. DR event have been for the maximum outrageous element call for into three boss form BDR, PDR, and SDR.

Microaneurysms

These are the top-notch medical function to be noteworthy with inside the eye. They should seem in separation or in packs as a genuinely thoughts boggling don`t plan anything, faint crimson spots or acting to be little hemorrhages with within side the sensitive problematic retina. Their sizes is going from 10-100 microns as an occasion beneath 1/12th the broadness of an elegant optics plate and are spherical in shape, at this stage, the ruining is not eye coming across a few middle ground.

Hemorrhages:

Occurs within side the extra giant layers of the retina and are a big a part of the time known as 'smear' hemorrhages thinking about their spherical shape.

Hard Exudates:

These are one of the reliably occurring additives of diabetic retinopathy and could appraisal size-wonderful from minute portions to monster patches with easy edges. As precisely as blood, fluid this is prosperous in fats and protein is contained with inside the concept and that is the very disposition pours out to line the exudates. These can discourage mild and notable thru safeguarding sensitive from acting on the retina.

Sensitive Exudates:

These are commonly known as 'cotton downy spots' and are the extra regularly determined in country of the artwork retinopathy.

2. Neovascularization:

This can be depicted as sudden development of veins in place of the concept nearby the retina and is related to modern and smart misfortune. This takes place mulling over ischemia, or faded circulatory system to observable tissues. If the ones surprising veins make throughout the student, glaucoma can stop end result from the growing stress within side the concept. These new veins have extra important frail dividers and might mischief and exhaust, or make scar tissue broaden which can pull the retina far from the once more of the concept. At the variable whilst the retina is pulled away it's far known as a retinal detachment and enduring that left untreated, a retinal segment can factor of view certifiable ingenious and eager occasion, nearby perceptible inadequacy.

Spilling blood can cloud the shimmering (the sensible, jam like substance that fills the concept) and square the sensitive going thru the understudy to the retina, bringing approximately darkened and deformed pictures. In furthermore developed multiplication retinopathy; diabetic sturdy or scar tissue can painting on the retina.

2.1 Features Extracted from Retinal Images

To analyze retinal images described above and extract information, features need to be mined. These features include blood vessels, microaneurysms and the optic disc for that purpose initially use canon fundus camera.

Figure 1: Canon Fundus Camera

2.1.2 Blood Vessel Features

Lines are produced the usage of edges. Adcock and Thomas portrayed an facet in a digitized photograph as a get-collectively of associated facet locations in which an facet is portrayed via way of means of unexpected modifications in pressure displaying the restrict among areas in a photograph. Taking into consideration this, a line as proven via way of means of their definition is a place of constant electricity determined among edges which pass possibly as an give up for the line. Veins within side the retina suit the requirements of a line. figure. 2 indicates times of veins. Vessels are visible going thru all bits of the retina from the nerve fiber layer to the outer layer. There are wellsprings of blood by skip directly to the mammalian retina: the considerable retinal vicinity and the choroid veins. The choroid receives the pleasant circulatory structure (65%-85%) and is via way of means of and big massive for the help of the out of doors retina (explicitly the photoreceptors) and the extra 20%-30% streams to the retina thru the considerable retinal channel from the optic nerve head to assist inside retina.

eISSN 1303-5150



Figure 2: The Corresponding color bands (a) Red (b) Green (c) Blue of Color Retinal Image

3. Microaneurysms Features

Microaneurysms are the dilation of retinal capillaries. They are round intra-retinal lesions ranging from 10 to 100 micrometers in size and red in color. The cross-section of a microaneurysms exhibits a Gaussian distribution. Figure.3 illustrates examples of different microaneurysms taken from color retinal images. The top part shows their original format while the bottom depicts them in the green channel (so their shape is more visible). Researchers at the European Association for the Study of Diabetes 45th Annual Meeting in Vienna, Austria, reported that an increase in the number of retinal microaneurysms is associated with worse retinopathy prognosis in patients with Type 1 or 2 diabetes.



Figure 3: Two Fundus Images (a),(b) and its Corresponding Vessel Map (c),(d)

3. 1. Microaneurysms Detection

Microaneurysms can be detected by pixel classification, mathematical morphology, the fusion of the two, template-based and supervised learning. A description of each is provided below.

3.1.1 Pixel Classification

J. Staal has developed a method to detect Microaneurysms by integrating a vessel segmentation technique. Both the vessel map and possible Microaneurysms are extracted at once, with the map subsequently separated from the Microaneurysms candidate objects. Pixel classification being a supervised method requires the training of examples. All the pixels in the training set were thus assigned a label and a feature vector. After experimenting with different classifiers, they found the *k*-NN classifier produced the best result. The first step in [19] was to resize the image converted to its green plane so the field of view had a certain width. The image was then normalized by subtracting an estimate of the image background. This background was determined by filtering the image with a large median kernel. Using an unsupervised mixture model based clustering method, the microaneurysms candidates were detected from the normalized image intensities. Each pixel was assigned one of three classes, class 1 background elements; class 2 foreground elements, e.g. vessels, optic disc and lesions; class 3 outliers. A three class Gaussian mixture model was applied to fit the image intensities and a group of Microaneurysms candidates were segmented by thresholding the fitted model. The vessel map was extracted and used to remove any candidates that lie on the vasculature. With logistic regression, likelihood for each of the remaining candidates was calculated based on color, shape and texture properties. V. Durga Prasad Jasti et al. [20] have proposed ML classification. Suneet Gupta et al. [21] have worked on user behavior. Sunil L. Bangare et al. [22-23] proposed deep learning and fuzzy methods. Xu Wu et al. [24] have talked about crawler. Nilesh Shelke et al. [25] discussed LRS-DNN. Ajay S. Ladkat et al. [26] have worked on brain tumor. J. Alanya-Beltran et al. [27] proposed on machine learning application.

3.1.2 Mathematical Morphology

In the image preprocessing stage the image background is removed to create a shade corrected image. This is accomplished by subtracting the image with the result of a 25 × 25 median filter applied to the image. Afterwards, candidate extraction is performed on the shade corrected image by extracting vessels with morphological opening using 12 rotated linear structuring elements at 15° and producing 12 responses. Taking the maximum pixel values of all 12 responses at each pixel location produces a vascular map which is subsequently removed from the shade corrected image. The remaining candidates inside this image should no longer contain elongated structures but microaneurysms. Region growing is applied to each candidate before 13 features based on shape and color intensities are extracted. This is used to construct a feature vector for classification. After normalization by subtracting a median filtered version of the image, noise was subsequently removed by another median filter with a small kernel. A top hat transforms by morphological reconstruction using an elongated structuring element at different orientations was employed to detect the vasculature. With the vasculature removed, a microaneurysms matched filtering step was applied to locate the position of the candidates by thresholding. Region growing was directed at each of the remaining candidate before a number of features based on color, intensity and shape were extracted. A Bayesian classifier was then used to assign a likelihood of being a true microaneurysms to each of the detected candidates.

3.1.3 Fusion Technology

J. Staal devised another way to detect microaneurysms in fundus images based on candidate detection and classification. Candidate detection consisted of locating all possible microaneurysms by combining mathematical morphology with pixel classification. The combination was accomplished by placing all candidate objects in a set. Afterwards, all objects were checked to see if they overlap with one another in the set. In case of an overlap, one of the objects is removed. When both candidate detection systems detect the same object it does not matter which object is removed. The pixels were classified using a k-NN classifier with a reference standard that manually marked each image pixel. After the candidates are combined, the procedure extracts 68 features (from each candidate), again using k-NN to classify the candidate as either microaneurysms or non-microaneurysms. This work reported a 100% true positive rate with an 87% true negative rate when deciding if an image had a microaneurysms.

3.1.4 Template-Based

Template-based algorithms design templates to match with microaneurysms. The algorithm presented applied wavelet image decomposition. It compared a small window of the image with a microaneurysms template modeled by a Gaussian curve. The comparative result was the squared errors sum between coefficients of each sub-band and the micro aneurysm's corresponding coefficients. Thresholds were used to separate microaneurysms from other structures. It based their method on template matching also in the wavelet domain. To perform template matching in the wavelet domain, the wavelet transform of the Gaussian microaneurysm model at several different standard deviations was used. The coefficients of the wavelet transform model were compared to the coefficients of the wavelet transform of the image. Places in the image where a difference below a certain threshold existed, were assigned the microaneurysm locations. The size of the detected microaneurysm was determined by parameters of the matched model. Any candidates on the vasculature were removed based on a vessel segmentation step using wavelet analysis. For each of the remaining candidates, a likelihood determined by the local difference in wavelet coefficients was assigned.

3.1.5 Supervised Learning

The algorithm initially begins by preprocessing the fundus image to reduce the differences in intensity and contrast. This is accomplished by brightness and gamma correction as well as contrast enhancement. Microaneurysm detection is performed using a modified double ring filter. The double ring filter was originally designed to detect areas in an image where the average pixel intensity is lower than the average pixel intensity in an area surrounding it. It modified this filter to detect areas where the average pixel intensity in the surrounding area is lower by a certain fraction of the number of pixels under the filter. This is done to reduce false positive detections on smaller capillaries. A vessel map is next detected using the original double ring filter with different parameter settings to remove any candidates that lie on the vasculature. Afterwards, 12 features are extracted from each of the remaining candidates which had region growing applied to it. The features include shape, intensity, color and contrast features. An artificial neural network was trained and used to separate micro aneurysms from non-micro aneurysms. Local contrast normalization with local vessel detection was regarded as another useful approach to detect microaneurysms. After the initial preprocessing stage, a watershed retinal region growing method was applied to be used for contrast normalization of each candidate micro aneurysm. Local vessel detection detected vessels that occur with micro aneurysms and a *k*-NN classifier was used to classify the candidates. The algorithm presented in can be divided into four steps. The first step consisted of image enhancement: shade correction and image normalization of the green channel. The second step was candidate detection using diameter closing with an automatic threshold scheme. The third step involved feature extraction to facilitate the forth step of classification which was based on kernel density estimation in conjunction with Bayesian risk minimization. It employed a two stage process to detect micro aneurysms. The approach first used intensity information from red and green channels of the fundus image to correct non-uniform illumination. Matched filters were then applied to enhance the contrast of micro aneurysms against the background. The enhanced microaneurysms were segmented by a thresholding scheme which maintains the spatial structure of the microaneurysm segments. The vasculature was then removed from the image and detected via morphological top hat transform. The remaining candidates after the previous stage were classified using SVM to separate microaneurysms from other dark segments.

4. Steps implemented for experimentation

In proposed this method center is to distinguish computerized microaneurysms (MAs) to forestall diabetic retinopathy because of which visual deficiency happens in a diabetic patient. There are a few pathologies has complexities that lead to the crumbling, or even loss of the sight. Among them, quite possibly the most significant is the diabetic retinopathy. This is, at an eye level, the principle and difficult issue of diabetes mellitus.

1. The utilization Slant Stacking lessens the impact of irregular commotion on the state of an item and empowers the calculation to change a point identification issue into a line recognition issue. There are likewise a few constraints of the calculation, like the raised number of applicants and the reality it will in general bomb when there are structures almost a MA.
2. Programmed location of microaneurysms presents a significant number of the difficulties. The shape and shade of microaneurysms is basically the same as the veins. Its size is variable and normal exceptionally little so it tends to be handily mistaken for clamor present in the picture. In person retina, there is deviation in a pigmentation, surface, size and area. The more bogus positives happen when the veins are covering or adjoining with microaneurysms. So there is a need of a powerful computerized microaneurysms location technique so diabetic retinopathy can be treated at a beginning phase and the visual deficiency because of diabetic retinopathy can be forestalled.
3. Proposed framework utilizes shading and surface as visual highlights to depict the substance of a retinopathy picture of microaneurysms area. The proposed work done in 3 ways. Essential, we apply Gabor channels to pull out surface highlights from self-assertive formed MA districts isolated from a retinopathy picture. Then, at that point give division to picture increment the construction adequacy. Then, to accelerate recovery and comparability calculation, the data set pictures are sectioned and the separated locales are bunched by their element vectors incline stacking calculation. Third, to additional expansion the recovery exactness of our framework from ordinary and unusual data set, we consolidate the district based highlights extricated from picture areas, with worldwide highlights separated from the whole picture, which will be prepare and
4. Characterize utilizing Artificial insight and

execution of the proposed conspire is assessed by utilizing precision and affectability boundaries and contrasted and existing framework.

Matlab programming is utilized for reproducing the proposed Early Detection of Diabetic Retinopathy Using Microaneurysms structure. Matlab is a discrete-even test system that prepares assortments of designing and innovation tool compartments. This quick inclination change is balanced and henceforth invertible on its reach; it is quickly invertible to any level of wanted precision utilizing a preconditioned form angle solver.

In everyday the interaction for the location of miniature aneurysms

- *Retinal Fundus Image*
- *Image Preprocessing and Gabor change*
- *Color change*
- *Determination of Lesion Feature*
- *Using inclination and stack calculation*
- *Extraction of Global veil for database (Color+ direction + surfaces)*
- *Training and arrangement Using AI (ANN/KNN/DT/RF/NB/SVM)*
- *Performance Measure.*

5. Comparative of Different Classifiers:

- Accuracy, specificity and sensitivity are estimated using formulae in table 1.

Table 1 Performance Parameters

Parameters	Formula
Accuracy	TP+FN/(TP+TN+FP+FN)
Precision	TP/(TP+FP)
Recall	TP/(TP+FN)
F1 Score	2*(Recall*Precision)/ (Recall+Precision)



Figure 5.1: Performance Graph of Machine

Learning Algorithm

AI calculations strategic relapse, KNN, NB, DT and SVM show varieties in exactness because of individual assembly capacity. The paired grouping regarding highlights size and remarkable elements of the info include vectors are liable for characterizing the presentation of order. The single component values are not difficult to order for NB calculation and as element size expands NB execution diminishes. Then again expansion in trademark highlights builds the presentation of SVM.



Figure 5.2: Precision Analysis

KNN and LGST show similar accuracy, but theirs precision changes which shows dissimilar capabilities in terms of TP and FP results. The accuracy of SVM is seen better, precision of DT is seen better and recall of DT is seen well. In nuts and shell with consideration of only accuracy parameter SVM is better but in all parameters, DT shows better performance. This results are also seen to have similar effects in other applications where DT shows better performance over other classifiers when binary classification task is considered as application.



Figure 5.3: Recall Analysis



Figure 5.4: F-score Analysis

Based on accuracy, precision, recall and F-Score, DT outperforms over other classifiers.



Figure 5.5: F-Score analysis for 80:20 ratio of training and testing dataset



Figure 5.6: F-Score analysis for training to testing ratio of 75:25



Figure 5.7: F-Score analysis for training to testing ratio of 85:15



Figure 5.8: F-Score analysis for SVM mode training to testing ratios

The training and validation is split is configures for 80% and 20 % respectively and this combinations are changed to 75-25, 85-15 and 70-30 ratios. The results for 70-30 are seen better compared to other combinations as shown in figure 5.4. Also, in all combinations SVM shows better results hence comparison of SVM model only are shows in figure 5.6 to figure 5.8.

Conclusion:

Programmed location of microaneurysms presents a significant number of the difficulties. The size and shade of microaneurysms is basically the same as the veins. Its size is variable and normal exceptionally little so it tends to be effectively mistaken for commotion present in the picture. This contribution shows the extracted features are classified for diabetic retinopathy with use of support vector machine (SVM), k-nearest neighbor (KNN), Naive Bays (NB), Decision Tree (DT), Random Forest (RF) and artificial Neural network. The support vector machine classification results outperform against all classifiers.

REFERENCES:

[1] Mohammed Hafez, Sherif Abdel Azeem, "Using Adaptive Edge Technique for Detecting Microaneurysmsin Fluorescein Angiograms of the Ocular Fundus"IEEE MELECON 2002, May 7-9,2002, Cain, EGYPT.

[2] Rumano A. Simandjuntakl''Development of Computer-Aided Diagnosis System for Early Diabetic Retinopathy based on Micro AneurysmsDetection from RetinalImages'', Department of Electrical Engineering, Institut Teknologi Bandung, Indonesia.

[3] Thomas P. Karnowski, "Retina Lesion and Microaneurysm Segmentation usingMorphological Reconstruction Methods with Ground-Truth Data"30th Annual International IEEE EMBS ConferenceVancouver, British Columbia, Canada, August 20-24, 2008

[4] Meindert Niemeijer, Bram van Ginneken''Retinopathy Online Challenge: AutomaticDetection of Microaneurysms in DigitalColor Fundus Photographs''Ieee Transactions On Medical Imaging, Vol. 29, No. 1, January 2010

[5] B´alintAntal, Istv´an Lazar, AndrasHajdu, ZsoltTorok, Adrienne Csutak, T¨undePeto, "Evaluation of the grading performance of an ensemble-based microaneurysm detector", 33rd Annual International Conference of the IEEE EMBS, September 3, 2011.

[6] Giancardo, Student Member, IEEE, F. Meriaudeau, Member, IEEE, T. P. Karnowski, Member, IEEE, Y. Li, Member, IEEE, K. W. Tobin Jr, Senior Member, IEEE and E. Chaum, Member, IEEE "Microaneurysm Detection with Radon Transform-based Classification on Retina Images"33rd Annual International Conference of the IEEEEMBS, September 3, 2011.

[7] Ankita Agrawal, Charul Bhatnagar, Anand Singh Jalal, "A Survey on Automated Microaneurysm Detection inDiabetic Retinopathy Retinal Images"978-1-4673-5986-3/13/$31.00 ©2013 IEEE

[8] L. Giancardo, F. Meriaudeau, "Validation of Microaneurysm-based Diabetic Retinopathy Screening across Retina Fundus Datasets",978-1-4799-1053-3/13/$31.00 c 2013 IEEE.

[9] Jorge Oliveira, Grac¸a Minas and Carlos Silva "Automatic Detection of Microaneurysm Based on the Slant Stacking"978-1-4799-1053-3/13/$31.00 c 2013 IEEE.

[10] Tsuyoshi Inoue, Yuji Hatanaka, Chisako Muramatsu, and Hiroshi Fujita"AutomatedMicroaneurysm Detection Method Based onEigenvalue Analysis Using Hessian Matrix in Retinal Fundus Images"Osaka, Japan, 3 - 7 July, 2013.

[11] R. Vidyasari, I. Sovani, and T.L.R. Mengko, H. Zakaria, "Vessel Enhancement Algorithm in Digital Retinal Fundus Microaneurysms Filter for Nonproliferative Diabetic Retinopathy Classification"2011 International Conference on Instrumentation, Communication, Information Technology and Biomedical Engineering8-9 November 2011, Bandung, Indonesia.

[12] Gwenole Quellec, Stephen R. Russell, and Michael D. Abramoff, "Optimal Filter Framework for Automated, Instantaneous Detection of Lesions in Retinal Images", IEEE TRANSACTIONS ON MEDICAL IMAGING, VOL. 30, NO. 2, FEBRUARY 2011.

[13] V. Vijaya Kumari, N. Suriyanarayanan, C. Thanka Saranya, "Feature Extraction for Early Detection of Diabetic Retinopathy"2010 International Conference on Recent Trends in Information.

[14] Kanika Verma, Prakash Deep and A. G. Ramakrishnan, "Detection and Classification of Diabetic Retinopathy using Retinal Images" Department of Electrical Engineering, Indian Institute of Science.

[15] https://apps.who.int/iris/bitstream/handle/10665/120216/em_RC1_summary_minutes_4_en.pdf?sequence=1

[16] S. Wild, G. Roglic, A. Green, R. Sicree and H. King, "Global Prevalence of Diabetes: Estimates for the Year 2000 and Projections for 2030," Diabetes Care, Vol. 27, No. 5,

2004, pp. 1047-1053. doi:10.2337/diacare.27.5.1047

[17] "1987 Index - IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol. PAMI-9," in IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. PAMI-9, no. 6, pp. 846-851, Nov. 1987, doi: 10.1109/TPAMI.1987.4767992.

[18] Zhu, X. and Anthony Tung Shuen Ho. “A slant transform watermarking for copyright protection of satellite images.” Fourth International Conference on Information, Communications and Signal Processing, 2003 and the Fourth Pacific Rim Conference on Multimedia. Proceedings of the 2003 Joint 2 (2003): 1178-1181 vol.2.

[19] M. Niemeijer, B. van Ginneken, M. Cree, A. Mizutani, G. Quellec, C. Sanchez, B. Zhang, R. Hornero, M. Lamard, C. Muramatsu, X. Wu, G. Cazuguel, J. You, A. Mayo, Q. Li, Y. Hatanaka, B. Cochener, C. Roux, F. Karray,M. Garcia, H. Fujita, andM. Abramoff, “Retinopathy online challenge: Automatic detection of microaneurysms in digital color fundus photographs,” IEEE Trans. Med. Imag., vol. 29, no. 1, pp. 185–195, Jan. 2010.

[20] V. Durga Prasad Jasti, Enagandula Prasad, Manish Sawale, Shivlal Mewada, Manoj L. Bangare, Pushpa M. Bangare, Sunil L. Bangare, F. Sammy, "Image Processing and Machine Learning-Based Classification and Detection of Liver Tumor", BioMed Research International, vol. 2022, Article ID 3398156, 7 pages, 2022. https://doi.org/10.1155/2022/3398156.

[21] Suneet Gupta, Sumit Kumar, Sunil L. Bangare, Shibili Nuhmani, Arnold C. Alguno, Issah Abubakari Samori, "Homogeneous Decision Community Extraction Based on End-User Mental Behavior on Social Media", Computational Intelligence and Neuroscience, vol. 2022, Article ID 3490860, 9 pages, 2022. https://doi.org/10.1155/2022/3490860.

[22] Sunil L. Bangare, Deepali Virmani, Girija Rani Karetla, Pankaj Chaudhary, Harveen Kaur, Syed Nisar Hussain Bukhari, Shahajan Miah, "Forecasting the Applied Deep Learning Tools in Enhancing Food Quality for Heart Related Diseases Effectively: A Study Using Structural Equation Model Analysis", Journal of Food Quality, vol. 2022, Article ID 6987569, 8 pages, 2022. https://doi.org/10.1155/2022/6987569.

[23] Sunil L. Bangare, “Classification of optimal brain tissue using dynamic region growing and fuzzy min-max neural network in brain magnetic resonance images”, Neuroscience Informatics, Volume 2, Issue 3, 2022, 100019, ISSN 2772-5286, https://doi.org/10.1016/j.neuri.2021.100019.

[24] Xu Wu, Dezhi Wei, Bharati P. Vasgi, Ahmed Kareem Oleiwi, Sunil L. Bangare, Evans Asenso, "Research on Network Security Situational Awareness Based on Crawler Algorithm", Security and Communication Networks, vol. 2022, Article ID 3639174, 9 pages, 2022. https://doi.org/10.1155/2022/3639174.

[25] Nilesh Shelke, Sushovan Chaudhury, Sudakshina Chakrabarti, Sunil L. Bangare, G. Yogapriya, Pratibha Pandey, “An efficient way of text-based emotion analysis from social media using LRA-DNN”, Neuroscience Informatics, Volume 2, Issue 3, 2022, 100048, ISSN 2772-5286, https://doi.org/10.1016/j.neuri.2022.100048.

[26] Ajay S. Ladkat, Sunil L. Bangare, Vishal Jagota, Sumaya Sanober, Shehab Mohamed Beram, Kantilal Rane, Bhupesh Kumar Singh, "Deep Neural Network-Based Novel Mathematical Model for 3D Brain Tumor Segmentation", Computational Intelligence and Neuroscience, vol. 2022, Article ID 4271711, 8 pages, 2022. https://doi.org/10.1155/2022/4271711

[27] J. Alanya-Beltran, P. Narang, Taufikin, S. L. Bangare, C. Valderrama-Zapata and S. Jaiswal, "An Empirical Analysis of 3D Image Processing by using Machine Learning-Based Input Processing for Man-Machine Interaction," 2022 2nd International Conference on Advance Computing and Innovative Technologies in Engineering (ICACITE), 2022, pp. 2478-2482, doi: 10.1109/ICACITE53722.2022.9823699.