Assessment of surface water for drinking and irrigation purpose: eco-chemical study in chosen regions of Jaipur district, Rajasthan

Narendra Pal Lamba, Manmohan Singh Chauhan, Surabhi Jain*

Amity school of Applied Sciences, Amity University Rajasthan, Jaipur, 303002, Rajasthan

*Corresponding author E-Mail: sjain9681@gmail.com

Abstract

This study is included to assess the surface water excellence within the chosen areas (Jamwa-Ramgarh, Virat-Nagar, Bassi, Amber, Tehsils Jaipur district, Rajasthan) for three consecutive years (2019-2022) to discover a load of synthetic detergents on the environment and suitability of water for drinking and irrigational purpose. Nineteen surface water samples were collected and investigated for diverse Physico-chemical parameters. Appropriate methodologies were adopted for obtaining data for the analysis of surface water. All observation and results include physiochemical parameters- Sodium, potassium, alkalinity, hardness, PH, Water Quality Index (WQI), etc., as well as corrosive parameters such as Aggressive Index (AI), Langelier Saturation Index (LSI), Ryzner Index (RI), and irrigational parameters such as Percentage Sodium (percent Na), Sodium Adsorption Ratio (SAR), Exchangeable Sodium Percentage (ESP), and Residual Sodium Carbonate (RSC) are calculated and presented in tabular form with appropriate statistical analysis of data Obtained data has been compared with standards values prescribed by authentic agencies (WHO 2004, BIS 1991) to evaluate the load of synthetic detergents in domestic use.

Keywords surface-water assessment, physico-chemical parameters, water quality index, irrigation parameters

DOI Number: 10.14704/nq.2022.20.9.NQ440072 **Neuro Quantology 2022; 20(9):650-660**

Introduction

Feasible advancement of social and productive circumstances all through the world relies upon the openness of water exchequer. Water with appropriate quality and volume is required for the advancement of mechanical, cultivating, and house exercise **(Mirzabeygi et al. 2017).** As a considerable result of population development, water hobby for homegrown as well as agrarian and current usage is appreciably expanding. This has caused extreme usage of surface water belongings because of the precept water supply **(Chakraborty and Dey 2022)**. Since there may be a risk of natural contamination in-surface water, valid techniques need to be carried out for the expulsion of poisons. Synthetic cleansers have a large poison and are responsible for water and soil infection. In around 60 years of the formative duration of innovation Synthetic cleansers have supplanted cleansers in quite tons of each area besides more than one person's consideration purposes. Cleansers have each natural and inorganic component of their plan. The inorganic part of cleansers affects the physicochemical parameters of water and soil; (this paper thinks approximately simply water **(Mirzabeygi et al. 2016)** assessment) as a consequence the appraisal of water is vital. Various strategies of evaluation were taken to exercise were taken to exercise the exact water pleasant assessment. In this kind of manner, the water quality indices (WQI) adjustments over the water pleasant facts and available information from intricacy to straight forwardness for human beings in general and the administrant. All matters being equal, some markers are not extensive and want the opposite water pleasant/quality parameters to present a complete WQI that is a fundamental report/character of water quality. This technique is used for both surface and groundwater **(Soleimani et al. 2018); (MohseniBandpi et al. 2018)**Besides, creating ingesting water pleasant report (DWQI), the

Irrigation Water Quality Index (IWQI), was produced for assessment of the water quality in numerous utilizations(Mohammadi et al. 2017) Altogether, the character of the water gadget water ought to be assessed to avoid or limit opposed outcomes on farming (Zidane, Safi, and Sabri 2018). This approach is specified to be used in each out of the door and groundwater pleasant assessment this framework is referring to the appraisal gadget to DWQI added by (Sayato 1989) (Walker 1974); (Bartram et al. 1996) Other method given by (Mirzabeygi et al. 2017) for determination of IWQI. It seems there may be a want to pay attention to the evaluation of the floor water pleasant for ingesting and rural functions within side the selected Tehsils of Jaipur place Rajasthan, India. The factors of the modern evaluation which has been executed in the course of the three-yr checking duration have been to determine the physicochemical attributes of floor water in a delegated place and its pleasant appraisal for ingesting farming functions. Cleansers, the ability wellsprings of contamination have been taken into consideration on this focus on which would possibly affect the water quality within side the focused on the place. In every activity, cleansing cleansers are used definitely which subsequently finally ends up being giant for the surroundings affecting the Eco-examine of the location. Spoiling of undesired additives of chemical reasons a long stretch and slow ramifications for the concept of the place such as human prosperity; thusly it's far taken into consideration gainful to do present Eco substance research confused over.

Materials and method

Research Area

Surface water samples were collected from selected villages of Jamwa-Ramgarh, Bassi, Amber, Virat-Nagar, Tehsils are chosen for research which all is part of Jaipur district, it is one of the old cities of India, and maps are shows location of study area The main reason for choosing this particular study field, because of excessive Use of surface water for This area is used for domestic, agricultural, and commercial reasons.



Fig.1, 2 MAPS ARE SHOWING SAMPLING LOCATION

Field Work

To discover the load of synthetic detergents on surface water, 19 surface water samples were collected from four Tehsils (Jamwa-Ramgarh, Bassi, Virat-Nagar, and Amber) of Jaipur District. Water samples have been accrued in Polyethylene boxes cleansed with sampled surface water earlier than filling and appropriately labeled, throughout four seasons The assessment times in the evening and morning are 2019, 2020, and 2021 (pre-post-storm, winter-spring). The water sample that was taken from that site where the detergents exercises/activities are assessed high (hand pump, well, lake, ponds, river,). Conservation, collection, and research of the samples/checks/

trendy methods **(Idoko 2010); (Narsimha, Venkatayogi, and Geeta 2018)** have been used. The preference for locales is achieved to provide inclusion to the largest area of the Jaipur district. Observations and outcomes received throughout the 3 years of examination have been recorded in tabular form. These unique indices or limitations have been calculated within side the 3-year observe, for example, WQI, AI, LSI, % Na, SAR, ESP, and so forth for evaluation of drinking, domestic quality of water, and additionally agricultural, commercial use of water The outcomes/outcomes have been in comparison with the water fine trendy cost prescribed via way of means of extraordinary true organizations to reveal a restriction of contamination.

Laboratory Analysis

For calculation **(APHA 1992)** of PH electrometric technique was utilized, for Conductivity Laboratory Method was utilized, for TDS estimation technique was utilized, total alkalinity, Total Hardness, calcium and magnesium hardness, by the titration method, Chloride, Sulphate, Nitrate, Fluoride Ion-particular electrode method were used, The substance examination was completed according to the technique is given in**(Idoko 2010)**;**(Varol et al. 2012)**The insightful information got were polished for an exhaustive Eco-synthetic examination. The interionic connection charts, **(Bartram et al. 1996)**outline, **Wilcox(1948)** graph, LSI results, WQI results, and different boundaries results were arranged to utilize Microsoft Excel Version 2007.

Results and discussion

Water quality index

Water quality assessment changed into finished utilizing WQI, that's broadly applied for surveying ingesting/drinking the state of the water In addition to groundwater standard appraisal, the WQI is also specified for use in outside/surface water. Brown et al. wrote, "The WQI changed before everything was proposed via way of means" **(Khairy et al. 2022)**"Using WQI could help with understanding the combinatorial effect of each boundary in addition to all subjective limits on swallowing water quality," according to reviews In 2004, the "World Health Organization (WHO)" published a report. In this way, the WQI might be utilized as a dependable tool for surveying and rating the character of water wells. Each subjective boundary's well worth is resolved grounded on the counseled morals and associated with distinctive limitations. To verify the WQI, the well worth of physicochemical limitations has been allotted via way of means of the overall means of limitations within side the well-known nature of water for ingesting/drinking. The overall weight changed into processed utilizing the accompanying condition:

$$W = K\backslash S$$

Where: "K" stands for the proportionality constant. “Sn” = the maximum value of the n parameter that can be used. “W” = "n^{th}”parameter unit weight overall WQI represented by

$$\sum_{n=1}^{n=10} Qn.Wn \,/\, \sum_{n=1}^{n=10} Wn$$

Where; Qn = Subindex, Qn = Index, Qn = Index, Qn = n = Number of boundaries taken, Vn = observed worth of an nth boundary, Sn = standard worth of an nth border, V1= perfect pH=7.0, DO=14.6 6 mg/L, and other values and any remaining boundaries = zero.

In the wake of gathering the outcomes, the centralization of every contamination was changed over into a WQI. The all-out amount of all toxins WQI turned into the by and large WQI for a specific/chosen area. Higher value of WQI represent the water is not suitable for drinking and domestic use, and, the more prominent the harm to wellbeing.

Table 1. Assigned unit weights of various water quality parameters for Jamwa-ramgarh tehsil during 2019-2021, compared with standard values of World Health Organization (WHO 2009) (Sayato 1989).

PARAMETERS	MINIMUM	MAXIMUM	AVERAGE	St. DEVIATION	WHO 2004 St.(s_i)	BIS 1991	WIGHT (w_i)	RELATIVE WEIGHT (W_i)
PH (on scale)	7.6	8.2	7.921429	0.196815304	6.5-8.5	6.5–8.5	4	0.12121
TDS	91	460	229.6667	116.7553405	500-2000	500	4	0.12121
Total Alkalinity(mg/l)	164	622	371.2667	133.5308775	200-600	-	2	0.06061
Total Hardness(mg/l)	90	570	266.7333	133.7932663	300-600	-	2	0.06061
Ca^{+2} (mg/l)	60	**290**	151.8	66.92981398	75-200	75	2	0.06061
Mg^{+2} (mg/l)	30	**280**	115	68.81133628	30-150	30	3	0.09091
Cl^- (mg/l)	17	110	54.46667	25.58142928	250-1000	250	3	0.09091
SO_4(mg/l)	29	250	102.5333	78.99897528	200-400	200	4	0.12121
NO_3(mg/l)	20	61	36.66667	12.06332498	45-100	45	4	0.12121
F^-(mg/l)	0.1	0.3	0.157333	0.054702659	1.0-1.5	-	5	0.15152
Total	-	**-**	-	-	-		**33**	**1.000**

Table 2. Assigned unit weights of various water quality parameters for Virat-nagar tehsil during 2019-2021 compared with standard values of World Health Organization (WHO 2009) (Sayato 1989).

PARAMETERS	MINIMUM	MAXIMUM	AVERAGE	St. DEVIATION	WHO 2004 St.(s_i)	BIS 1991	WIGHT (w_i)	RELATIVE WEIGHT (W_i)
PH (on scale)	7.6	8.2	7.9	0.196815304	6.5-8.5	6.5–8.5	4	0.12121
TDS	86	300	167	116.7553405	500-2000	500	4	0.12121
Total Alkalinity(mg/l)	144	441	276.8	133.5308775	200-600	-	2	0.06061
Total Hardness(mg/l)	141	**315**	216.2667	133.7932663	300-600	-	2	0.06061
Ca^{+2} (mg/l)	60	**241**	135.2667	66.92981398	75-200	75	2	0.06061
Mg^{+2} (mg/l)	20	**148**	86.86667	68.81133628	30-150	30	3	0.09091
Cl^- (mg/l)	30	100	60.6	25.58142928	250-1000	250	3	0.09091
SO_4(mg/l)	26	204	106.0667	78.99897528	200-400	200	4	0.12121
NO_3(mg/l)	10	33	23.73333	12.06332498	45-100	45	4	0.12121
F^-(mg/l)	0.1	0.2	0.126667	0.054702659	1.0-1.5	-	5	0.15152
total	-	**-**	-	-	-		**33**	**1.000**

Table 3. Assigned unit weights of various water quality parameters for Bassi tehsil during 2019-2021, compared with standard values of World Health Organization (WHO 2009) (Sayato 1989).

PARAMETERS	MINIMUM	MAXIMUM	AVERAGE	St. DEVIATION	WHO 2004 St.(s_i)	BIS 1991	WIGHT (w_i)	RELATIVE WEIGHT (W_i)
PH (on scale)	7.8	8.2	7.946667	0.150554531	6.5-8.5	6.5–8.5	4	0.12121
TDS	126	364	234.0667	69.63934301	500-2000	500	4	0.12121
Total Alkalinity(mg/l)	145	415	245.5333	71.98498521	200-600	-	2	0.06061
Total Hardness(mg/l)	142	**510**	271.4	99.92554371	300-600	-	2	0.06061
Ca^{+2} (mg/l)	80	**300**	167.933	56.85001152	75-200	75	2	0.06061
Mg^{+2} (mg/l)	25	**217**	104.4	59.93663321	30-150	30	3	0.09091
Cl^- (mg/l)	30	140	66.93333	26.53156252	250-1000	250	3	0.09091
SO_4(mg/l)	54	211	115.9333	46.178948	200-400	200	4	0.12121
NO_3(mg/l)	20	70	43.06667	11.88316136	45-100	45	4	0.12121
F^-(mg/l)	0.08	0.14	0.112	0.01698739	1.0-1.5	-	5	0.15152
total	-	**-**	-	-	-		**33**	**1.000**

Table 4. Assigned unit weights of various water quality parameters for Amber tehsil during 2019-2021, compared with standard values of World Health Organization(WHO 2009) (Sayato 1989)**.**

PARAMETERS	MINIMUM	MAXIMUM	AVERAGE	St. DEVIA.	WHO 2004 St.(s_i)	BIS 1991	WIGHT (w_i)	RELATIVE WEIGHT (W_i)
PH (on scale)	7.7	8.7	8.066667	0.308466392	6.5-8.5	6.5–8.5	4	0.12121
TDS	7.8	214	125.725	79.96643756	500-2000	500	4	0.12121
Total Alkalinity(mg/l)	142	340	230.25	67.37294439	200-600	-	2	0.06061
Total Hardness(mg/l)	134	320	234.5	72.13686487	300-600	-	2	0.06061
Ca^{+2} (mg/l)	10	160	124.5833	46.27871754	75-200	75	2	0.06061
Mg^{+2} (mg/l)	30	**161**	84.08333	41.77310647	30-150	30	3	0.09091
Cl^{-} (mg/l)	2	85	37.25	26.38913344	250-1000	250	3	0.09091
SO_4(mg/l)	13	62	41.25	17.31066408	200-400	200	4	0.12121
NO_3(mg/l)	20	72	38.25	15.1425049	45-100	45	4	0.12121
F^{-}(mg/l)	0.09	0.13	0.114167	0.013113722	1.0-1.5	-	5	0.15152
total	-	**-**	-	-	-		**33**	**1.000**

In the wake of aggregating the outcomes; the convergence of every pollutant was changed over into a WQI. The absolute amount of all toxins WQI turned into the by and large WQI for a particular location. The higher the WQI score, the more contaminated the water is and the bigger the risk to human health. Water quality order in light of WQI values classes in 5 gatherings given(WHO 2009) WHO 2009 rules.

Table 5. WQI Water quality index results for particular sample

S.No. (sample no.)	WQI Value	Water quality type
1	88.80	Water quality is Good
2	130	Water quality is Poor
3	90	Water quality is Good
4	110	Water quality is Poor
5	60	Water quality is Good
6	70	Water quality is Good
7	65	Water quality is Good
8	74	Water quality is Good
9	80	Water quality is Good
10	109	Water quality is Poor
11	122	Water quality is Poor
12	79	Water quality is Good
13	80	Water quality is Good
14	118	Water quality is Poor
15	90	Water quality is Good
16	93	Water quality is Good
17	90	Water quality is Good
18	92	Water quality is Good
19	85	Water quality is Good

Evaluation of water for the irrigational use/industrial purpose

Irrigational Parameters

The amount and synthesis of broken-down basics in water layout its greatness for cultivating use over the top focus. Broken-up particles in cultivating change soil arrangement, porousness, and air circulation that straightforwardly trouble plant improvement **(Zhang et al. 2022);(Chen, Gutowski, and Sternweis 2018); (Evangelides and Arampatzis 2018)**. The amount and creation of broken-up fundamentals/components in water layout its greatness for cultivating use. Extreme swabs in the water system restrain the development of a plant through physical means, such as limiting water uptake through osmotic tension contrasts, and by compound ways, such as altering metabolic processes (Caliciotti et al. 2018). Seepage is a significant component related to plant development. Notwithstanding,

a water system with a liberal amount of saline water might prompt the creation of the yield, however, an inadequately depleted region might neglect to develop the agreeable harvest in any event, when flooded with great quality water **(Narsimha, Venkatayogi, and Geeta 2018); (Amoo, Fagbenle, and Oyewola 2022)**. The boundaries like EC, percent sodium (%Na), sodium adsorption proportion (SAR), RSC, are vital to layout the wellness of surface water for rural/agriculture use **(Kayode, Okagbue, and Achuka 2018).**

Percent sodium and electrical conductance

Percent sodium and Electrical conductivity (%Na and EC) chosen for the surface water quality for agriculture purpose. The degree/extent of Sodium among all of the cations present in water is typically conveyed/imparted like percent sodium.

$$\% Na = \frac{Na^+}{[K^+ + Na^+ + Ca^{2+} + Mg^{2+}]} \times 100$$

(Ca^{+2}, Mg^{+2}, k^+ and Na^+ ions are in meg/l.)

Sodium Adsorption Ratio (SAR)

Ratio of sodium ion and square route of calcium and magnesium ion.SAR use for the checking the water quality for agriculture purpose. Represent by following equation.

$$SAR = \frac{Na^+}{\sqrt{\frac{Ca+2 + Mg+2}{2}}}$$

(Above ions of equation are in meq/l.)

Exchangeable Sodium Percentage

It is a also irrigation parameter use for the determine the water quality for agriculture purpose. It is determined with the assistance of the accompanying condition

$$ESP = \frac{100\ (-0.0126 + 0.01475\ SAR)}{1 + (-0.0126 + 0.01475\ SAR)}$$

Table 6. Classification of irrigational water as per Wilcox (1948)

PARAMETERS	CLASS	LIMIT
%Sodium	superb	<20
	good quality	20-40
	allowed	40-60
	unsure	60-80
	inappropriate	>80
Electrical Conductance (µS/cm)	Excellent	<250
	Good	250-750
	Permissible	750-2250
	Doubtful	2250-300
	unsuitable	>3000

655

Table 7. Classification of irrigational water as per Richard (1954)

PROBLEMS	PARAMETERS	CLASS	LIMIT
Salinity Hazard	Electrical Conductance (µS/cm)	small (C_1)	100-250
		average(C_2)	250-750
		elevated (C_3)	750-2250
		extremely High(C_4)	2250-5000
Sodium (Alkali) Hazard	Sodium Adsorption Ratio (SAR)	small (S_1)	0-10
		average (S_2)	10-18
		elevated (S_3)	18-26
		Extremely High(S_4)	>26

Residual Sodium Carbonate (RSC)

Water can be classified into three groups based on RSC: safe category "1.25 meq/l," hardly category "1.25-2.5 meq/l," and inadmissible category "2.5 meq/l." During the current investigation, it was discovered that each of the samples falls within the protected class. It is also use for the checking the water quality for irrigation purpose and determine by following equation.

$$RSC = (CO_3^{-2} + HCO_3^-) - (Ca^2 + Mg^2)$$

Corrosive Parameters

Aggressive Index (AI)

Aggressive index is determined by the pH, (TH) is the complete hardness in mg/L as CaCO3 and,

(TA) is the absolute hardness in mg/L as CaCo3, it is calculated by following equation.

Aggressive index = log (TA.TH) + pH

"Aggressive index esteems under 10 demonstrate profoundly forceful water; values somewhere in the range of 10.0 and 12.0 show reasonably forceful water as well as standards more prominent than 12.0 demonstrate non-powerful water".

Ryznar Index (RI)

The Ryznar steadiness/stability is a precise method for expecting to scale penchants of water-subject to an examination of working results with various drenching/immersion lists of water.

RI = 2pHs-pH = pHs–Langelier immersion pH

Langelier Saturation Index (LSI)

It implies that recognizing pH as an expert variable is the most important motivation for scale improvement/association and development. It is an equilibrium report that addresses the Thermodynamic fundamental drive for the development of a calcium carbonate scale recreation plan. It makes no mention of how much calcium carbonate or scale will cause the conveying water to change? Consider the following if LSI is negative: CaCO3 is soluble in water and does not precipitate. The scale can form and CaCO3 precipitation can occur if the LSI value is positive. Assume LSI is near zero and scale potential on the periphery. To calculate the LSI, you'll need to know the water's alkalinity (mg/L CaCO3), total hardness (mg/L CaCO3), totally disintegrated solids (mg/L TDS), pH, and temperature (°C).

$LSI = pH-pH_s$ (1)

pH stands for "potential hydrogen" in water. PH 656

pHs is defined as the pH of calcium carbonate when immersed in calcite.

$pH_s = (9.3 + A+B) - (C+D)$ (2)

$A = (\log10 [TDS] – 1)/10$ (3)

$B = -13.12 X \log10 (°C + 273) +34.55$ (4)

C = log 10 [TH as CaCO3] - 0. 4 (5)

D = log 1o [total alkalinity as CaCO3] (6)

It demonstrates the initial impulse for scale arrangement and advancement with pH as a specialized variable. It maintains a balanced record and deals with a variety of issues. LSI exploitation conditions (1) were determined from separated/examined data (6). Using the Langelier condition, it was feasible to anticipate the propensity of standard or altered water to store calcium carbonate or weaken calcium carbonate. This predicts the water's inclinations to scale or resist. If the water isolates calcium carbonate, the water is unpleasant, and if the calcium carbonate is stored, the water has a negative value. It's a scaling trend within Table-8 concomitant, and a positive value consciousness of LSI values.

Table 8. Represent the Langelier saturation index result.

index	Appearance	Water quality issues
-4	Very harsh corrosion	Conditioning required
-3	Harsh corrosion	Conditioning frequently recommended
-2	reasonable corrosion	a few conditioning is recommended
-1	gentle corrosion	require a few conditioning
-.5	small corrosion	might require a few conditioning
0.00	fair	Conditioning frequently not compulsory
.50	weak scale coating	Conditioning frequently not suggested
1.00	minor scale/Encrustation	a few diagram appearance concerns
2.00	gentle scale/Encrustation	Should consider some conditioning
3.00	reasonable scale/Encrustation	Should utilize a few condition
4.00	harsh scale/Encrustation	Conditioning frequently required

Table 9. Interpretation of Ryznar Index (RI) test results

SATURATION INDEX	APPEARANCE/DESCRIPTION	WATER CODITION COMMENTS
4.0-5.0	serious Scaling	Non-Aggressive, Non-Corrosive
5.0-6.0	reasonable Scaling	Non-Aggressive, Non-Corrosive
6.0-7.0	small Scaling	small Corrosion, Balanced Saturation
7.0-7.5	Non Scaling, Corrosive	Aggressive, below Saturation
7.5-9.0	Heavy Corrosive	extremely Aggressive, reasonable Corrosive
9.0 and Above	harsh Corrosion	enormously Aggressive, extremely Corrosive

Table 10. Calculated indices average (irrigation, corrosive parameter) value obtaining after three year investigation

CALCULATED INDICES	JAMWA-RAMGARH		VIRAT-NAGAR		BASSI		AMBER	
	Mor./sunrise	Eve./sunset	Mor./sunrise	Eve./sunset	Mor./sunrise	Eve./sunset	Mor./sunrise	Eve./sunset
WQI	96.09	89.138	20.19	20.71	19.78	18.48	92.80	92.66
AI	12.8	12.98	7.01	7.66	13.05	11.38	12.9	13.06
LSI	0.91	1.064	6.0	6.8	13.02	11.18	.96	1.14
RI	5.9	5.99	7.04	8.00	15.79	13.28	6.09	5.90
%Na	53.08	54.00	7.29	8.45	17.93	14.94	44.14	41.68
SAR	4.16	4.27	.21	.025	3.2	2.35	3.04	2.66
ESP	4.76	4.69	-0.43	-0.53	2.79	1.99	2.97	2.58
RSC	1.958	1.97	-1.82	-2.5	1.14	.8	0.78	0.465

Discussion

Electrical the scientific boundaries and lists could be used to recognize the acceptability of water quality for various applications such as drinking or water systems. The city of Jaipur is a contemporary metropolis in Rajasthan. Because of the lack of treatment capacity at treatment plants, the majority of the city's wastewater is discharged directly into natural water bodies such as rivers, lakes, and lakes. The impurities/contamination also reaches the surface water, causing it to be harmful to human health. The table shows the effects of factual variables such as physicochemical borders, destructive limits, and irrigational boundaries of surface water in the Jamwa-Ramgarh, Virat-Nagar, Bassi, and Amber tehsil areas. The temperature ranges from 19°C to 24°C, with the average being 21.3°C. The association's pH level almost became within side the normal attain which suggests the water can respond with base or acidic substances leaving within side the water. As in step with the WHO rule, the usual furthest reaches of pH within side the water are 6.5-8.5 final results receives in the breaking point. Electrical conductivity on this observes modified from 130-580µS/cm which provides the excessive degree of salts within side the floor water. Moreover, TDS, absolute alkalinity, chloride, sulfate, fluoride, and nitrate are in as far as possible exemption complete hardness, calcium, the magnesium viewed as out of the cutoff in surface water because of advancement of salts in the surface water. It very well may be additionally a result of the cooperation of rock and water and rural exercises. Getting information of WQI uncovers that a Few records were viewed as in great quality and a few records are in poor quality so gentle treatment is essential before use for homegrown and drinking purposes. AI records presented the water having low scaling/ non-forceful.

Information of LSI uncovers that the idea of surface water tests of the review region was neither extreme destructive nor serious scale/encrustation however generally gentle treatment is required. RI results uncover that Jamwa-Ramgarh surface water has the propensity of Moderate Scaling, Virat-Nagar surface water inclines Heavy Corrosive, Virat-Nagar surface water keeps an eye on Severe Corrosion, and Amber surface water tends Moderate Scaling. %Na results uncover that a greater part of the information under as far as possible (40-60), a few outcomes were in suspicious class (60-80), and remaining outcomes show un-suitable for water system purposes. Generally, we can say assuming water has a higher measure of sodium particles that water isn't reasonable for water system purposes. Characterization of surface water tests according to US Agricultural standards uncovers that one record was in medium (S2) class remaining outcomes are in low (S1) class. In this way, the utilization of surface water for farming was having low salt dangers. Order in Electrical conductivity and SAR (table 7) shows that one record was of C2S2 class, 12 records were of C2S1 class, and 6 records of C1S1 class. RSC (Residual Sodium Carbonate) information got after a dissected example in four significant seasons in progressive three years uncovers that 10 records were of amazing class, 5 records are in great class and other 4 records were in unsuitability of class.



Fig.3. the triangular diagram for the surface water sample in study region



Fig.4. Concentration of nitrate during study period.

Conclusions

The customary Eco-synthetic strategies and quality records are utilized to figure out the situation with surface water quality for its usage in drinking and agribusiness purposes. It has a tendency to be reasoned that the Eco-science of the overview district is confined through each every day and anthropogenic variable. The surface water of the overview locales is impartial to rather antacid, due to the deluge of HCO3 debris within side the floor water spring, that's introduced through the reaction CO2 concentrations in soil and water Figure 3 also shows a Piper triangle diagram for the water type on the other side of the look at point. The amounts of sulphate and chloride, as well as calcium and magnesium, are high, according to the findings. The desire for cation overflow is Ca > Na > Mg > K, according to hydro geochemistry. All the water tests include pH esteem inside as far as possible saw by WHO (2004). Given TDS, the whole examples were inside the scope of alluring to admissible for the end goal of drinking. A little over half of the tests of surface water in the review area are good for the end goal of drinking with the little precautionary measure as the vast majority of the boundaries are inside as far as possible set by WHO (2004). Out hardness (magnesium hardness, calcium hardness) contamination is a significant issue in the review area, as 40% of tests have an all-out hardness fixation more than the (WHO 2009) consent limit. The principle wellspring of hardness in the surface water is homegrown sewage (cleansers) and creature excreta water and overabundance compost input. In the wake of ascertaining different lists and proportions which are broadly utilized in the exploration to

evaluate the wellness of surface water for horticulture purposes, it tends to be inferred that virtually every one of the examples is alright for agrarian use. The results acquired from the review will be useful to perceive the surface water quality condition for productive administration and utilization of surface water assets for drinking and water system use. The surface water tests having a high absolute hardness focus need medicinal measures before consumable purposes. Bioremediation, physical adsorption, reverse osmosis, ion exchange, and elctrodialysis are a portion of the accommodating strategies for complete hardness disposal for safe drinking water of locales,

Acknowledgement This paper was financially supported in part by the research committee at the Amity University of Jaipur Rajasthan. I would like to thank my supervisor assistant professor **Dr. Narendra Pal Lamba, Dr. Manmohan Singh Chauhan** in the department of chemistry, amity school of applied sciences, amity university Jaipur, for her useful advice for improving the quality of this paper.

References

Amoo, O. M., R. O. Fagbenle, and M. O. Oyewola. 2022. "A Comparative Analysis of Numerical Methods Applied to Nonsimilar Boundary Layer-Derived Infinite Series Equations." *Ain Shams Engineering Journal* 13(5): 101713. https://doi.org/10.1016/j.asej.2022.101713.

APHA. 1992. "American Public Health Association Method 3112: Standard Methods for the Examination of Water and Wastewater." *Methods for examination of water and wastewater* 552: 7.

Bartram, Jamie., Richard. Ballance, United Nations Environment Programme., and World Health Organization. 1996. *Water Quality Monitoring : A Practical Guide to the Design and Implementation of Freshwater Quality Studies and Monitoring Programmes*. E & FN Spon.

Caliciotti, Andrea, Giovanni Fasano, Stephen G. Nash, and Massimo Roma. 2018. "Data and Performance Profiles Applying an Adaptive Truncation Criterion, within Linesearch-Based Truncated Newton Methods, in Large Scale Nonconvex Optimization." *Data in Brief* 17: 246–55. http://dx.doi.org/10.1016/j.dib.2018.01.012.

Chakraborty, Rubi, and Arindam Dey. 2022. "Probabilistic Assessment of Seismic Response of Toe-Excavated Hillslopes Retained Using Anchored Sheet-Pile-Wall." *Ain Shams Engineering Journal* 13(5): 101736. https://doi.org/10.1016/j.asej.2022.101736.

Chen, Zhe, Steven Gutowski, and Paul C. Sternweis. 2018. "Crystal Structures of the PH Domains from Lbc Family of RhoGEFs Bound to Activated RhoA GTPase." *Data in Brief* 17: 356–62. http://dx.doi.org/10.1016/j.dib.2018.01.024.

Evangelides, Chris, and George Arampatzis. 2018. "Data for Moisture Measurements during Vertical Absorption in Building Porous Materials Such as Brick and Limestone." *Data in Brief* 17: 575–78. http://dx.doi.org/10.1016/j.dib.2018.01.067.

Idoko, Ocheri Maxwell. 2010. "Seasonal Variation in Iron in Rural Groundwater of Benue State, Middle Belt, Nigeria." *Pakistan Journal of Nutrition* 9(9): 892–95.

Kayode, Olusola T., Hilary I. Okagbue, and Justina A. Achuka. 2018. "Water Quality Assessment for Groundwater around a Municipal Waste Dumpsite." *Data in Brief* 17: 579–87. http://dx.doi.org/10.1016/j.dib.2018.01.072.

Khairy, S. et al. 2022. "Drainage Water Reuse Strategies: Case of El-Bats Drain, Fayoum Governorate, Egypt." *Ain Shams Engineering Journal* 13(5): 101681. https://doi.org/10.1016/j.asej.2021.101681.

Mirzabeygi, Majid et al. 2016. "Evaluation of Corrosion and Scaling Tendency Indices in Water Distribution System: A Case Study of Torbat Heydariye, Iran." *Desalination and Water Treatment* 57(54): 25918–26.

———. 2017. "Evaluation of Groundwater Quality and Assessment of Scaling Potential and Corrosiveness of Water Supply Networks, Iran." *Journal of Water Supply: Research and Technology - AQUA* 66(6): 416–25.

Mohammadi, Ali Akbar et al. 2017. "Skeletal Fluorosis in Relation to Drinking Water in Rural Areas of West Azerbaijan, Iran." *Scientific Reports* 7(1): 4–10. http://dx.doi.org/10.1038/s41598-017-17328-8.

MohseniBandpi, Anoushiravan et al. 2018.

"Health Risk Assessment of Heavy Metals on PM2.5 in Tehran Air, Iran." *Data in Brief* 17: 347–55. http://dx.doi.org/10.1016/j.dib.2018.01.018.

Narsimha, Adimalla, S. Venkatayogi, and S. Geeta. 2018. "Hydrogeochemical Data on Groundwater Quality with Special Emphasis on Fluoride Enrichment in Munneru River Basin (MRB), Telangana State, South India." *Data in Brief* 17(126): 339–46. http://dx.doi.org/10.1016/j.dib.2018.01.059.

Sayato, Yasuyoshi. 1989. "WHO Guidelines for Drinking-Water Quality." *Eisei kagaku* 35(5): 307–12.

Soleimani, Hamed et al. 2018. "Data on Assessment of Groundwater Quality for Drinking and Irrigation in Rural Area Sarpol-e Zahab City, Kermanshah Province, Iran." *Data in Brief* 17: 148–56.

Varol, M., B. Gökot, A. Bekleyen, and B. Şen. 2012. "Water Quality Assessment and Apportionment of Pollution Sources of Tigris River (Turkey) Using Multivariate Statistical Techniques-a Case Study." *River Research and Applications* 28(9): 1428–38.

Walker, Russell C. 1974. "On $B\mathbb{N}$ and $\mathbb{N}^*$." *The Stone-Čech Compactification*: 70–94.

WHO. 2009. "Boron in Drinking-Water." *WHO, Geneva, Switzerland*: 1–36. http://scholar.google.com/scholar?hl=en&btnG=Search&q=intitle:N-Nitrosodimethylamine+in+drinking-water+Background+document+for+development+of+WHO+Guidelines+for+Drinking-water+Quality#0.

Zhang, Xu, He Cheng, Youjun Xu, and Hongliang Li. 2022. "A Case Study on Performances of Overlying Pipelines Due to Shallow Tunnels Excavation in Water-Rich Gravel Ground." *Ain Shams Engineering Journal* 13(5): 101746. https://doi.org/10.1016/j.asej.2022.101746.

Zidane, Mohammed, Said Safi, and Mohamed Sabri. 2018. "Measured and Estimated Data of Non-Linear BRAN Channels Using HOS in 4G Wireless Communications." *Data in Brief* 17: 1136–48.