Energy Supervision System for Ship Hybrid Power System Based on Renewable Energy Resources

John De Britto C[1*], V.Loganathan[2], Dr.S.T.Subha[3], Elakkiyavendan R[4]

Assistant Professor[1*], Department of EEE, Saveetha Engineering College, Chennai-602105, Tamilnadu, India.
Research Scholar[2], Faculty of Electrical Engineering , Anna University Chennai- 600 025.
Professor[3],Department of EEE,Veltech Multitech Dr Rangarajan Dr Sakunthala Engineering College, Avadi, Chennai-600 062, Tamilnadu, India.
Research Scholar[4], Department of EEE, Anna University Regional Campus Coimbatore– 641 046.
Email id: yjohnde@gmail.com[1*],logu_pm@yahoo.co.in[2], thaisubha@gmail.com[3],elakkiyavendan@gmail.com[4]

Abstract-A combination of ship power system comprised of fuel cells and storeroom system super capacitors is possible.Residential by incorporating renewable power sources. The addition of PV to the Proposed system improves the system's dependability and reliability. A powerful control approach, however, is required. Control the measured power among the fuel cell and the photovoltaic show the best moment to charge or set free the stored power based on load claim .The ideal solution is to control the ship's hybrid propulsion system using an intelligent neural network technique. Because of the nonlinearity of the method and the commonness of pulsing and high immensity load demand. A critical component of an cleversupervision scheme is managing the leakage of a hybrid system in response to switch in shipmentrequest and battery state of charge (SoC) by means of the ANFIS/Simulink toolbox, which setup a aim. Based on adaptive neuro-fuzzy measures, this paper fine-tunes a hybrid powerbasis for use in a marine ship's unvoicedstyle of functionat the same time aslook for submarines through a low auralcross. The most importantidea of this scrutiny is to measure up to the effectiveness of the plannedstructure preserving with sensiblegrades obtained startingearlierjob. These studies presentchief insights keen on the surge of EMS in hybrid power systems on the marinepitch.

Keywords- condition mining, Machine learning, Ship emotional power system, All-electric ship Energy supervision system, Integrated power system, Adaptive neuro-fuzzy inference system ANFIS Training system.

I. Introduction

Several syntheticbrainpower applications in direct systems comprised and introduced more the last century Artificial intelligence (AI) methods are necessary in recentexcitingweight systems. When a range of power fabrication systems are connected to the grid, the inbuiltworries of solar and wind energy guide to difficulty in supremacy system recital, shipment forecasting, guardand organize. Fuzzy logic (FL), adaptive fuzzy logic (AFL), expert systems (ESs), artificial neural networks (ANNs), genetic algorithms (GAs), and adaptive neuro-fuzzy twisting upschemes are all (AI) models worn in electric power systems (ANFIS). The worldwide Maritime Organization's (IMO) initial sea green House Gas (GHG) policy to speed up building industry decarburization pains [1]. The emotional ship was the modelkey for dropping GHG emissions by thrilling ship tools [2]. All-electric ships (AES) techniques have been urbanized by the Navy, allowing all ship's masses, momentum system, and examinationmasses to be motorized from the same power supply [3]. All-Electric Ships agree to for condensed greenhouse gas emissions and a greater use of renewable and sustainable energy in marineships [4]. The naval ship takes advantage of this opportunity to grow in this field. Loads on a naval ship include not simplymomentum system loads, but also missile and sensor loads. All ship systems must be electrified, and an integrated power system is required (IPS).

Artificial Intelligence (AI.) provides solutions to multiparteffort in power system engineering, which was previously difficult and time-consuming[7]. Though, the Hybrid renewable energy structure shines as the ample use of renewable energy payable to the presence of quite a fewno uniformenergy. These ships' hybrid power systems are traction systems that require control and management [8]. These strategies differ depending on the vehicle application [9, 10]. Autonomous Vehicles represent a new trend [11]. Fuzzy logic is second-hand to organize the real-time design of a power management scheme for a hybrid exciting traction scheme in order to avoid overcharging of the storage battery all throughcyclic braking energy gathering [12].

Artificial neural networks (ANN) and machine knowledge are used to shield the mistake in a shipboard power system[13, 14]. The ANFIS adaptive neuro-fuzzy technique is used to control the hybrid system's strategy, which includes fuel cells, PV, and wind energy [15, 16].A battery running system (BMS) is required for the batteries to function properly. State of Charge (SOC) is an important item in BMS that indicates the indict level of the batteries and belongs to the interior states of the battery[17].The models were created using commercially available components and implemented in the MATLAB-Simulink environment. The implemented control is based on a plan of correspondinguse

eISSN 1303-5150

minimization. It enables appropriate energy administration of the mixture system, reducing hydrogen consumption [18].This document describes the proposal of a power converter for electric vehicle (EV) applications powered by a Li-ion battery (LiB) and a super capacitor (SC). The combination of these energy sources is a good solution for improved performance [19].an ANN relay to identify the position of the fault on the electrical division system Maintaining the truthfulness of a shipboard controlscheme in the happening of severalinstantaneous electrical faults is compulsory to make certain that all loads be givencontinualcheckindifficult combat setting[20].The ship's combination energy power classification is completed up of quite a few non-homogeneous powerincome such as a diesel maker, a renewable powerestablishment or more, an energy-storing scheme, and maybe hydrogen fuel cells. To make sure system stability and steadiness, the EMS manages and wheel the equilibriumamongunlike types of sources and consignmentorder [21].on the whole, artificial intellect is the skill to use computers to crack some compoundtroubles, such as pictureappreciation, and to moderator the capability to know the crisis [22].

II.Detailed Procedure on ANN

The ANFIS modus operandidetermination be accepted out based on the cultureeffect obtained from the preceding trial or individualpractice. This is a profit of by means of ANFIS, more than ever for nonlinear systems that necessitate a fastresult in real-time.

The broad energy management scheme will be introduced in this scheme, and depending on the request, the scheme with fuel cell and storage gap system (battery, super capacitor) can be second-hand in aeroplane ships, or cars. The merelydivision is the EMS's aim for The peakmain concern for marine ships is planeprotection. The peakambition for automobiles is fidelity. The chiefambition is to lessen fuel expenses. With the discovery of hazy techniques in control applications, manufacturers are looking for an regulareducation process to holdmanufacturing applications. The Adaptive Neuro-Fuzzy Inference System (ANFIS) was a explanation that mutual the reimbursement of both the informationcapability of reproduction neural networks (ANN) and the suppositionpotential of rule-based fuzzy logic organize to achieve a complete set of all types of feed-forward neural networks with supervised informationmeans. The ANFIS system achieves a hybrid educationpractice based on professionalfacts and input-output data.

a)Higher potential SoC

Because the control stored in the battery in this mode is superior than the favoured energy for battery fitness, the PI energy runningscheme regulates the fuel cell powershaped to be a smaller amount than the require load.

The concretecobalt line defines the energetic load require, and the red line enumerates the twisted fuel cell controlunderneath the load correct curve. That is, the load require is met by equally the battery and the fuel cell.

b)Lower potential SoC

The red line represents fuel cell energy output, and the incredibly hard blue line represents active load demand. A buck-boost bidirectional converter is used by the PI energy management device to charge the battery when the energy produced by the fuel cell is more than the load demand at t = (0-90) seconds, as seen by the lower diagram's negative drained current. The fuel cell power remains steady at 7 kW as the load demand rises from 7 kW to 10 kW at t = (90-130) s. At t = 130 s, the current battery changes to discharge and make power available to the load. At t = 170 s, the load reaches 7 kW, and at t = 170 s, the fuel cell power remains stable at 7 kW.

III. The proposed architecture of the Energy Management System with ANFIS model

A battery that is directly linked to the dc bus is charged and discharged using a DC/DC bidirectional buck-boost set converter. The battery's energy is controlled by the battery management system (BMS), which also safeguards the battery against excessive charging and dischargingand heating up. The DC bus structure works in tandem with a DC/AC three-phase inverter to provide demand loads by converting DC electricity to three-phase AC power.

eISSN 1303-5150



Fig.1 The proposed architecture of the Energy Management System with ANFIS model.



Fig.2 An optimized design of ANN.

Characteristically, algorithms are used to optimise weights, systembuilding, learning rules,

Time in sec	EMS Input			EMS Output	
	S.O.C	O/P Power	Light Intensity	F.C Power	P.V Power
0	90	6	0	8.3	0
1	85	6	1	0	8.2
2	85	7	0	8.3	0
3	75	8	0	7.6	0
4	65	8	0	7.6	0
5	55	9	1	0	9.2
6	55	7	1	0	8.3
7	65	8	1	0	6.2
8	65	5	0	7.5	0
9	70	6	0	7.5	0
10	80	7	1	0	8.5
11	80	8	0	7.2	0
12	70	6	1	0	9.4
13	75	7	0	7.3	0
14	60	10	1	0	9.3
15	70	11	1	0	10.2
16	80	12	1	0	9.3
17	90	5	1	0	8.2
18	80	8	0	7.3	0
19	90	9	0	7.2	0
20	80	8	0	7.2	0
21	70	7	1	0	5.6
22	80	9	0	7.2	0
23	90	9	1	0	5.2
24	95	10	1	0	8.6
25	95	8	1	0	8.2
26	95	7	0	6.3	0

neurons, launchmeaning, and prejudice. An additional method for optimising and getting better the ANN is to use an reducer to put rear the neural network's unique algorithms by means of optimization algorithms, and to restoreback spread with any optimization techniques to resolvepositiveassociated issues. However, in its place of back-propagation, employ an optimization algorithm, such as the Liebenberg Marquardt neural net with any

eISSN 1303-5150

optimization techniques for quick or precise neural systemeducation. This re-examine focuses on getting better neural networks by optimising algorithms that switch neural network parameters or guidance parameters to locate the greatestconfigurationset-up pattern to solve trouble with high precision and speed.

IV. Simulation Results

The ANN-based energy management organization's evaluation of the MATLAB simulation.Marine at two intervals based on light concentration for one day. The time is displayed on the first support throughout the day. the third, fourth, and second places. Columns represent system inputs (battery source, load demand, and light intensity),and the outputs are represented by the rows. The analytical power supported by the EMS and the permitted power supply are described in the two columns that follow. the initial window of time, from dawn at 5 a.m. to first light at 6 a.m., when solar energy is enabled and all the stipulated load is completed by the photovoltaic unit and safe hydrogen inspired in the fuel cell and the battery.The energy source is created from the fuel cell and battery based on the demand load during the second phase, which runs from sunset to sunrise, when the light concentration is low. Low brightness concentration will cause the fuel cell to provide enough power to the load depending on the source, increasing system consistency.

Table.1 Proposed Simulation result from EMS based ANN model



Fig.3 PI, energy management system, results at high and normal SoC mode.



Fig.4 PI, energy management system, results at low SoC mode.



Fig.5 Fuel cell control obtained from ANFIS EMS at peak SoC mode.



Fig.6 Fuel cell control obtained from ANFIS EMS at medium SoC mode.

eISSN 1303-5150



Fig.7 Fuel cell control obtained from ANFIS EMS at lower SoC mode.

V. Conclusion

The smart energy management system for an all-electric ship influence system based on ANFIS is a controlling practise for the smart grid ship power system's potential, which is yet in its infancy.Additionally, it highlights the need for clean energy for naval ship applications and enables the power system management flexibility. It also allows for the regulation of generated energy. Artificial intelligence (AI) techniques improve the system's dependability and flexibility while adding more energy sources or downsizing the power system.The established PI have power over the system's resources, but the ANFIS is easier to operate than changing the hardware. This system will function better in the future if a PV array is added to reduce the cost of hydrogen. Before being installed aboard the ship, the system will additionally be tested on a tested ship power system.This work is a ring of the chain that develops a hybrid power system for the ship, enhances its routine by incorporating a renewable energy source, and rigs this real-time intelligent supervisory structure utilising an embedded raspberry Pi to lower structure expenses.

REFERENCES

[1] S. UNFCCC, "Report of the Conference of the Parties on its twenty-first session, held in Paris from 30 November to 13 December 2015. Addendum. Part two: Action taken by the Conference of the Parties at its twenty-first session.

[2]. J. Prousalidis, I. K. Hatzilau, P. Michalopoulos, I. Pavlou, and D. Muthumuni, "Studying ship electric energy systems with shaft generator." pp. 156-162. Doi:10.1109/ESTS.2005.1524669

[3]. D. Paul, "A History of Electric Ship Propulsion Systems [History]," IEEE Industry Applications Magazine, vol. 26, no. 6, pp. 9-19, 2020.Doi:10.1109/MIAS.2020.3014837

[4]. M. Gaber, S. H. El-banna, M. Eldabah and M. S. Hamad, "Model and Control of Naval Ship Power System by The Concept of All-Electric Ships Based on Renewable Energy," 2019 21st International Middle East Power Systems Conference (MEPCON), Cairo, Egypt, 2019, pp. 1235-1240, doi: 10.1109/MEPCON47431.2019.9007914.

[5]. G. Sulligoi, A. Vicenzutti, and R. Menis, "All-Electric Ship Design: From Electrical Propulsion to Integrated Electrical and Electronic Power Systems," IEEE Transactions on Transportation Electrification, vol. 2, no. 4, pp. 507-521, 2016. Doi: 10.1109/TTE.2016.2598078

[6]. A. Vicenzutti, G. Trincas, V. Bucci, G. Sulligoi, and G. Lipardi, "Early-Stage design methodology for a multirole electric propelled surface combatant ship." pp. 97-105. Doi: 10.1109/ESTS.2019.8847793

[7]. S. Rahman, "Artificial intelligence in electric power systems: a survey of the Japanese industry," IEEE Transactions on Power Systems, vol. 8, no. 3, pp. 1211-1218, 1993. DOI:10.1109/59.260875

[8]. M. K. Dayeni, and M. Soleymani, "Intelligent energy management of a fuel cell vehicle based on traffic condition recognition," Clean Technologies and Environmental Policy, vol. 18, no. 6, pp. 1945-1960, 2016.Doi: 10.1007/s10098-016-1122-2

[9]. A. Wangsupphaphol, N. Idris, A. Jusoh, N. Muhamad, and L. W. Yao, "The energy management control strategy for electric vehicle with Supercapacitors." pp. 1-5. DOI:10.1109/cencon.2014.6967469

[10]. H. Ji, O. Alfarraj, and A. Tolba, "Artificial Intelligence-Empowered Edge of Vehicles: Architecture, Enabling Technologies, and Applications," IEEE Access, vol. 8, pp. 61020-61034, 2020. DOI:10.1109/ACCESS.2020.2983609

[11]. D. Phan, A. Bab-Hadiashar, C. Y. Lai, B. Crawford, R. Hoseinnezhad, R. N. Jazar, and H. Khayyam, "Intelligent energy management system for conventional autonomous vehicles," Energy, vol. 191, pp. 116476, 2020. DOI:10.3390/su14159378

[12]. H. Hemi, J. Ghouili, and A. Cheriti, "A real time fuzzy logic power management strategy for a fuel cell vehicle," Energy Conversion and Management, vol. 80, pp. 63- 70, 2014/04/01/, 2014. Doi: 10.1016/j.enconman.2013.12.040

[13]. E. William, M. Manic, and B. Johnson, "Ann relays used to determine fault locations on shipboard electrical distribution systems." pp. 143-147. **DOI:** 10.1109/NAPS.2007.4402301

[14]. S. Liu, Y. Sun, L. Zhang, and P. Su, "Fault diagnosis of shipboard medium-voltage DC power system based on machine learning," International Journal of Electrical Power & Energy Systems, vol. 124, pp. 106399, 2021/01/01/, 2021. Doi: 10.1016/j.ijepes.2020.106399

[15]. A. Mahesh, and K. S. Sandhu, "ANFIS based energy management strategy for PV/Wind/Battery hybrid energy system." pp. 1-5. Doi:10.11097POWERI.2016.8077221.

[16]. Sujil, A., Kumar, R., Bansal, R.C., 2019. FCM clustering-ANFIS-based PV and wind generation forecasting agent for energy management in a smart microgrid. J. Eng. 2019, 4852–4857. DOI:10.1049/joe.2018.9323

[17]. Topan, P.A., Ramadan, M.N., Fathoni, G., Cahyadi, A.I., Wahyunggoro, O., 2016. State of Charge (SOC) and State of Health (SOH) estimation on lithium polymer battery via Kalman filter. In: 2016 2nd International Conference on Science and Technology-Computer (ICST). pp. 93–96. **DOI:** 10.1109/ICSTC.2016.7877354

[18]. Torreglosa, J.P., Jurado, F., García, P., Fernández, L.M., 2011. Hybrid fuel cell and battery tramway control based on an equivalent consumption minimization strategy. Control Eng. Pract. 19, 1182–1194, 2011/10/01/. DOI:10.1016/j.conengprac.2011.06.008

[19]. Wangsupphaphol, A., Idris, N., Jusoh, A., Muhamad, N., Yao, L.W., 2014. The energy management control strategy for electric vehicle applications. In: 2014 International Conference and Utility Exhibition on Green Energy for Sustainable Development (ICUE). pp. 1–5.

[20]. William, E., Manic, M., Johnson, B., 2007. Ann relays used to determine fault locations on shipboard electrical distribution systems. In: 2007 39th North American Power Symposium. pp. 143–147. **DOI:** 10.1109/NAPS.2007.4402301

[21]. Yoon, G., Cho, K., Park, L.W., Lee, S.H., Chang, H., 2020. Artificial intelligence-base d energy data monitoring and management system in smart energy city. In: 2020 IEEE International Conference on Consumer Electronics (ICCE). pp. 1–2. **DOI:** 10.1109/ICCE46568.2020.9043110

[22]. Zhao, X., Zhang, X., 2016. Artificial intelligence applications in power system. In: 2016 2nd International Conference on Artificial Intelligence and Industrial Engineering (AIIE 2016). DOI:10.2991/aiie-16.2016.36.

Acknowledgement-

Mr.C.John De Britto M.E.,(Ph.D)., Working as Assistant Professor at Saveetha Engineering College from Jan 2022 to Till Date. I haveexperienced as a Chief Examcell Coordinator from Jeppiaar Engineering College during 2017 to 2020. As a Rotaract club Coordinator I have received more than 10 awards for the support and contribution towards Rotaract Club of Chennai along with Jeppiaar Engineering College. And from Academics I have recived more than 22 Excellence Awards. And I have Membership from IEI,IFERP, IEEE Sensor Council, CWSIR, IAENG, AICTSD, IAEEEE,Internet Society.



Mr. V.Loganathan, M.E.,(Ph.D), is working as an Assistant Professor in EEE department having teaching experience of more than a decade in various engineering colleges. At present he is carrying out his research in Anna University under the faculty of Electrical Engineering. His major research area is renewable energy, particularly in Wave Energy Conversion Systems and Solar PV Systems. He published a paper in a Scopus indexed journal and in a national conference. He also extended his contribution in authoring a book in the field of renewable energy. Also

eISSN 1303-5150

he is a professional member of IEEE and life member of ISTE.

Dr.ST. Subha received her B.E degree in Electrical & Electronics from S.R.M Engineering College, Madras University, India in 1996, M. E degree in Power Electronics & Drives from Sathyabama University, Chennai in 2004, and Ph.D degree in the field of wireless communications from SRM University, Chennai in 2012. She is currently working as a Professor in the Department of Electrical and Electronics at Veltech Multitech, Avadi, Chennai, India. Her research interests include wireless power transfer, wireless communications, diversity combining and MIMO. She has published 7 International Journal papers, presented 7 International Conference papers on the above topics.

Mr. Elakkiyavendan RPursued B.E.(EEE) in sri venkateswara college of engineering on April 2010. Pursued M.E.(EEE)-Electrical drives and embedded control in Anna University Regional campus Coimbatore on July 2012. Worked as Teaching fellow(EEE) in Anna University Regional campus Coimbatoreon November 2012 to July 2016. As research attachment in lee kong chian school of medicine,NTU, singapore.Currently pursuing Ph.D.(EEE) in Anna University Regional campus Coimbatore. Research areas: Renewable energy sources, Soft computing, Biomedical imaging from July 2017 to Present.

eISSN 1303-5150