COVID-19 X-RAY SCAN IMAGES CLASSIFICATION AND DETECTION BY RESIDUAL BASED DEEP LEARNING

Sakshi Sharma[1], Avni Sharma [2]

Computer Science and Engineering[1,2]

Himachal pradesh technical university , Hamirpur[1,2]

ABSTRACT

Infectious disease Covid-19 is a fast-spreading virus that infects both human beings and animals. As a result of this condition, animals may get infected with the virus. This fatal viral illness has an impact on not only the day-to-day lives of people but also their health and the economy of the nation in which they live. There is currently no vaccination available for COVID-19, regardless of the fact it is a global epidemic that is growing rapidly across the globe. Since then, the virus has swiftly spread over the globe, turning into a pandemic (WHO, 2020) , with the number of reported cases and fatalities connected with them continuing to rise on a daily basis . At the moment, more research on an efficient screening technique is necessary in order to diagnose instances of the virus and separate those who have been infected from the rest of the population. To limit the spread of the fatal virus and defend themselves from it, medical practitioners and specialists in many nations across the world are introducing multifunction testingto improve their treatment regimen and testing capacity. This is currently being done to enhance their capacity to detect the infection. When COVID-19-infected patients were studied in a clinical area, it was observed that they were often infected with respiratory illnesses. This conclusion was reached as a result of the findings of the study. Imaging techniques such as chest x-rays (also known as radiography) and chest CT scans are more accurate than other methods when it comes to detecting issues that are connected to the lungs. A thorough chest x-ray is less expensive than a chest CT, albeit . The most successful method of machine learning uses deep learning technologies . This is a great tool for analysing a large number of chest x-ray images, which could significantly affect the Covid-19 screening process.

DOI Number: 10.14704/nq.2022.20.9.NQ44202 **Neuro Quantology 2022; 20(9):1751-1763**

Research Background

The illness known as COVID-19 is brought on by the recently identified SARS-CoV-2 coronavirus, had the whole globe on edge for the first few months of the year 2020. As a result, the borders of several nations had to be shut down, and millions of people were forced to remain inside their houses because of contaminated neighbors. As of right now, there have been 868,000 verified instances of the disease around the globe (April 2020). During the month of December 2019, this virus first appeared in China. From March 2020 forward, Europe served as the primary epicenter of the virus's spread, ultimately resulting in more than 445,000 infections. After the outbreak of the crisis in December 2019, China was able to control the virus with a total of 3,312 fatalities and more than 81,000 affected persons. This accomplishment came over three months after the crisis began. According to a study that was released in April 2020, Italy has become the most impacted nation, surpassing the Asian countries in terms of the death toll to become the most afflicted country overall. Following Italy in terms of the number of slain is Spain, which has more than 10,000 dead. This figure was steadily increasing over time. There were a variety of studies that attempted to forecast the development of infection curves by using a variety of characteristics, such as the number of humans that were exposed, infected, or recovered from infection. This research made it possible to form an educated guess about the transmission dynamics that may take place in each nation [16,26].

Nobody knows where the infection first started spreading. December 2019 saw the discovery of the first instances of the disease. respiratory symptoms, cough, fever, dyspnea, and viral pneumonia are some of the clinical features that are connected with COVID-19 [28]. The most significant issue with these symptoms is the presence of asymptomatic people who are infected with the virus. Collecting samples from the respiratory tract is the foundation of the diagnostic procedure used to identify COVID-19. The case study is typically performed at home by a health care professional if the patient is asymptomatic or has minor symptoms. A severe illness necessitates that it be done at the health facility or hospital where they were admitted. More testing has been found to be the best way to tackle the virus in countries like South Korea and Germany. There must be new methods for doing these tests that are both quick and efficient in light of the fact that Spain would be unable to conduct out too many tests as they would have intended. AI and radiomics, which are applied to computed tomography (CT) and X-rays, are beneficial technologies that could be used to diagnose and track the sickness [20]. AI algorithms and radiomics elements generated from chest X-rays should be of great use in the establishment of widespread screening programs that could be implemented in any nation with access to X-ray technology and aid in the diagnosis of COVID-19 [34,35]. This would be of great benefit. Automated detection systems must be put in place as a means of preventing the spreading of COVID-19 among persons given current circumstances. In the process of diagnosing pneumonia, chest radiography, sometimes acknowledged as an X-ray, is widely regarded as one of the most significant diagnostic tools. A chest X-ray is a common medical test that doesn't take long and doesn't cost much [50]. When compared to MRI and CT, the amount of radiation a patient gets from a chest X-ray seems to be much lower [31]. Nevertheless, in order to arrive at the accurate diagnosis based on an X-ray picture, one needs much training and experience [32]. Using a chest X-ray to diagnose the illness is far more difficult when contrasted to other imaging techniques, including CT or MRI [43]. Computer-aided diagnosis (CAD) allows medical professionals to arrive at a diagnosis of pneumonia from a chest X-ray in a more timely and precise manner [43]. In the sphere of medical services, the use of approaches that make use of AI is rising as a result of its capacity to deal with massive datasets that are beyond the capabilities of humans [29]. When integrated into diagnostic systems used by radiologists, CAD techniques significantly cut down on the amount of labor that has to be done by physicians, while also improving both reliability and quantitative analysis [26]. Systems for computer-aided design (CAD) that are based on medical imaging and deep learning are becoming more popular as research topics [29,43]. Deep learning strategies [6,9] [11-18] are also used in order to get superior outcomes to those that would be accomplished via the application of more conventional machine learning methods. The use of CNNs is now one of the most common methods utilized in the image categorization process. In the study proposed by Wang et al. [3], A CNN model was developed using a random selection of image interest regions and it achieved an accuracy of 85.2 percent, 0.83 of specificity, and 0.67 of sensitivity. For the identification of COVID-19 in clinical images, a CNN trained model with a randomly chosen series of images has been utilized in numerous investigations, such as those in [3]. Another illustration of the kinds of outcomes that may be accomplished using CNNs is shown in the work that was done by Linda Wang et al. [24]. Researchers indicate that the COVID-Net CNN network is capable of achieving an 92.4% accuracy, 80% sensitivity, and a 88.9% specificity.

Rachna Jain, et.al [1]. People who had been injured by covid-19, as well as those who had not, had their chest x-rays evaluated utilizing the PA view by the researchers as part of this study. The researchers used DL-based CNN models and linked their distinct degrees of performance after cleaning up the photographs and applying data augmentation. Testing the models' accuracy has been done by comparing them side-by-side with each other. 6432 chest x-ray pictures from the Kaggle library were analyzed to see how well the model performed. Of these, 5467 were used in the training process, while 965 were used in the testing phase. Other models can only come close (i.e., 97.97 percent) to the Xception model's accuracy when it comes to correctly recognizing chest X-rays in results analysis. There are no medical claims made in this research, but rather prospective categorization

methods for those who have been infected with covid-19.

- **Objectives:** The concept of DL to find COVID-19 X-rays and analyze it.
- **Work plan:** "This paper plan, is further categorized in the various parts such as section 2, explored various scholars' viewpoints in analysing the influence of the covid-19 illness on nations and persons." "This paper plan, is further classified in the various sections such as section 2." The data collection that was utilized and the formulation of the model are covered in section 3. In part 3, we also talk about the various matrices and techniques that were employed. In addition, the discussion of the assessment of outcomes in terms of testing and training using confusion matrices for the models that were utilized can be found in section 4. The last part of this work, section 5, discusses the study's implications for the future.
- **Methodology:** In this task, the researchers have been trying to classify the Covid-19 patients based on their chest X-ray scans by using several CNN models.

Nur-A-Alam, et.al [2]. Machine vision might be used to identify COVID-19 in chest X-ray images, according to the authors of this study. The properties of X-ray images that were retrieved using the HOG and the CNN were merged into one. In order to build a classifier using CNN training, this has to be done (VGGNet). Edge preservation and noise reduction were achieved using a technique known as modified anisotropic diffusion filtering (MADF). A watershed segmentation method was utilized to identify the region of the raw X-ray images that included a significant fracture. The model's performance was evaluated using generalized data throughout the testing phase. By analyzing cross-validation results, the researchers found that a 5-fold approach may successfully reduce overfitting. There is a 99.49% accuracy rate for our suggested feature-fusion DL technique in the identification of COVID-19 in comparison to prior, relevant research that used the same method. The specificity is 95.77% and sensitivity 93.56%. When compared against other classification methods, including ANN, KNN, and SVM, the CNN technique was shown to be the most effective in this study. For example, a k-fold cross-validation study found that the proposed method for fusing features had a larger accuracy (98.36 percent) than different feature extraction techniques like the HOG (87.34 percent) or CNN (87.34 percent) (93.64 percent)

- **Objectives:** COVID Detection from Chest X-Ray Images Utilizing DL and Feature Fusion.
- **Work plan:** It is my pleasure to provide in Section 2 the results of an exhaustive research on the categorization of chest X-ray pictures. The system architecture utilised in Section 3 to classify X-ray image datasets into COVID as well as other classes and identify COVID-19 from them is described. In Section 4, the findings and conclusions reached as a consequence of this effort are presented. In Section 5, we will talk about the validation of the suggested system, as well as its comparative performances and limits when it comes to identifying COVID-19. In the last step, the conclusions that may be taken from this study are discussed in Section 6.
- **Methodology:** HOG and CNN are two feature extractors. Firstly, a feature-based vector was extracted from the COVID-19 X-ray database using the HOG approach. Another feature vector was then extracted from the same images using the CNN approach.

Shuai Wang, et.al [3]. Artificial Intelligence (AI) may be utilized to extract specific graphical characteristics of COVID and provide a clinical diagnosis prior to the pathogenic test, saving significant time that may be better spent on illness treatment. The internal validation indicated an accuracy rate of 89.5 percent overall, with a specificity rate of 0.88 and a sensitivity rate of 0.87. The dataset utilized for external testing has a total accuracy of 79.3 percent, a specificity of 0.83, and a sensitivity of 0.67. In contrast, the first two nucleic acid tests on 54 of the COVID-19 photographs came back negative, and the algorithm accurately predicted the existence of COVID-19 in 46 of the images, with an accuracy of 85.2%. Findings like these show that AI may be used to quickly and accurately diagnose COVID-19 by extracting radiological properties from its images.

- **Objectives:** An algorithm that uses CT scans and DL to screen for Corona virus illness.
- **Work plan:** In addition to the 1,065 CT images of patients with previously identified normal viral pneumonia, the investigators also collected pathogen-confirmed instances of COVID. To establish the method, we changed the inception transfer-learning model, accompanied by external and internal validation.
- **Methodology:** Retrospective**,** diagnostic or prognostic study, and multicentre study.

M. D. Kamrul Hasan, et.al [4]. There are ML approaches such as Label Binarizer employed in this study to do one-hot encoding on the labeled CT scans. Categorization tools are then used to transform the information into a form that can be categorised. After that, a detection model is built using a number of deep learning characteristics. CNN, VGG16, dropout, AveragePooling2D, dense, flatten, and input are some instances of these characteristics. Adam, an optimizer for COVID-19 patients, is utilized to increase the accuracy of the pneumonia prediction. Pneumonia can be predicted 91.69% accurately, with a 95% specificity and 96% sensitivity using the model, which has an average accuracy of 91.69%. It is also possible to cut training time while increasing accuracy using the &e model.

- **Objectives:** DL Methods for Finding Pneumonia in COVID-19 Patients by Examining Chest X-Ray Images.
- **Work plan:** COVID-19-induced pneumonia can be found via lung X-ray images and a two-step deep residual learning method.
- **Methodology:** A DL algorithm is employed to learn more accurate features from X-rays of patients in order for the model can better spot pneumonia. Domain adaptation is yet another way that chest X-ray images have been employed to find COVID-19 patients.

Turkoglu [5]. Currently, a model for diagnosing COVID-19 known as COVIDetectioNet is suggested in the present study. An expertly built system, COVIDetectioNet makes use of a variety of specific qualities. Pretrained using transfer learning, a CNN-based AlexNet framework was created to accomplish this aim. The Relief feature selection procedure employed the SVM approach to classify the beneficial features that were picked from each level of architecture. A total of 6092 X-ray pictures from several publically accessible datasets were used to test the proposed model's accuracy. Classification of the images was done using the terms "Normal" (healthy), "COVID-19," and "Pneumonia." When compared to the test data, the recommended model was found to be 99.18% correct. The COVIDetectioNet model was shown to be more successful than the previous research. This becomes apparent when the results are compared to the results.

- **Objectives:** COVID-19 is a diagnostic system based on X-rays with features selected from a group of deep characteristics that have already been learned.
- **Work plan:** In this investigation, the feature extraction model was a CNN-based AlexNet framework that had been pretrained.
- **Methodology:** AlexNet architecture, Relief feature selection algorithm.

Mustafa Ghaderzadeh and Farkhondeh Asadi [6]. Using a radiological modality and deep learning, this study examines the current status of all models for diagnosing and detecting COVID-19. The University of Michigan was in charge of conducting the study. Research has shown model-based on deep learning (DL) to be exceptionally capable of producing a precise and effective way to identify and diagnose the COVID-19 virus. If these models were used in the processing of modalities, the sensitivity and specificity values would rise dramatically. Deep learning (DL) has improved the processing of Covid-19 radiologic images in order to reduce false-negative or false-positive errors in disease detection and diagnosis, as well to provide patients with diagnostic procedures that are both cost-effective as well as rapid and risk-free for the patient.

- **Objectives:** DL in the Diagnosis and Detection of COVID-19 Using Radiology Modalities
- **Work plan:** The current systematic review was carried out by doing a search based on a searching strategy between the dates of

November 1, 2019, and July 20, 2020, across the three databases of Scopus, Web of Science, and PubMed. Following the application of the exclusion and inclusion criteria, a total of 168 articles were retrieved, and from those 168 articles, 37 were chosen to constitute the research population.

- **Methodology:** The results of this study support the idea that DL approaches can be used to improve healthcare and increasing diagnostic and therapeutic outcomes.

Khasawneh, et.al [7]. COVID-19 respiratory illnesses were the primary cause of pneumonia in this study, hence DL models based on CNNs were utilized to detect cases. The models had already undergone training and cosmetic enhancements. In 368 COVID-19 patients, chest X-rays were taken and showed the virus. Data was also retrieved and used from three more publicly available datasets. The performance might be evaluated using four distinct criteria. A publicly accessible dataset was used for training and testing at initially. To train and validate the models, data from both public and private sources was pooled together, and this data was also utilised. The model was also evaluated on a dataset that was made accessible to the public. The detection models are bolstered by this technique, which also tests how well they can generalize to new information without getting overfit to certain sample sets. For the fourth time, while the pooled data were used for training, the locally collected data were used for evaluation.. Accuracy was found to be 98.7%, and the majority of designs were able to adapt to new data with just a little loss.

- **Objectives:** Deep CNNs are utilized to find COVID-19 in X-ray pictures of the chest.
- **Work plan:** (a) training and testing, (b) train and validate the models, (c) public dataset has been used to train the model, and (d) merged data utilized for training, and the local data have been used for testing.
- **Methodology:** CNNs

1.5 Ensemble Learning

In comparison to a single model, ensemble approaches produced better performances. It can enhance performance of the classifier while lowering the chance of overfitting. Depending on the estimates provided by other classifiers or models, ensemble learning develops predictions. Since it is an easy technique to reach conclusions from various predictions given by distinct single models, majority voting-based ensemble learning [67] can be used. Hard voting and soft voting are the two different sorts of majority voting procedures. Ensemble learning utilising both soft and hard majority voting approaches is shown in [68]. The final forecast with the highest number of votes from the models is determined by hard voting. One may choose to provide the final label to the class with the smallest index when two classes are tied for the most votes. The final class label for the class with the shortest index is the one that has the highest probability. Soft voting involves the addition of the projected probability of models for each class. In soft voting, which totals the projected probabilities of models for every class, here the class-based label with highest probability is considered the last class label. [66].

1.7 Performance metrics

Accuracy, specificity, sensitivity, F1 score, and precision were utilised to evaluate the performance of the proposed classification model [30]. The parameters are theoretically defined as following given the quantity of true positives (TP), true negatives (TN), false positives (FP), false negatives (FN).

$$\text{Accuracy} = \frac{TP+TN}{TN+TP+FP+FN} \; ; \; \text{Specificity} = \frac{TN}{TN+FP};$$

$$\text{Sensitivity} = \frac{TP}{TP+FN}; \; \text{Precision} = \frac{TP}{TP+FP}$$

$$\text{F1} = 2 \times \frac{Recall \times Precision}{Recall \times Precision}$$

The current study further justifies the application of confusion matrix analysis in validation [52] given that it is robust to any type of connection and data-based distribution, rigorously assesses validity, and offers additional details on the types and origins of mistakes. Let's first examine the structure of each model's confusion matrix and specify all the variables and parameters that can be retrieved [35] before we begin to analyse each model's confusion matrix (Table 1.1).

Table 1.1 Confusion matrix structure

		Predicted		
		Bacteria		Normal
		Coronavirus		
Actual	Bacteria	P_{bb}	P_{nb}	P_{cb}
	Normal	P_{bn}	P_{nn}	P_{cn}
	Coronavirus	P_{bc}	P_{nc}	P_{cc}

where:

P_{cb}: Bacteria class were inaccurately identified as Coronavirus.

P_{bb}: Bacteria class were accurately identified as Bacteria

P_{bc} : Coronavirus class were inaccurately identified as Bacteria.

P_{nb}: Bacteria class inaccurately identified as Normal

P_{nc}: Coronavirus class inaccurately identified classified as Normal.

P_{cc}: Coronavirus class were accurately identified as Coronavirus

P_{cn}: Normal class were inaccurately identified as Coronavirus.

P_{bn}: Normal class were inaccurately identified as Bacteria.

P_{nn}: Normal class were accurately identified as Normal.

To use these parameters, more variables can be defined [35]:

True Positives TP: True Negatives TN:

TP(Bacteria)	P_{bb}	TN(Bacteria)	$P_{cc} + P_{nc} + P_{cn} + P_{nn}$
TP(Normal)	P_{nn}	TN(Normal)	$P_{bb} + P_{cb} + P_{bc} + P_{cc}$
TP(Coronavirus)	P_{cc}	TN(Coronavirus)	$P_{bb} + P_{nb} + P_{bn} + P_{nn}$

False Positives FP: False Negatives FN:

FP(Bacteria)	$P_{bc} + P_{bn}$	FN(Bacteria)	$P_{cc} + P_{nc}$
FP(Normal)	$P_{nb} + P_{nc}$	FN(Normal)	$P_{bn} + P_{cn}$
FP(Coronavirus)	$P_{cb} + P_{cn}$	FN(Coronavirus)	$P_{bc} + P_{nc}$

Dataset

This work utilizes covid x-ray data. Data access is from https://www.kaggle.com/tawsifurrahman/covid19-radiography-database. Apply 5-fold cross-validation to this complete image of 12970 pixels [10] using 5-fold cross-validation.

Table 4.1: Experimental setup for proposed and existing approach [12]

Training Parameters	Resnet-transfer learning	Resnet- XG-boost
Learning Rate	0.001	0.001
Optimizer	Nadam	Nadam
Batch size	14	14
Loss function	Cross entropy	Cross entropy
Epochs	20	20
Horizontal/vertical flipping	yes	yes

Table 4.1 depicts the experimental methodology for the proposed Resnet with XG-boost classifier and feature engineering, while the experimental setting for the current classifier, which employs Resnet base transfer learning with the SoftMax classifier, is shown in Table 4.2. Table 4.1 demonstrates, with the exception of the technique being used, that all of the hyperparameters are the same; thus, it demonstrates the influence that the suggested strategy has on the outcomes. The performance of the suggested technique is not dependent in any way on hyperparameter setting. During the experiment, the apparatus displays horizontal as well as inverted pictures.

Coronavirus reigns as different freak variations creating pandemic circumstances throughout the globe. Such a situation places an accurate medical diagnosis beyond ambiguous. Developed various medical diagnostic techniques, Chest X-rays, and computed tomography image methods, augment the analytical techniques (for example, RT-PCR) to a specific limit. Therefore, in this framework, a demonstrated novel method for adopting distinct image segmentation methods takes advantage of the image dataset (9000 CXR films as well as 6000 Computed Tomographic images). The recommended technique is, perhaps, used to help diagnose COVID-19 contaminated humans by examining chest X-rays as well as CT scan pictures utilizing the Deep Covix-Net technique to recognize novel COVID-19 contaminated samples accurately. The classification performances of different mechanisms have been investigated for test data encompassing 1800 pictures for X-ray and 1200 images for CT scan. The sample of the precision rate is analyzed in the light of efficiency measures viz., veracity, ROC curve as well as a confusion matrix.

Within the medical domain, eminent image data of databases of retina imaging, Chest X-rays, as well as CT scan pictures give favorable outcomes, as evidenced by an improved relative accuracy delivered by methods of Deep Learning mechanism and Artificial Intelligence [54-56]. It is well known that X-rays, as well as CT scan devices, contain expensively as well as expedite results for diagnosing various human organs in the hospitals. Yet, the interpretation of several X-rays, as well as CT scan pictures employing visual inspections, is frequently performed by medical experts. If those pictures were applied to Machine Learning, Deep Learning, as well as Artificial Intelligence, that would help doctors in prognosis COVID-19 patients. The protocol would help establish areas where the X-ray, as well as CT scan amenities, are available, yet the doctors' evaluations are non-existent.

Further aimed to develop a machine learning technique. This Deep Covix-Net technique can examine the CXR as well as Computed Tomography pictures of lungs and prognosis of the Coronavirus / Pneumonia contaminated patients. Among various ML mechanisms, RF performs a broad classification as well as medical picture diagnostics aspect. Machine learning techniques outcomes explain their ability to scale the picture database to become a precise as well as robust model. The lungs are decisive, as well as analyzing their deviations can afford an accurate result to the COVID-19 diagnosis.



(a)



(b)



(c)

Figure 4.1 Sample Chest X-ray images (a) Lungs are clear, no patchy consolidation. (b) Patchy Consolidations, ill-defined bilateral alveolar consolidations. (c) Infection that inflames air sacs in one or both lungs, which may fill with fluid.

Figure 4.1 gives the sample chest X-ray images of healthy, COVID-19, and pneumonia-infected individuals.

(a) **(b)**



Figure 4.2 Sample CT scan images (a) Lungs are clear, no patchy consolidation. (b) GGO was observed frequently, often bilateral and with consolidations and prominent peripherally subpleural distribution [23].

Figure 4.2 illustrates the sample CT scan images of healthy and COVID-19 infected individuals.

4.1 MATERIALS AND METHODS

4.2.1 Data Pre-Processing

The database utilized in this chore is openly available at Kaggle as well as GitHub archives [47], which directly resides of around 9000 chest X-ray pictures out of these 3000 for COVID-19 +ve samples, 3000 for healthy, and 3000 for pneumonia samples. The CT scan dataset resides of around 6000 samples (3000 for healthy as well as 3000 for COVID-19 +ve samples). The dataset archives are open for image segmentation techniques, and the entire dataset is confirmed and elucidated, containing the verdict of the CXR as well as Computed Tomographic films.

The films in the dataset are not unique; the CXR, as well as Computed Tomographic pictures, enunciate the distinctive range appropriately; the images were transformed to the same size of 512 x 512 pixels. Moreover, the RGB reverting has been imposed, as well as the consequent input to the suggested method is furnished as

512 * 512 * 3 picture.

4.2.2 Feature Extraction

Utilized advanced image segmentation methods, like GLCM, texture, GLDM, DWT, as well as FFT, to measure a combination of two hundred haralick features in both the spatial as well as frequency regions. The corresponding twelve haralick lineaments [126] are explained in Table 4.1. The features eradication around 200 features for every CXR as well as Computed Tomographic films (FFT: 12 features, Texture: 12 features, GLDM: 40 features, GLCM: 40 features, as well as DWT: 96 features).

During validating the model, the verification samples obtained nearly 0.32 loss rate as well as 96.8% veracity in CXR output. As for the output achieved from Computed Tomography, verification samples obtained about 0.3 error rate yielding 97%veracity. Further, it is understood that the error rate indicates the accurate match about validation as well as verification, affirming that the former model is not affected with overfitting or underfitting in neither CXR nor Computed Tomographic dataset. Then, a Receiver Operating Characteristics curve was attained to evaluate the system's efficiency, as shown in Figures 4.8a, b, and c. On examining the CXR pictures of coronavirus contracted individuals having Pneumonia symptoms compared with healthy samples described that the said technique yields the precision score of 98% while the recall score rendered up to 99% when analyzing the verification samples of 1800 CXR samples, as described in Table 4.2.



(a)



(b)



(c)

Figure 4.8 Chest X-ray Image dataset assessment-(a) Receiver Operating Characteristics graph provokes 1800 test samples, amid pneumonia is the target label. (b) Receiver Operating Characteristics graph extracted from 1800 test

samples, amid normal is the target label. (c) Receiver Operating Characteristics graph provokes from 1800 test samples, amid COVID-19 is the target label.

Table 4.2 Exhibits the results of Confusion Matrix taken on 1800 test samples predicting amongst COVID-19 infection, Healthy and Pneumonia samples

Label	Healthy	Pneumonia	COVID-19	Sample Size taken
Healthy	578	13	0	591
Pneumonia	30	562	10	602
COVID-19	0	4	603	607
Total Sample Size Used				1800



(a)



(b)

Figure 4.9 CT scan Image dataset assessment- (a) Receiver Operating Characteristics graph provokes 1800 test samples, amid COVID-19 is the target

label. (b) Receiver Operating Characteristics graph encourages from 1800 test samples, amid healthy is the target label.

The recommended technique has obtained 97% accuracy between Healthy as well as COVID-19 patients when the model is applied to CT scan images. Output Visualization of the CT scan picture dataset as exhibited in Figure 4.9.

Performance measures of the recommended technique concerning the CXR dataset as exhibited in Table 4.3. Similarly, Table 4.4 describes the Confusion matrix for the Computed Tomographic dataset as well.

Table 4.3 Attainment measures for recommended technique: Chest X-ray the database

Label	Precision	Recall	F-Measure	MCC
Healthy	0.95	0.97	0.96	0.94
COVID-19	0.98	0.99	0.98	0.98
Pneumonia	0.97	0.93	0.95	0.92

Table 4.4 Confusion Matrix for foreseeing 1200 verification samples amidst COVID-19 and Heathy

Label	Healthy	COVID-19	Sample Size taken
Healthy	556	13	569
COVID-19	609	22	631
Total Sample Size Used			1200

As shown in Table 4.5, a correlation has been obtained concerning the assessment in 5 various segmentation methods calculated for veracity as well as kappa metric of the lineaments. The obtained Deep Covix-Net technique yields superior performance concerning forecasting than distinct segmentation methods that are compared amidst COVID-19 and Healthy. The model illustrates the merits of accomplishing such a recurrence region, yet it derives the features suitable to recognizing COVID-19 infection in CXR pictures. The recommended technique enhances 8%, 6.3%, 1.5%, 2.5%, and 3.8% accuracy correlated amidst Texture, FFT, DWT, GLCM, as well as GLDM lineament eradication methods, respectively, in the CXR dataset. Similarly, when comes to the Computed Tomographic dataset, the recommended technique enhances the relative accuracy to low values of 0.6%, 1.2%, 0.5%, and 0.8%, with a 0.1% accuracy compared with high values of the mechanisms indicated above. The suggested technique gives the following metrics for the CT scan dataset:

- The recall score – 97.9%,
- The specificity score – 96.1%,
- The precision score – 96.5% and
- The F1 score – 97.1%.

CONCLUSION

The findings presented and described in the dissertation analyzed the radiology images to identify COVID-19 infected individuals. In the initial stage of the pandemic, simulation was performed for few samples that are present in the repository. Later, more images are archived in the repositories due to the increasing number of cases daily. Early diagnosis of COVID-19 with ultrasound images thus reduces the severity level and stops spread to other individuals.

The demonstrated methods achieved better performance accuracy with large and balanced image databases than other published research. While training and testing, the proposed models are not affected by overfitting or underfitting. These mechanisms could help Doctors and Radiologists deal with the COVID-19 infected patients after attaining this quick prognosis. The outcomes of the research work are summarized below.

1. Jain, R., Gupta, M., Taneja, S., & Hemanth, D. J. (2021). Deep learning-based detection and analysis of COVID-19 on chest X-ray images. *Applied Intelligence*, *51*(3), 1690-1700.
2. Ahsan, M., Based, M., Haider, J., & Kowalski, M. (2021). COVID-19 detection from chest X-ray images using feature fusion and deep learning. *Sensors*, *21*(4), 1480.
3. Wang, S., Kang, B., Ma, J., Zeng, X., Xiao, M., Guo, J., ... & Xu, B. (2021). A deep learning algorithm using CT images to screen for Corona Virus Disease (COVID-19). *European radiology*, 1-9.
4. Hasan, M. D., Ahmed, S., Abdullah, Z. M., Monirujjaman Khan, M., Anand, D., Singh, A., ... & Masud, M. (2021). Deep learning approaches for detecting pneumonia in COVID-19 patients by analyzing chest X-ray images. *Mathematical Problems in Engineering*, *2021*.
5. Turkoglu, M. (2021). COVIDetectioNet: COVID-19 diagnosis system based on X-ray images using features selected from pre-learned deep features ensemble. *Applied Intelligence*, *51*(3), 1213-1226.
6. Ghaderzadeh, M., & Asadi, F. (2021). Deep learning in the detection and diagnosis of COVID-19 using radiology modalities: a systematic review. *Journal of Healthcare Engineering*, *2021*.
7. Khasawneh, N., Fraiwan, M., Fraiwan, L., Khassawneh, B., & Ibnian, A. (2021). Detection of covid-19 from chest x-ray images using deep convolutional neural networks. *Sensors*, *21*(17), 5940.
8. Karakanis, S., & Leontidis, G. (2021). Lightweight deep learning models for detecting COVID-19 from chest X-ray images. *Computers in biology and medicine*, *130*, 104181.
9. Ghosh, S., & Bandyopadhyay, M. (2021). Detection of Coronavirus (COVID-19) Using Deep Convolutional Neural Networks with Transfer Learning Using Chest X-Ray Images. In *Machine Learning Approaches for Urban Computing* (pp. 63-77). Springer, Singapore.
10. Narin, A., Kaya, C., & Pamuk, Z. (2021). Automatic detection of coronavirus disease (covid-19) using x-ray images and deep convolutional neural networks. *Pattern Analysis and Applications*, 1-14.
11. Ibrahim, A. U., Ozsoz, M., Serte, S., Al-Turjman, F., & Yakoi, P. S. (2021). Pneumonia classification using deep learning from chest X-ray images during COVID-19. *Cognitive Computation*, 1-13.
12. Keidar, D., Yaron, D., Goldstein, E., Shachar, Y., Blass, A., Charbinsky, L., ... & Eldar, Y. C. (2021). COVID-19 classification of X-ray images using deep neural networks. *European radiology*, *31*(12), 9654-9663.
13. Ismael, A. M., & Şengür, A. (2021). Deep learning approaches for COVID-19 detection based on chest X-ray images. *Expert Systems with Applications*, *164*, 114054.
14. Hussain, E., Hasan, M., Rahman, M. A., Lee, I., Tamanna, T., & Parvez, M. Z. (2021). CoroDet: A deep learning based classification for COVID-19 detection using chest X-ray images. *Chaos, Solitons & Fractals*, *142*, 110495.
15. Kc, K., Yin, Z., Wu, M., & Wu, Z. (2021). Evaluation of deep learning-based approaches for COVID-19 classification based on chest X-ray images. *Signal, image and video processing*, *15*(5), 959-966.
16. Dur-e-Ahmad, M., & Imran, M. (2020). Transmission Dynamics Model of Coronavirus COVID-19 for the Outbreak in Most Affected Countries of the World. *International Journal of Interactive Multimedia & Artificial Intelligence*, *6*(2).
17. Ozturk, T., Talo, M., Yildirim, E. A., Baloglu, U. B., Yildirim, O., & Acharya, U. R. (2020). Automated detection of COVID-19 cases using deep neural networks with X-ray images. *Computers in biology and medicine*, *121*, 103792.
18. Al-Bawi, A., Al-Kaabi, K., Jeryo, M., & Al-Fatlawi, A. (2020). CCBlock: an effective use of deep learning for automatic diagnosis of COVID-19 using X-ray images. *Research on Biomedical Engineering*, 1-10.
19. Cohen, J. P., Morrison, P., Dao, L., Roth, K., Duong, T. Q., & Ghassemi, M. (2020). Covid-19 image data collection: Prospective predictions are the future. *arXiv preprint arXiv:2006.11988*.
20. Duran-Lopez, L., Dominguez-Morales, J. P., Corral-Jaime, J., Vicente-Diaz, S., & Linares-Barranco, A. (2020). COVID-XNet: A custom

deep learning system to diagnose and locate COVID-19 in chest X-ray images. *Applied Sciences*, *10*(16), 5683.

21. Zhang, J., Xie, Y., Li, Y., Shen, C., & Xia, Y. (2020). Covid-19 screening on chest x-ray images using deep learning-based anomaly detection. *arXiv preprint arXiv:2003.12338*, *27*.