GREEN NETWORKING WITH PACKET PROCESSING ENGINES: MODELING AND OPTIMIZATION

Amit Kumar Mishra
Asst. Professor, Department of Comp. Sc. & Info. Tech., Graphic Era Hill University, Dehradun, Uttarakhand India 248002

Abstract

The process of choosing energy-efficient networking tools and devices while limiting resource use is known as green networking. Which pipeline best captures the performance and behaviour of an energy-aware network gadget with Ability to use LPI plus AR? The major objective is to manage both pipeline power setup and optimal method of traffic flow distribution. Modern packet processing engines, which frequently consist of a variety of concurrent pipelines to "divide and conquer" the amount of incoming traffic, were the subject of this work. This work focuses on energy-aware gadgets that can lower their energy needs by adjusting their performance. In order to do so properly depict the effects of technologies for green networks (such reduced power idle as well as adaptive capacity) on network- and energy-aware performance measures, it suggests an analytical model. The model has been tested by applying real-world traffic traces and energy-conscious software routers, with positive results. In order to dynamically modify the design of energy-aware devices to reduce energy consumption while managing incoming traffic volumes along with achieving network performance requirements, an optimization process predicated upon the framework has been presented also then put to the test in experiments..

DOI Number: 10.48047/nq.2021.19.5.NQ21077 **NeuroQuantology 2021; 19(5): 308-313**

1. INTRODUCTION

Earlier this decade, the research of energy-saving network devices has been predicated on the potential to match the energy needs of the network to the real traffic load. In fact, it is common knowledge that network connections as well as devices are frequently configured to handle heavy or rush-hour loads that usually surpasses their regular use by a significant margin. Nevertheless though it's rare to reach this margin, network gadgets are built using it as a foundation, so even in the midst of variable traffic load, their power consumption is roughly constant. So, dynamically adjusting the network's resources is the key to any sophisticated power-saving requirement, connection, according to the weights and needs, or equipment level of the present flow of traffic. In this regard, existing methods to green networking have been built around a variety of energy-related standards, which should be applied specifically to network hardware and component interfaces.

Nonetheless, power management is a crucial feature of today's CPUs across all market sectors, as well as it is fast growing in other hardware technologies. The bulk of currently in use networking hardware is incapable of power scaling. The latter compels networks or processing engines to rapidly transition to a high power state while delivering or processing one or more packets, while maintaining low power states elsewhere. In order to understand the trade-off amongst network as well as energy awareness performance measures when AR and/or LPI techniques are used in a network device, our major goal is to construct a unique analytical model based on basic queuing theory notions. The system ran multiple tests using actual traffic traces to confirm the suggested model, and it then compared the projected performance indices to experimental measurements made using Component Off-The-Shelf software routers. Consequently, the system takes into account a straightforward energy-conscious optimization method according to the analytical approach we suggest. This process tries to change the device's energy-aware configuration on a regular basis to be able to reduce power consumption while still

ensuring that network Quality of Service (QoS) requirements are met also incoming traffic levels are met.

This scenario raises the prospect of adjusting the energy needs of the network to the real traffic profiles. So, the secret to every sophisticated power-saving standard calls for dynamic resource adaptation. offered at the network, link, or equipment levels to the loads and traffic conditions at the moment. Current energy-conscious networking strategies include the deployment of energy-aware hardware as well as network interfaces, as well as unique traffic engineering and routing criteria. The analysis and assessment of the effects of power scaling GNT upon next-generation network devices is the main topic of this article. This is accomplished by using two basic strategies: Adjustable Rate along with Low Power Idle. The former enables dynamically adjusting a link's or a processing engine's capacity to accommodate traffic loads and service demands.

Based on these findings, we made the decision to concentrate on packet processing engines, which are often the most demanding parts of high-end routers as well as other network devices. These engines are implemented using a variety of heterogeneous hardware methods, ranging from traditional application-specific integrated circuit or field programmable gate array chips to those depending upon graphics processing units (GPUs) [10, 11]. To "divide and conquer" the traffic load coming from a variety of high-speed ports, and frequently feature highly parallel designs.

2. LITERATURE SURVEY

Systems that evenly distribute traffic across several pathways are necessary for dynamic load balancing. The required load share is swiftly assigned to each link via packet-based splitting, but TCP misinterprets this reordering as congestion. Flow-based splitting prevents packet reordering and pegs each segment to a particular path. With the help of a specialised team, we can provide you with the best possible service. FLARE calculates the maximum delay difference on these routes and sets the owlet timeout to that value. The research comes to a number of intriguing results, including the fact that extremely accurate traffic splitting can be accomplished with little to no effect on TCP packet reordering and with very little state overhead. A new generation of real-time adaptive traffic engineering can be made possible by owlets, which can also improve the responsiveness of load balancing. Last but not least, the presence and use of owlets demonstrate that TCP burstiness is not always a bad thing and may be utilised profitably [1].

This article covers the analysis of actual traffic traces and the implementation of power management strategies to a platform for new-generation SW routers. It is predicated upon the integration, use, and administration of power management features (such as rate adaptation and sleeping) inside network equipment designs and parts. While no activities are being carried out, these technologies enable decreasing power consumption, and Whenever the hardware is in use also carrying out operations, they enable adjusting the trade-off between performance and energy. You must be very knowledgeable about how to use the instruments at your disposal if you want to get the greatest outcomes. These SW governors' main goal is to configure network devices as efficiently as possible in relation to their predicted performance. Adjusting each component of the device's power use to the anticipated network performance. An effective way to dynamically optimise a modular network device's power use in relation to its anticipated forwarding performance. Yet, because they are easily modifiable and feature power management capabilities, it has an impact on optimization [2].

The fundamental causes and benefits of green networking from the research along with industry communities are thoroughly surveyed in this study. It offers a study of the most representative projects and standardisation initiatives and focuses on the innovations, protocols, including standards for networks that are energy-efficient that have been developing over the past several years. The survey only looks at fixed network infrastructure; it makes no mention of energy-efficient methods and tools used in domains connected to networks, such green data centres. It examines the most recent data and perspective studies on the energy use of next-generation networks and outlines the primary interventional lines that can be inferred from the available research. Emerging are three fundamental ideas: re-engineering networking equipment's architectural components, dynamic network connection and resource adaptation to traffic load, and utilisation of sleeping/standby states. Adapt to high volume traffic flows while reducing power usage. These adaptive network devices may scale their traffic processing capacity using AR and LPI techniques, which allows them to conserve energy. Yet, devices enter low-power resting states less frequently the possibility of burst inter-arrival time, and for shorter amounts of time before awakening once again is greater than the drop rate [3].

The Advanced Configuration and Power Interface standard offers power management methods to decrease power usage while no work is being done and to change the balance amongst efficiency and functionality whenever the hardware is working.

By turning off individual components or altering the silicon's operating frequency and voltage, these power management support functions are often achieved at the hardware layer. Dynamically configuring such power profiles via the ACPI standard interfaces requires specialised control software, such as governors. To lessen the environmental impact of duplicated core and transit nodes and parts, however, some standby modes might be investigated. In addition to managing TCP connections as well as UDP data flows, as well as responding to application messages, an NCP is assumed to manage ARP, ICMP, DHCP, also other low-level network presence responsibilities for a network host. An NPC can be implemented as a functional addition to a network interface, an Ethernet switch, a third-party server, or any other type of equipment close to sleeping hosts. The study and development of specialised techniques for preserving connection and device presence in the network while maintaining extremely low energy for redundant hardware and/or connections states will be the focus of future research [4].

Although recent attempts have been made to enable smoother functioning in the context of forced disconnectedness, the design of the Internet still mainly presupposes constant connectivity. The architectural elements needed to provide selective connectivity—where a host may choose to be "connected" or "disconnected"—are examined in this study. Our reasoning is based on the need to allow hosts to sleep in order to save energy without compromising their position in the network. We look at concepts such as soft state, host-based control, assistants, and application primitives. This article describes the assumption made by the existing network design that hosts would maintain IP connection over extended periods of time. It also demonstrates the fact that contemporary networks do endure a lot of "chatter" when the majority of hosts are not in use. The paper introduces many novel architectural elements and abstractions to achieve this while preserving a host's network status. The concept asks for the creation of generic primitives that might be utilised by various applications to be able to offer assistants control over a variety of network activities [5].

3. PROPOSED SYSTEM

The system suggests using a processing system with many parallel pipelines. Modern packet processing engines, which frequently consist of a number of concurrent pipelines to "divide and conquer" the amount of incoming traffic, were the subject of this work. The work load is divided across several parallel pipeline systems in this system.

The current generation SR designs fully parallelize the packet forwarding operation across the active cores, allowing them to take full use of multi-core hardware platforms. The router's packet processing engine's cores function as parallel pipelines. The cores are specifically committed to handling incoming packets, processing layer 2 and layer 3 headers (including procedures with relation to looking up IP addresses), also broadcasting them onto the allocated output ports. The execution of identical instances of the same software running on all cores is what makes all of these processes possible. We concentrated on cutting-edge packet processing engines, Pipes are usually the most energy-intensive components of network devices and are frequently constructed comprising a variety of simultaneous pipelines to "divide and conquer" the weight of incoming information. Maximizing the trade-off between energy utilisation moreover, network performance measures is the objective, we set out to regulate both the power configuration of pipelines and the most effective method of allocating traffic flows among them.

The results show that the suggested optimization technique offers intriguing amounts of power savings. The results were achieved using a lot of multi core SRs plus data on real link traffic. The system put out a cutting-edge analytical model that could reflect the effect of power management tools on network performance indicators. The analytical methodology takes into account packet-level stochastic incoming traffic with LRD features. The validation findings show how the suggested model can accurately describe performance indexes that are network- and energy-aware by combining Linux-based SR with AR and LPI primitives and actual traffic traces.

Also, a model-based optimization method has been suggested and empirically assessed. According to the findings, this approach can save more than 16–17% more energy than using a device with solely LPI capability. In order to comprehend the implications of the suggested optimization policy and the function of the tradeoff parameter in the multiple pipeline situation, the system evaluates further test results in this part. On the other hand, the load balancer tries to pack as much traffic volume into a small number of pipelines as feasible when the system is trying to reduce a specific threshold for the maximum latency times' power usage.

Given that the errors are less than 0.1% for loss probability also less than 2% for latency times, the findings demonstrate that the suggested AM accurately depicts network-aware performance indexes as well. The complexity of the AM and the execution timings depend linearly on the buffer size N, and neither ever go over 150 ms. the

following is a list of the several benefits of the suggested approach:

- It controls the volume of input traffic.
- The work load is divided among many tubes in this system to reduce energy usage.




Fig 1: System Architecture

The design for the parallel pipeline method for packet processing is depicted in Fig. 1 above. To reduce energy consumption when processing segmented packets, many pipe lines are built. Aggregating the results received by the multiple pipeline where packets are arranged according to packet id. A pipeline is a series of processing components, or co-routines, organised so that each component's output serves as the subsequent component's input; The name makes reference to a real pipeline. Between neighbouring portions, some buffering is frequently provided. These pipelines often transport streams of records, bytes, or bits of data, and the pipeline elements may be thought of as filters; this is also recognized as the pipes and filters design pattern. Function composition is similar to connecting components in a pipeline. Although the term "pipeline" is occasionally used to refer to more broad flows, a pipeline is linear and one-directional. In the lexer hack, for instance, a pipeline that is largely one-directional may have some communication going in the opposite direction termed as a return channel or backchannel, or a pipeline may be totally bi-directional. Since they lack cycles and operate similarly to (linear) pipelines, Unofficially, pipelines are flows with directed acyclic graph and one-directional tree topologies.




Fig 2: Flow Diagram

The flow diagram in Fig. 2 above clearly demonstrates how packets are processed in various pipe lines. Input work load is divided into several packets and stored in a separate pipeline queue during the first phase of the flow. The packets are then taken from each pipeline's queue. The queue size determines how a pipeline is processed. The aggregate of packets is the final flow. We made the decision to concentrate on packet processing engines, which are often the most demanding parts of high-end routers as well as other network devices. The traffic burden coming in from several high-speed ports is divided and conquered using packet processing engines. They frequently feature extremely parallel designs and are achieved using heterogeneous hardware, such as traditional application-specific integrated circuits or field programmable gate array chips. Serializer/Deserializer buses (Ser Des), which can be implemented using a variety of standards, are used to transport the traffic into and out of the engine. The following details should be understood to be for informative purposes only and not as legal advice. This element can be added to alternatively

install the interface cards before the SerDes bus, using the same packet processing engine. Moreover, line-card-based packet processing engines with a large number of parallel pipelines might erroneously believe that each pipeline can independently alter its rate also that any subset of the pipelines can handle all incoming frames.

4. RESULTS

The acquired findings illustrate how the suggested model may accurately describe the performance indices that are given in the images below that are energy- and network-aware. Also, a model-based optimization method has been suggested and empirically assessed. The process tries to deal with incoming traffic volumes and fulfil network performance requirements while dynamically modifying the configuration of the energy-aware device to decrease energy usage. Statistics regarding network energy requirements and the associated carbon footprint were supplied by telecom operators, Internet service providers, as well as government entities, revealing a worrisome and escalating trend.




Fig 3: Energy Consumption




Fig 4: Data Rate




Fig 5: Busy-Idle Cycle




Fig 6: PGF

5. CONCLUSION

So as to understand the effect of power management skills on network performance measures, this research suggests a unique analytical approach. It takes into account incoming traffic that is stochastic and has LRD features at the packet level, and it makes parameter selections to maximise the intended trade-off between energy consumption along with QoS while enforcing the fulfilment of predetermined upper bounds on both. A Linux-based open source router with AR and LPI primitives was used to empirically test the model using traffic produced by real-world traces. The best possible trade-off between energy use and network performance indicators must be made, it was necessary to regulate both the power configuration of pipelines and the most effective method of distributing traffic flows among them.

REFERENCE

[1] R. Bolla, R. Bruschi, A. Carrega, F. Davoli, D. Suino, C. Vassilakis, and A. Zafeiropoulos, "Cutting the energy bills of Internet service providers and telecoms through power management: an impact analysis," Comput. Netw., vol. 56, no. 10, pp. 2320–2342, 2012.

[2] C. Bianco, F. Cucchietti, and G. Griffa, "Energy consumption trends in the next generation access network—a telco perspective," in *Proc. 29th INTELEC*, Rome, Italy, Sep.–Oct. 2007, pp. 737–742.

[3] The Climate Group—GeSI, "SMART 2020: Enabling the low carbon economy in the information age," 2008 [Online]. Available: http://www.smart2020.org/_assets/files/02_Smart2020Report.pdf

[4] S. Nedevschi, L. Popa, G. Iannaccone, S. Ratnasamy, and D.Wetherall, "Reducing network energy consumption via sleeping and rate-adaptation," in *Proc. 5th USENIX NSDI*, San Francisco, CA, USA, 2008, pp. 323–336.

[5] R. Bolla, F. Davoli, R. Bruschi, K. Christensen, F. Cucchietti, and S. Singh, "The potential impact of green technologies in next-generation wireline networks: Is there room for energy saving optimization?," *IEEE Commun. Mag.*, vol. 49, no. 8, pp. 80–86, Aug. 2011.

[6] R. Bolla, R. Bruschi, F. Davoli, and F. Cucchietti, "Energy efficiency in the future Internet: A survey of existing approaches and trends in energy-aware fixed network infrastructures," *IEEE Commun. Surveys Tut.*, vol. 13, no. 2, pp. 223–244, 2nd Quart., 2011.

[7] L. Chiaraviglio, M. Mellia, and F. Neri, "Minimizing ISP network energy cost: Formulation and solutions," *IEEE/ACM Trans. Netw.*, vol. 20, no. 2, pp. 463–476, Apr. 2012.

[8] R. Tucker, R. Parthiban, J. Baliga, K. Hinton, R. Ayre, and W. Sorin, "Evolution of WDM optical IP networks: A cost and energy perspective," *J. Lightw. Technol.*, vol. 27, no. 3, pp. 243–252, Feb. 2009.

[9] D. Neilson, "Photonics for switching and routing," *IEEE J. Sel. Topics Quantum Electron.*, vol. 12, no. 4, pp. 669–678, Jul.–Aug. 2006.

[10] Netlogic, Irvine, CA, USA, "The Netlogic XLP processor family," [Online]. Available: http://www.netlogicmicro.com/Product/MultiCore/XLP.asp

[11] "The NetFPGA Project," [Online]. Available: http://www.netfpga.org

[12] S. Han, K. Jang, K. Park, and S. Moon, "PacketShader: A GPU-accelerated software router," in *Proc. ACM SIGCOMM*, New Delhi, India, Aug.–Sep. 2010, vol. 40, pp. 195–206.

[13] Z. Yi and P. Waskiewicz, "Enabling Linux network support of hardware multiqueue devices," in *Proc. Linux Symp.*, Ottawa, ON, Canada, Jun. 2007, vol. 2, pp. 305–310.

[14] W. Shi, M. MacGregor, and P. Gburzynski, "Load balancing for parallel forwarding," *IEEE/ACM Trans. Netw.*, vol. 13, no. 4, pp. 790–801, Aug. 2005.

[15] H. Tijms, A First Course in Stochastic Models.Chichester,U.K.:Wiley, 2003. [16] B. Doshi, "A note on stochastic decomposition in a queuewith vacations or set-up times,"J. Appl. Probab., vol. 22, no. 2, pp.419–428, Jun. 1985.

[17] H. Kim and N. Shroff, "Loss probability calculations and asymptoticanalysis forfinite buffer multiplexers,"IEEE/ACM Trans. Netw., vol.9, no. 6, pp. 755–768, Dec. 2001.