TASKS SCHEDULING WITH VIRTUAL MACHINES OF THE DEADLINE-AWARE PRIORITY SCHEDULING (DAPS) MODEL INCLOUD COMPUTING

ARVIND KUMAR SINGH
Research Scholar, Department Of Computer Science &Engg. MUIT LucknowDR. MANISH VARSHNEY
Prof. School Of Engineering & Technology, MUIT, Lucknow

Abstract

Cloud Computing suggests to both the applications conveyed as administrations over the Web and the hardware and systems software in the datacenters that give those administrations. The administrations themselves have for quite some time been alluded to as Software as an Administration (SaaS) the datacenter hardware and software is the thing that we will call aCloud at the point when a Cloud is influenced accessible in a compensation as-you-to go way to the overall population, we call it an Open Cloud; the administration being sold is UtilityComputing. The CloudSim toolkit will enable you to design and enhance the policies that will be applied across all of the CloudSim components. As a result, it will be regarded as a useful study tool since it can replicate the complexity that emerges from different settings. In order to conductthe simulation tests, the following setups will be used on a laptop: 2.5 GHz Intel Corei5processor, 4 GB of RAM, and a 512 GB hard drive. We can say that the DAPS model's methodis that tasks are ranked in ascending order based on length priority, and the Virtual Machine's (VM's) state is labeled as successful when the deadline restriction is met. The jobs are then assigned to the appropriate VM while keeping the make span and completion time to a minimum. Results of all experiments revealed that the proposed model performs better other algorithms by lowering makespan while increasing the variety of tasks.

Keywords: *Cloud Computing, Load, balance, task, scheduling, Deadline-Aware Priority Scheduling (DAPS) model, etc*

DOI Number: 10.14704/nq.2022.20.9.NQ44603 Neuro Quantology 2022; 20(9):5226-5231

1. INTRODUCTION

Cloud Computing suggests to both the applications conveyed as administrations over the Web and the hardware and systems software in the datacenters that give those administrations. The administrations themselves have for quite some time been alluded to as Software as an Administration (SaaS) the datacenter hardware and software is the thing that we will call a Cloud at the point when a Cloud is influenced accessible in a compensation as-you-to go way to the overall population, we call it an Open Cloud; the administration being sold is Utility Computing. We utilize the term Private Cloud to allude to inner datacenters of a business or other association, not made accessible to the overall population. Along these lines, Cloud Computing is the total of SaaS and Utility Computing, yet does exclude Private Clouds.

Individuals can be clients or providers of SaaS, or clients or providers of Utility Computing. Cloud computing is another innovation used to offer various types of assistance.

Cloud is partitioned into two significant models in particular, service model and arrangement model. The fundamental three service models are Software as a Service (SaaS), Platform as a Service (PaaS) and Infrastructure as a Service (IaaS). The new four cloud sending models are private cloud, local area cloud, public cloud and half breed cloud. Certain significant difficulties in cloud computing are Security, Cost and Service level understanding. Data Transaction Management (DTM) is one of the challengeable occasions in cloud computing. IaaS is essential to deal with the cloud transaction management.

The data are kept up in the database – as-a-service (DaaS) model. It has databases in cloud environment and gives highlights like data definition, data stockpiling and data recovery. The main cloud computing suppliers like Amazon, Google, IBM, Oracle and Microsoft furnish database – as-a-service with their cloud DaaS arrangements. In Cloud assets are ordinarily flexible, with limitless measure of figure force and capacity accessible on request and pay-just for-what-you-use.

1.1 Load balance awareness in task scheduling

Another significant restriction in cloud settings is load balancing, which has a significant impact on the performance of the task scheduling process. Even during task scheduling process, it is necessary to ensure that the resources are neither overloaded nor under loaded in any way. In addition, because the majority of the resources are expected to be distributed at the same time, the scheduling system must guarantee that all of the resources are balanced in relation to its capacity throughout the allocation process. Due to the fact that the issue is not only overcrowded VMs, but also under loaded idle VMs, this helps to improve resource usage. When virtual machines (VMs) remain in an idle state, it has an impact on the service provider's earnings. As a result, in order to make better use of available resources, an effective load balance aware task scheduling algorithm must be included as a component of the task scheduling methodology. Load balancing may be accomplished in a variety of methods, but in most situations, dynamic load balancing is preferable to static load balancing due to the fact that the cloud computing architecture is entirely real-time oriented. When it comes to dynamic load balancing, there are two options: one is that it may be performed during the task scheduling process, and another is that it can be performed after the task scheduling process.

2. LITERATURE REVIEW

Dr. DiwakarRamanujTripathi (2019) Cloud computing ensures different central focuses for the organization of data-raised applications. One essential assurance is decreased expense with a remuneration as-you-go business show. Another assurance is (all things considered) endless throughput by including workers if the responsibility increases. This paper records elective constructions to affect cloud computing for database applications and reports on the outcomes of a thorough evaluation of existing business cloud benefits that have gotten these plans. The point of convergence of this work is on trade dealing with (i.e., peruse and invigorate jobs), rather than assessment or OLAP jobs, which have as of late got a ton of thought. The results are surprising

in a couple of ways. Most importantly, it gives the idea that each and every huge dealer have accepted a substitute designing for their cloud organizations. Accordingly, the expense and execution of the organizations contrast basically depending upon the responsibility.

Gawali (2018) Modern technology necessitates the use of cloud computing. The scheduling of tasks and the distribution of resources are critical components of cloud computing. This paper proposes a heuristic approach for performing task scheduling and resource allocation that incorporates the modified analytic hierarchy process (MAHP), bandwidth aware divisible scheduling (BATS) + BAR optimization, longest expected processing time preemption (LEPT), and divide-and-conquer methods. Each job is processed prior to being allocated to cloud resources in this technique, which is accomplished through the use of an MAHP process. The resources are assigned utilizing a combined BATS + BAR optimization technique, which takes into account the bandwidth and load of the cloud resources as restrictions while allocating the resources. The suggested system also preempts resource-intensive activities using LEPT preemption, which is an extension of the previous system. When turnaround time and response time are used as performance metrics, the divide-and-conquer approach improves the proposed system, as demonstrated experimentally through comparison with the existing BATS and improved differential evolution algorithm (IDEA) frameworks when the divide-and-conquer approach is used.

Mitrevski et al (2017) Cloud computing is a new appealing term in the IT world. The expression "Cloud Computing" emerges from the thought for incorporating the capacity and calculation in appropriated data. Its drawn out objectives are to give an adaptable, on – request bundle to the cloud client, giving him considerably more opportunity, adaptability and dependability simultaneously, accomplishing the entirety of the above by utilizing a straightforward "utility computing model". It vows to welcome on-request estimating, less IT overhead and a capacity to scale IT here and there rapidly. The focal point of this work tumbles down on transaction processing applications which work in multi – processing and cloud conditions. All significant sellers have embraced an alternate engineering for their cloud dministrations. Therefore, in this paper we will survey some of them and their basic methodologies on improving Cloud Transactions.

QusayKanaanKadhim et al (2017) Cloud computing is the most encouraging current execution of utility computing in the business world, since it gives some critical highlights over exemplary utility computing, for example, flexibility to permit clients progressively increase and scale- down the resources in execution time. In any case, cloud computing is as yet in its untimely stage and encounters absence of normalization. The security issues are the primary difficulties to cloud computing appropriation. Hence, basic ventures like government associations (services) are hesitant to believe cloud computing because of the dread of losing their touchy data, as it lives on the cloud with no information on data area and absence of straightforwardness of Cloud Service Providers (CSPs) systems used to get their data and applications which have made a hindrance against receiving this spry computing worldview. This examination means to audit

and group the issues that encompass the execution of cloud computing which a hot region that should be tended to by future exploration.

Sultan Aldossary (2016) Cloud computing switched the world up us. Presently individuals are moving their data to the cloud since data is getting greater and should be available from numerous gadgets. In this manner, putting away the data on the cloud turns into a standard. Nonetheless, there are numerous issues that counter data put away in the cloud beginning from virtual machine which is intend to share assets in cloud and finishing on cloud stockpiling itself issues. In this paper, we present those issues that are keeping individuals from embracing the cloud and give a review on arrangements that have been done to limit dangers of these issues. For instance, the data put away in the cloud should be private, safeguarding uprightness and accessible. Additionally, sharing the data put away in the cloud among numerous clients is as yet an issue since the cloud specialist organization is dishonest to oversee verification and approval. In this paper, we list issues identified with data put away in cloud stockpiling and answers for those issues which vary from different papers which center around cloud as broad.

ArtanMazreka et al (2016) Cloud Computing is one of the innovations with quick improvement lately where there is expanding interest in industry and the scholarly world. This innovation empowers numerous services and assets for end clients. With the ascent of cloud services number of organizations that offer different services in cloud framework is expanded, accordingly making a rivalry on costs in the worldwide market. Cloud Computing suppliers offer more services to their customers going from infrastructure as a service (IaaS), platform as a service (PaaS), software as a service (SaaS), storage as a service (STaaS), security as a service (SECaaS), test environment as a service (TEaaS). The motivation behind suppliers is to amplify income by their value plans, while the primary objective of clients is to have nature of services (QoS) at a sensible cost. The reason for this paper is to think about and examine a few models and evaluating plans from various Cloud Computing suppliers.

3. OBJECTIVES

- To study Load balance awareness in task scheduling.

- To experiment tasks with various VMs of the DAPS model.

4. RESEARCH METHODOLOGY

4.1 Simulation Tool

An efficient tool for simulating task scheduling in homogeneous and heterogeneous cloud computing environments will be required. This tool should be flexible enough to support this environment while also receiving an increasing number of user requests. The toolkit will be a simulator that operates on an event-driven model and will be hosted in the Java programming language. The CloudSim toolkit will enable you to design and enhance the policies that will be applied across all of the CloudSim components. As a result, it will be regarded as a useful study

tool since it can replicate the complexity that emerges from different settings. In order to conduct the simulation tests, the following setups will be used on a laptop: 2.5 GHz Intel Corei5 processor, 4 GB of RAM, and a 512 GB hard drive.

4.2 Datasets

The datasets that will be used in the cloud computing environment vary depending on the applications that are being utilized. It will be utilized in this research to create two types of datasets the first, which will be obtained from the NASA site for research, and the second, which will be taken by utilizing the CloudSim toolkit, which will generate the dataset.

4.3 Proposed Models

The Deadline-Aware Priority Scheduling (DAPS) model will be the first of the scheduling models. As a result of this model, tasks will be planned and assigned to appropriate resources in order to decrease the amount of time required to complete them under the deadline constraintand to reduce the minimum completion time. When we will be developing an efficient task scheduling model, one of the variables that must be taken into consideration is the level of happiness that users have with the system. The technique will pertain to a concentration on scheduling activities based on a deadline restriction, and as a result, the deadline will be considered to be the time required to complete the work.

5. RESULT AND DISCUSSION

Tasks were produced and separated into groups of 250, 500, 1000, 1500, and 2000 tasks, with each block consisting of 500 tasks. For the purpose of evaluating the proposed DAPS model, we employed the following metrics: the average of makespan, the average of total average response time, resource utilisation, guarantee ratio, and the amount of breaches for the DAPS model, as explained in Table 1.

Table 1: Experiments done for tasks with various VMs of the DAPS model

Experiments	No. ofVMs	No. oftasks	Average makespan	Mean of totalaverageRT	Resource utilization	Guaranteeratio	No. ofviolations	Violation ratio
1	6	250	262818	34490	5621	0.992	2	0.8%
2	8	500	380478	45741	8403	0.99	5	1%
3	10	1000	568431	73229	14355	0.989	11	1.1%
4	12	1500	696511	88045	18389	0.992	12	0.8%
5	14	2000	716719	85337	19747	0.992	16	0.8%

5.1 Performance Assessment

In comparison to existing scheduling algorithms, the suggested DAPS model provides a better task scheduling approach based on a deadline constraint. The DAPS model employed a varietyof performance measures to reduce the average makespan and the number of tasks that were violated at the same time. Throughout this chapter, the following five experiments were investigated in order to assess the overall quality and reliability of the suggested DAPS model:

i. 250 tasks with six VMs.

ii. 500 tasks with eight VMs.

iii. 1000 tasks with ten VMs.

iv. 1500 tasks with twelve VMs.

v. 2000 tasks with fourteen VMs

Using measures such as average of makespan, average of total average response time, average of total average response time, resource utilisation, guarantee ratio, amount of violations and violation ratio, we evaluate our results DAPS model to the GA, Min-Min, SJF, and Round Robin algorithms.One of the most important criteria and the goal of the proposed DAPS model is to reduce the makespan, which refers to the total time it takes for all tasks within a virtual machine to be completed. As shown in Table 2, the suggested DAPS model surpassed other algorithms by determining the overall makespan while increasing the number of tasks when compared to GA, Min-Min, SJF, and Round Robin algorithms. The results of all experiments revealed that the proposed model performs better other algorithms by lowering makespan while increasing the variety of tasks.

Table 2: Average of makespan of DAPS, GA, Min-Min, SJF and Round Robin algorithms

Experiments		Averagemakespan				
No.of tasks	**No.of VMs**	**DAPS**	**GA**	**Min-Min**	**SJF**	**RoundRobin**
250	6	262818	305004	280130	307421	323316
500	8	380478	430264	422428	440850	474695
1000	10	568431	626303	598599	645316	630876
1500	12	696511	763337	733366	785707	751648
2000	14	716719	795613	760132	814443	826665

Figure 1 the X-axis represents the number of tasks, and the Y-axis represents the rise of the average makespan over time. When compared to existing algorithms, the suggested DAPS model has achieved a shorter average makespan in all of the trials conducted.



Figure 1: Contrasting of average makespan

Our proposed DAPS model improves the makespan ratio by 10%, 6%, 12%, and 12.7 percent when compared to GA, Min-Min, SJF, and Round Robin algorithms, respectively. In addition, the T-test was used to compare our suggested DAPS model to other algorithms such as GA, Min-Min, SJF, and Round Robin in a statistical study.

6. CONCLUSION

We can say that the DAPS model's method is that tasks are ranked in ascending order based on length priority, and the Virtual Machine's (VM's) state is labeled as successful when the deadline restriction is met. The jobs are then assigned to the appropriate VM while keeping the make span and completion time to a minimum. The DAPS model aims to achieve the optimum performance by lowering metrics like

average makespan, mean of total average reaction time, number of violations, and violation ratio in order to achieve user satisfaction. In addition, the DAPS model aims to maximize resource usage and guarantee ratio when the user is primarily concerned with the cost of completing tasks, which includes the cost of processing, memory, bandwidth, and storage depending on the budget constraint.

REFERENCES

[1]. Gagandeep Kaur (2021). Framework for Resource Management in Cloud Computing. 10.1007/978-981-15-7062-9_3.

[2]. Shaw, Rachael (2021),” Applying machine learning towards automating resource management in cloud computing environments”,

[3]. Harvinder Singh et al (2020),” Cloud Resource Management: Comparative Analysis and Research Issues”, International Journal of Scientific & Technology Research Volume 9, Issue 06

[4]. MohdAmeen Imran et al (2020),” Log as a Secure Service Scheme (LASS) for Cloud”, Journal of Scientific Research

[5]. Singh, Saurabh, Young-SikJeong, and Jong Hyuk Park. "A survey on cloud computing security: Issues, threats, and solutions." Journal of Network and Computer Applications 75 (2016): 200-222.

[6]. Gao, Yue, et al. "An energy and deadline aware resource provisioning, scheduling and optimization framework for cloud systems." Hardware/Software Codesign and System Synthesis (CODES+ ISSS), 2013 International Conference on. IEEE, 2013:1-10.

[7]. Dong, Ziqian, Ning Liu, and Roberto Rojas-Cessa. "Greedy scheduling of tasks with time constraints for energy-efficient cloud-computing data centers." Journal of Cloud Computing 4.1 (2015): 1-14.

[8]. Xu, Minxian, WenhongTian, and RajkumarBuyya. "A survey on load balancing algorithms for virtual machines placement in cloud computing." Concurrency and Computation: Practice and Experience 29.12 (2017):1-20.

[9]. Deldari, Arash, Mahmoud Naghibzadeh, and SaeidAbrishami. "CCA: a deadline-constrained workflow scheduling algorithm for multicore resources on the cloud." The journal of Supercomputing 73.2 (2017): 756-781.

[10]. Singh, Sukhpal, Inderveer Chana, and Maninder Singh. "The Journey of QoSAware Autonomic Cloud Computing." IT Professional 19.2 (2017): 42-49.

[11]. Panda, Sanjaya K., Indrajeet Gupta, and Prasanta K. Jana. "Task scheduling algorithms for multi-cloud systems: allocation-aware approach." Information Systems Frontiers (2017): 1-19.